

SITOP PSU400M/DC/DC/600V/24V/20A

SITOP PSU400M 20 A DC/DC converter input: 600 V DC output: 24 V DC/20 A

Input	
type of the power supply network	DC voltage
supply voltage at AC <ul style="list-style-type: none"> initial value 	startup from 340 V DC; derating necessary at 300 ... 400 V DC and 824 ... 900 V DC
supply voltage <ul style="list-style-type: none"> at DC 	600 ... 600 V
input voltage <ul style="list-style-type: none"> at DC 	300 ... 900 V
overvoltage overload capability	Shutdown at $V_{in} > 900$ V DC
input current <ul style="list-style-type: none"> at DC at rated input voltage 600 V 	0.85 A
current limitation of inrush current at 25 °C maximum	8 A
I ² t value maximum	0.02 A ² ·s
fuse protection type	yes, cut-off capacity 20 kA; L/R < 2 ms ("+" and "-" input)
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	24 V
output voltage <ul style="list-style-type: none"> at output 1 at DC rated value 	24 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage <ul style="list-style-type: none"> on slow fluctuation of input voltage on slow fluctuation of ohm loading 	0.3 % 0.3 %
residual ripple <ul style="list-style-type: none"> maximum typical 	150 mV 30 mV
voltage peak <ul style="list-style-type: none"> maximum typical 	200 mV 100 mV
adjustable output voltage	24 ... 28.8 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer; max. 480 W
display version for normal operation	Green LED for 24 V OK, green flashing LED for start delay
type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A; 30 V DC/1 A) for 24 V OK
behavior of the output voltage when switching on	No overshoot of V _{out} (soft start)
response delay maximum	0.1 s; 10 s adjustable using switch
voltage increase time of the output voltage <ul style="list-style-type: none"> maximum 	150 ms
output current <ul style="list-style-type: none"> rated value rated range 	20 A 0 ... 20 A; +60 ... +70 °C: Derating 5.5%/K
supplied active power typical	480 W
short-term overload current <ul style="list-style-type: none"> on short-circuiting during the start-up typical at short-circuit during operation typical 	40 A 60 A
duration of overloading capability for excess current <ul style="list-style-type: none"> on short-circuiting during the start-up at short-circuit during operation 	150 ms 25 ms
constant overload current	

<ul style="list-style-type: none"> on short-circuiting during the start-up typical 	23 A
product feature	
<ul style="list-style-type: none"> bridging of equipment 	Yes; switchable characteristic
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	95 %
power loss [W]	
<ul style="list-style-type: none"> at rated output voltage for rated value of the output current typical 	25 W
Closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	1.5 %
relative control precision of the output voltage load step of resistive load 50/100/50 % typical	1.5 %
setting time	
<ul style="list-style-type: none"> load step 50 to 100% typical 	1 ms
<ul style="list-style-type: none"> load step 100 to 50% typical 	1 ms
setting time	
<ul style="list-style-type: none"> maximum 	5 ms
Protection and monitoring	
design of the overvoltage protection	< 33 V
<ul style="list-style-type: none"> typical 	22 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Alternatively, constant current characteristic approx. 22 A or latching shutdown
enduring short circuit current RMS value	
<ul style="list-style-type: none"> typical 	22 A
overcurrent overload capability in normal operation	overload capability 150 % I _{out} rated up to 5 s/min
display version for overload and short circuit	LED yellow for "overload", LED red for "latching shutdown", red LED flashing for "Overtemperature"
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Protective extra low output voltage V _{out} according to EN 60950-1 and EN 50178
operating resource protection class	Class I
protection class IP	IP20
Approvals	
certificate of suitability	
<ul style="list-style-type: none"> CE marking 	Yes
<ul style="list-style-type: none"> UL approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
<ul style="list-style-type: none"> CSA approval 	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
<ul style="list-style-type: none"> cCSAus, Class 1, Division 2 	No
<ul style="list-style-type: none"> ATEX 	No
certificate of suitability	
<ul style="list-style-type: none"> IECEX 	No
<ul style="list-style-type: none"> NEC Class 2 	No
<ul style="list-style-type: none"> ULhazloc approval 	No
<ul style="list-style-type: none"> FM registration 	No
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> EAC approval 	Yes
<ul style="list-style-type: none"> C-Tick 	No
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	DNV GL
Marine classification association	
<ul style="list-style-type: none"> American Bureau of Shipping Europe Ltd. (ABS) 	No
<ul style="list-style-type: none"> French marine classification society (BV) 	No
<ul style="list-style-type: none"> DNV GL 	Yes
<ul style="list-style-type: none"> Lloyds Register of Shipping (LRS) 	No
<ul style="list-style-type: none"> Nippon Kaiji Kyokai (NK) 	No
EMC	
standard	

<ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	EN 55022 Class A (emission) - EN 61000-6-2
environmental conditions	
ambient temperature <ul style="list-style-type: none"> • during operation • during transport • during storage 	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection <ul style="list-style-type: none"> • at input • at output • for auxiliary contacts 	screw-type terminals DC input, +, -, PE: 1 screw terminal each for 0.2 ... 6/4 mm ² single-core/finely stranded +, -: 2 screw terminals each for 0.2 ... 6/4 mm ² single-core/finely stranded Alarm signals: 2 screw terminals for 0.14 ... 1.5 mm ² single-core/finely stranded
width of the enclosure	90 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing <ul style="list-style-type: none"> • top • bottom • left • right 	50 mm 50 mm 0 mm 0 mm
net weight	1.2 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
mechanical accessories	Device identification label 20 mm × 7 mm, pale turquoise 3RT1900-1SB20
MTBF at 40 °C	622 277 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

