

SITOP UPS500P/DC/24VDC/7A/10KWS/IP65

***** spare part ***** SITOP UPS500P maintenance-free uninterruptible power supply with USB interface basic device 10 kW input: 24 V DC output: 24 V DC/7 A degree of protection IP65



input	
supply voltage at DC rated value	24 V
input voltage	DC 22.5 ... 29 V
adjustable response value voltage for buffer connection preset	22.5 V
adjustable response value voltage for buffer connection	permanently set
input current at rated input voltage 24 V rated value	7 A; + approx. 2 A with empty energy storage (capacitor)
memory	
type of energy storage	with capacitors
design of the mains power cut bridging-connection	7 A for 49 s or 5 A for 68 s or 3 A for 108 s or 1 A for 351 s
buffering time in the event of power failure	0.82 min
energy content of energy storage	10 kW.s
output	
output voltage	
• in normal operation at DC rated value	24 V
• in buffering mode at DC rated value	24 V
formula for output voltage	$24\text{ V} \pm 3\%$
startup delay time typical	0.6 s
voltage increase time of the output voltage typical	25 ms
output voltage in buffering mode at DC	24 ... 24.7 V
output current	
• rated value	7 A
• in normal operation	0 ... 7 A
• in buffering mode	0 ... 7 A
peak current	22.5 A
charging current	2 A, permanently set
power loss	
efficiency in percent	
• at rated output voltage for rated value of the output current typical	96.5 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	5.2 W
supplied active power typical	168 W
protection and monitoring	
product function	
• reverse polarity protection against energy storage unit polarity reversal	Yes
• reverse polarity protection against input voltage polarity reversal	Yes
display version	
• for normal operation	Normal operation: LED green (OK); Lack of buffer standby: LED red (ALARM);

<ul style="list-style-type: none">in buffering mode	Energy storage > 85%: LED green (CAP. > 85%) Buffered mode: LED yellow (BAT); Prewarning buffer end after expiry of 80% of the available buffer time: LED red (ALARM); Energy storage > 85%: LED green (CAP. > 85%)
interfaces	
product component PC interface	Yes
product function communication function	No
design of the interface	USB
safety	
galvanic isolation between input and output	No
operating resource protection class	Class III
protection class IP	IP65
standard <ul style="list-style-type: none">for emitted interferencefor interference immunity	EN 55022 Class B EN 61000-6-2
standards, specifications, approvals	
certificate of suitability <ul style="list-style-type: none">CE markingUL approvalEAC approval	Yes No Yes
MTBF at 40 °C	500 000 h
standards, specifications, approvals marine classification	
shipbuilding approval	No
Marine classification association <ul style="list-style-type: none">Det Norske Veritas (DNV)	No
ambient conditions	
ambient temperature <ul style="list-style-type: none">during operationduring transportduring storage	0 ... 55 °C; with natural convection -40 ... +70 °C -40 ... +70 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
mechanical data	
type of electrical connection <ul style="list-style-type: none">at inputat output	Plug-in connection via connector set via connector set
design, dimensions and weights	
width × height × depth of the enclosure	470 × 80 × 80 mm
installation width × mounting height	600 × 80 mm
required spacing <ul style="list-style-type: none">leftright	0 mm 0 mm
fastening method <ul style="list-style-type: none">standard rail mountingS7 rail mountingwall mounting	Screw mounting No No Yes
housing can be lined up	No
net weight	2.2 kg
accessories	
electrical accessories	Connector set
further information internet links	
internet link <ul style="list-style-type: none">to website: CAX-Download-Managerto website: Industry Online Support	http://www.siemens.com/cax https://support.industry.siemens.com
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial security concept. Siemens' products and solutions constitute

one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit <https://www.siemens.com/industrialsecurity>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under <https://www.siemens.com/cert>. (V4.6)

Classifications

	Version	Classification
eClass	12	27-04-07-05
eClass	9.1	27-04-07-05
eClass	9	27-04-07-05
eClass	8	27-04-06-90
eClass	7.1	27-04-06-90
eClass	6	27-04-06-90
ETIM	9	EC000382
ETIM	8	EC000382
ETIM	7	EC000382
IDEA	4	4149
UNSPSC	15	39-12-10-11

Approvals Certificates

General Product Approval

[Manufacturer Declaration](#)

[Declaration of Conformity](#)



last modified:

12/1/2023