

product type designation



Power Supply PS791-1PRO

***** spare part ***** power supply PS 791-1PRO, AC/DC power supply unit, 10 W, IP65 (-20 ... +50 °C), input: 90 ... 265 V AC, output: 24 V DC, metal enclosure; scope of delivery: AC power 3+PE cable connector, DC power cord M12 for direct connection to SCALANCE W-700 PRO and SCALANCE X-200 PRO, mounting hardware, operating instructions German/English,

type of current supply	10 W, input: 90-265 V, output: 24 V DC
electrical data / input	
supply voltage / at AC	90 ... 265 V
buffering time / for rated value of the output current / in the event of power failure / minimum	20 ms; at full load, 25 °C
line frequency	47 ... 63 Hz
electrical data / output	
output voltage / at DC / rated value	24 V
relative symmetrical tolerance / of the output voltage	7 %
output current	
• rated value	0.42 A
supplied active power / typical	10 W
electrical data / closed-loop control	
switching frequency	100 kHz
interfaces	
type of electrical connection	
• at input	AC power 3+PE cable connector for AC 100-240 V supply
• at output	M12 plug PRO or power cord M12 for DC 24 V output voltage
operator element version	On/Off switch
design, dimensions and weights	
width	125 mm
height	60 mm
depth	130 mm
net weight	0.7 kg
ambient conditions	
ambient temperature	
• during operation	-20 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP65
standards, specifications, approvals	
standard	
• for safety / from CSA and UL	EN 60950
Marine classification association	
• French marine classification society (BV)	Yes
MTBF	68.4 a; at full load, 25 °C
• reference temperature	25 °C
• percental operating load	100 %

further information / internet links

internet link

- to web page: selection aid TIA Selection Tool <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAX-Download-Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

12/18/2020 