

HIGH PRECISION ELECTROCHEMICAL NO₂ GAS SENSOR BREAKOUT



DESCRIPTION

Ensure a safe and healthy environment with our High-Precision Electrochemical NO₂ Gas Sensor Breakout. This advanced sensor module detects nitrogen dioxide (NO₂) with exceptional accuracy, making it ideal for various applications, from industrial monitoring to environmental studies.

The breakout board works with both 3.3V and 5V power supplies. The EasyC connector provides a fast and easy connection with the microcontroller board. The board provides both analog and digital output with integrated ADC. The analog front end is fully programmable with I2C communication.

This breakout board is perfect for industrial safety, environmental monitoring, and research projects and provides a reliable foundation for precise gas detection solutions. Integrate this sensor into your systems to ensure timely alerts and maintain optimal safety standards.

FEATURES

- Accurately measures NO₂ levels, providing reliable data for various applications.
- Compatible with microcontrollers like Arduino and Raspberry Pi, featuring an I²C interface for straightforward communication and data acquisition.
- Four mounting holes for secure and easy installation.
- Built to withstand various environmental conditions, ensuring long-term reliability.
- Connectors: easyC
- Detects/Measure: Nitrogen dioxide (NO₂)
- Detection Range: 0-30 ppm
- Sensor output signal: 600 nA/ppm
- Operating Voltage: 5V on header (3.3V easyC)

- Dimensions: 38 mm x 38 mm / 1.5" x 1.5"

USEFUL LINKS

TIPS

By integrating the sensor with the appropriate electronic circuits and microcontrollers, such as Arduino or Raspberry Pi, you can create systems that monitor and analyze the concentration of gas in real-time. This capability allows you to take necessary actions promptly to maintain a healthy and safe environment. Enhance your gas detection capabilities with this high-precision NO₂ sensor breakout, ensuring timely alerts and optimal safety in your monitoring systems.

OTHER IMAGES



