

SNCA-PS24-4

An indoor power supply with one 4 Amp 24V AC fused output.



Overview

Key feature: Ideal for powering 24V AC housings and the camera. This power supply must be used when a camera is in a housing of any type (dome or fixed).

This power supply is to be used with housings and camera combinations only. Please use either SNCA-PS12-1 or SNCA-PS24-1 for other cameras

SNCA-HFIXED

SNCA-HRZ25

SNCA-HRZ30

SNCA-HRX550/EXT

SNCA-HRX550/EXT/W

SNCA-HRX550/EXT/R

SNCA-HRX550/INT

SNCA-HRZ50/EXT

SNCA-HRZ50/EXT/W

SNCA-HRZ50/EXT/R

SNCA-HRZ50/INT

Supply Voltage: 230V AC 50Hz

Input connection: Internal connection, no cable supplied

Current Consumption: Approx. 100W

Colour: White

Size in mm (W x H x D): 118 x 200 x 70

Weight in Kg: 2.1

Packed Size in mm (W x H x D): 124 x 208 x 76

Packed Weight (Kg): 2.2

Case Material: Powder coated Mild Steel

Operating Temperature: -10°C to +40°C

Storage Temperature: -20°C to +50°C

Environmental Class: 2 (indoor use only)

MTBF: 65,000 hours

CE approved: Yes

Output Voltage: 24V AC

Output Current: 4A (fused)

Output connection: Internal connection, no cable supplied

Tamper Switch: No

Accessories

Housings

SNCA-HRX550/EXT12V

SNCA-HRX550/EXT12V

Robust, IP66 rated dome housing for Sony PTZ cameras



SNCA-HRX550EXT

Outdoor dome camera housing



SNCA-HRX550EXT/W

Outdoor wireless dome camera housing



UNI-OPL7C3

Outdoor Pressurized dome camera housing

Other Accessories



SCA-M30

High quality, ceiling microphone for IP security cameras.



SCA-S30

High quality active outdoor loudspeaker for use with Sony's IP cameras

Pan Tilt Zoom



SNC-EP521

Standard Definition (PAL) PTZ Network Camera



SNC-EP550

720p/30 fps PTZ Camera - E Series



SNC-EP580

1080p/30 fps PTZ Camera - E Series



SNC-ER521

Standard Definition (PAL) Rapid Dome Network Camera



SNC-ER550

720p/30 fps Rapid Dome Camera - E Series



SNC-ER580

1080p/30 fps Rapid Dome Camera - E Series