



## Sparkle Power Inc.

A Leading Power Supply Manufacturer  
Web site: [www.sparklepower.com](http://www.sparklepower.com)

### SPI100F4BN

**(Active PFC, RoHS Compliant)**

**100 Watts Flex ATX Switching Power Supply**

#### Features

- Complied with Flex ATX and ATX12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CUL/UL60950-1 2ND, TUV EN60950-1 2ND, NEMKO EN60950-1 2ND (CB Report) CE

#### Input Characteristics

**Input Range:** 90 ~ 264Vac (RMS), Full Range Input

**Frequency:** 47 ~ 63Hz

**Input Current:** Max 3A (RMS) @ 115Vac, 1.5A (RMS) @ 230Vac

**Inrush Current:** No damage.

#### Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.3A	3A	6.0A	± 5%	± 1%	50mV P-P
+5V	0.3A	4A	8.0A	± 5%	± 1%	50mV P-P
+12V	1.0A	2A	4.0A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.15A	0.3A	± 10%	± 1%	120mV P-P
+5Vsb	0.0A	1.0A	2.0A	± 5%	± 1%	50mV P-P

\*+3.3V and +5V total output not exceed 50W

\* Total output for this subject power supply is 100W



#### Specification

- **Temperature Range:** Operating: 0°C ~ +50°C; storage & shipping: -20°C ~ +80°C
- **Humidity:** 85% on operating, 95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 1 second
- **Efficiency:** 70% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 150x81.5x40.5mm / 6x3.2x1.6inch

#### **Sparkle Power Inc.**

##### **Main Office**

1000 Rock Avenue  
San Jose, CA 95131  
TEL: 408-519-8888  
FAX: 408-519-9999  
E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

#### **Sparkle Power Inc.**

##### **Los Angeles Office**

17071 Green Drive  
City of Industry, CA 91745  
TEL: 626-839-7180  
FAX: 626-839-3395