



Main

Range	Square D X Series
Product or Component Type	Sensor
Device Application	Control
Device presentation	Mechanism with fixing frame
Aesthetic name	X Series
Number of gangs	1 gang
Number of poles	1

Complementary

Switch Function	1-way
Sensor Type	PIR Humidity sensor Light level sensor
[Ie] rated operational current AC	10 A
[Ue] rated operational voltage	120 V
Network type	AC
Network Frequency	60 Hz
Load type	Halogen 0...500 W Incandescent 0...500 W Dimmable LED 0...150 W Fan motor 2.5 A
Maximum Horse Power Rating	0.25 hp
Mounting Mode	By screws
Device mounting	Flush
Material	Plastic strap Metal fixing frame
Color	White
Surface Finish	Matte
Marking	LIGHT-FAN
Width	1.69 in (43 mm)
Height	4.06 in (103 mm)
Quantity per Set	1 piece

Environment

Product Certifications	CULus ICES-003
Standards	UL 1917

Ordering and shipping details

Category	09933-WD SENSORS
Discount Schedule	DE9
GTIN	785901549734
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.17 in (10.6 cm)
Package 1 Width	2.44 in (6.2 cm)
Package 1 Length	2.56 in (6.5 cm)
Package 1 Weight	6.10 oz (173.0 g)
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.45 in (11.3 cm)
Package 2 Width	5.39 in (13.7 cm)
Package 2 Length	12.60 in (32.0 cm)
Package 2 Weight	4.10 lb(US) (1.861 kg)
Unit Type of Package 3	PAL
Number of Units in Package 3	1920
Package 3 Height	47.24 in (120.0 cm)
Package 3 Width	39.37 in (100.0 cm)
Package 3 Length	47.24 in (120.0 cm)
Package 3 Weight	884.13 lb(US) (401.035 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: carbon black, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 year
----------	--------