standexelectronics.com



Datasheet

S12-AH5-5VP21 Analog Hall Sensor

- Analog hall, 2.5V offset
- > 5.0 mV/G gain
- > 5V input voltage
- Stainless 12x1mm x 35mm housing
- Free end PVC 22 AWG wires (1 foot length)



CUSTOMER FOCUSED ENGINEERING + MODULAR DESIGN -



HOUSING - Aluminum, stainless steel, plastic, threaded, flange mount, customer specific

ELECTRICAL - Every sensor function available in various electrical options (NPN, PNP, TTL, etc.) **CONNECTION -** Deutsch, Amphenol, many other brands, free end wires, pigtails, any length

Need a Custom Sensor Solution?... Send us your application specific requirements at <u>sensorso.com</u>

Analog Output Proportional to Field Strength, Gap or Height



Type - AH

DESCRIPTION

- The AH5 Analog Hall Sensor provides an analog output that changes in relation to the magnetic field strength perpendicular to the sensor's face. These sensors are polarity sensitive.
- No field present provides a 2.5V output (offset voltage), this output changes by 5.0 mV per gauss (gain).
- The Ratiometric version (-5V) has an output voltage proportional to the supply voltage. A regulated version (-RG) is available.
- For resolving the height, position, and movement of external magnets, the amplitude of current traveling down a conductor, the magnitude of field present in an electro- coil, etc.

FEATURES

- Low Cost, Potted and Sealed
- Radiometric or Regulated
- Shock & Vibration Resistant
- Solid State (Nothing to wear out!)
- Infinite Resolution





Datasheet

standexelectronics.com

S12-AH5-5VP21 Analog Hall Sensor

We also offer analog output Hall Effect sensors with several different offset voltages and gains. PAH and PAM sensors are also available programmed to your application. Contact us or check our website to see other Analog Hall sensors.

Note: Check our website or contact us to discuss all of our magnetic speed, count, and position detection sensors.

Electrical Specifications	Conditions	Min	Max	Unit
Temperature Range*	Operating	-40	+110	Deg C
Supply Voltage, Vcc	Over temperature	+4.5	+5.5	Volts DC
Supply Current	Into Vcc Io = 0	+2	+10	mA
Frequency Range	8x over sample	0	30	kHz
Saturation Voltage High	l out = 1 mA	Typ .2	0.4	Volts
Saturation Voltage Low	l out = 1 mA, Vcc = 5 V	4.5	Тур 4.7	Volts
ESD (Human Body Model)	Nondestructive	-	8000	Volts
EMI (Human Body Model)	20k to 1 G Hz	-	100	V/M
* T max = 150°C is available, contact factory.				

Magnetic Characteristics	Min	Тур	Max	Units
Quiescent Vo (0 Gauss, Vcc=5, T=25°C)	2.4	2.5	2.6	Volts
Change in Q-Vo Over Temp	030	0	+.030	Volts
Sensitivity at Vcc = 5, T = 25°C	4.5	5.0	5.5	mV/G
Change in Sensitivity at T = 150°C	-2.5	+2.5	+7.5	%
Change in Sensitivity at T = -40°C	-9	-1.3	+1	%

S12 Housing, 303 Stainless Steel, N	/12X1, 35mm Long
= 10.2 	2X NUT 17 HEX X 4.3 THK CONNECTION NICKEL PLATED BRASS SIDE M12X1-6g
DIM = MM, ID = 8.51 (.335")	35 Rev C

Absolute Max Limits	Min	Max	Unit
Supply Voltage, Vcc	-0.1	+8	Volts DC
Voltage Applied to Output	-0.1	+8	Volts
Current Into Output	-	10	mA
Current Out of Output	-	10	mA
Load Dump, 40 mS	-	TBD	Volts

Environmental Specifications		
Corrosion Resistance	500 hours salt spray ASTM B-117	
Installation Torque	23 Foot-Pounds Maximum	
Enclosure	Nema 1,3,4,6,13 & IEC IP67	
Vibration	10 G's 2 to 2000 Hz Sinusodal	
Mechanical Shock	100 G's, 11 mS Half-Sine	



Datasheet

standexelectronics.com

S12-AH5-5VP21 Analog Hall Sensor



Please note: All technical specifications on this series datasheet refer to the standard product range. Modifications in the sense of technical progress are reserved. For general information only. For more specific information, please consult the product datasheet, available upon request.

This series datasheet could contain technical inaccuracies or typographical errors. Changes are periodically made to the information herein. These change will be incorporated in future revisions.

For deviating values, most current specifications and products please contact your nearest sales office.