



SUNPOWER TECHNOLOGY CORP.
16F-1, No.150, Jian 1st Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.).
TEL: 886-2-8226-3100 FAX: 886-2-8226-3111
http://www.sunpower.com.tw
E-mail: sunpower@sunpower.com.tw

SPX-6300-GP1/SPX-6350-GP1

300W/350W, Six Output

For 1U System

ATX12V Power supply



205 x 100 x 40.5 mm
8.07 x 3.94 x 1.60 inch



Features:


- * Universal full range AC input with active PFC, P.F.> 0.95
- * High efficiency and reliability
- * Altitude during operation up to 4000M
- * Built-in long life ball bearing fan
- * 3.3V & 5V VRM design
- * Over voltage, over load & short circuit, over current, over temperature protection
- * With power good signal & PS-ON signal output
- * Meet Intel ATX 2.01 / ATX2.31 / ATX 12V
- * 2 year warranty

Specification:

INPUT	Voltage	90V ~ 264VAC universal full range or 127V ~ 375VDC						
	Frequency	47 ----- 63 Hz.						
	Current	SPX-6300-GP1	<4.2A @ 100VAC input, full load condition					
		SPX-6350-GP1	<5.0A @ 100VAC input, full load condition					
	Inrush Current(TYP.)	40A@115V , 60A@230V AC input, Cold start, at 25℃ ambient						
	Leakage Current	<1.5mA@264V AC input						
	Power Factor	PF > 0.95						
OUTPUT	Voltage	5V	3.3V	12V1	12V2	-12V	-5V	5Vsb
	Min Load	0.3A	0A	0.2A	0A	0A	0A	0A
	Max Load	25A	25A	16A	16A	0.5A Peak Load 1.5A ⑥	0.5A	3A
	Output Tolerance ②	±3%	±5%	±3%	±3%	±10%	±5%	±5%
	Ripple Noise MAX. ③	70mV	70mV	120mV	120mV	120mV	100 mV	70 mV
	Efficiency (TYP.)	83%						
	Output MAX.	SPX-6300-GP1 : 3.3V & 5V max 125W, total output max 300W SPX-6350-GP1 : 3.3V & 5V max 125W, total output max 350W						
PROTECTION	Over Voltage	5.4V~6.8V	3.7V~4.1V	13.1V~14.5V		----	----	----
		Shutdown and latch off, recover after re-start up.						
	Over current (MAX)	30A	30A	20A	20A	----	----	----
	OverLoad & ShortCircuit	When power supply over 105%~ 150% max load or short circuit acted, power supply will be shutdown and latch off, recover after re-start up.						
	Over Temperature	Over 95℃± 5℃ Shutdown, recovers automatically after fault condition has been removed.						
ELEC. CHAR.	Rise time	<20mS						
	Hold up time	>16mS@230V						
	Power Good signal	Power on within 100~500ms, high level TTL signal release.						
	PS-ON signal	P/S ON: PS-ON=Low or <0.8V, P/S OFF: PS-ON=Hi or >2V						
ENVIRONMENT	Temperature ④	Operating: -10~70℃; De-rating: 50~70℃ : 2.5%/℃. ; Storage: -20~+85℃						
	Humidity	Operating: 20% ~ 90% RH (non condensing) ; Storage: 10% ~ 95% RH (non condensing)						
	Altitude	13124ft (≐ 4000m) operating						
SAFETY	Withstand voltage	I/P-O/P:3.0KVAC, I/P-PE:1.8KVAC, 1minute						
	Isolation resistance	I/P-O/P, I/P-PE > 100MΩ/500VDC at 25℃/ 70% RH						
	Safety standard	UL 62368-1, 2 nd Edition, 2014-12-01, CAN/CSA C22.2 No.62368-1-14, 2 nd Edition, 2014-12, IEC 62368-1:2014						
EMC	EMI	EN / BS EN 55032 CLASS B, FCC CFR 47 PART 15 CLASS B						
		Compliance to EN / BS EN 61000-3-2 CLASS D, EN / BS EN 61000-3-3						
	EMS	EN / BS EN 55035 : 2017 EN / BS EN 61000-4-2,3,4,5,6,8,11						
OTHERS	Cooling	Forced airflow cooling with a DC fan.						
	M.T.B.F.	108.7 K hours						
	Dimension	205 x 100 x 40.5 mm (L*W*H)						
	PACKING	N.W.: 1.25 KG / 1PC; 12 PCS / 2.02 CUFT / 1 CTN						



De-rating Curve :



(Unit: mm)

SPX-6300-GP1/SPX-6350-GP1

