

SuperChassis 830P4

[Products](#) ▶ [Chassis](#) ▶ [Pedestal](#) ▶ [[SC830P4](#)]

Chassis Picture
Not Yet Available

Key Features

1. 400W+400W Redundant Hot-swap, Power Supply
2. 4 x 3.5" SCA Ultra320/160 SCSI Hot-swappable Drive Bays (optional)
3. 9 x 5.25" Peripheral Drive Bays
4. 2 x 3.5" Drive Bays
5. 9x Full-height, Full-length expansion slot
6. 8 x 90mm Hot-swappable Fans
7. 2 x 120mm Rear-exhaust Fan
8. Power Switch & 5 LED Indicators

Note: Image above may show a varied configuration or optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs - Discontinued SKU. Please contact sales-rep for possible OEM production quantities. MOQ may apply

CSE-830P4 ■ SuperChassis 830P4 (Beige)

Form Factor

Pedestal chassis support for max. motherboard size - 13" x 18" SWTX

Processor Support

Dual/Single Xeon® Processors

Dimensions

Height	19.9" (505mm)
Width	15.0" (381mm)
Depth	22.6" (570mm)
Gross Weight	77 lbs (35kg)
Available Colors	Beige

Expansion Slots

9x Full-height, Full-length expansion slots

Drive Bays

Hot-swap	<ul style="list-style-type: none"> • 4x 3.5" SCA Ultra320/160 Hot-swap Drives • 1x M35S Mobile Rack
Peripheral Bay(s)	<ul style="list-style-type: none"> • 9x 5.25" Peripheral Drive Bays • 2x 3.5" Drive Bays

Front Panel

Buttons	<ul style="list-style-type: none"> • Power On/Off button • System Reset button
LEDs	<ul style="list-style-type: none"> • Power LED • Hard drive activity LED • 2x Network activity LEDs • System Overheat LED • Power Fail LED
Ports	none

System Cooling

Fans	<ul style="list-style-type: none"> • 8x 90mm Hot-swappable Fans • 2x 120mm Rear Exhaust Fan
------	---

System Monitoring

Chassis intrusion switch

Operating Environment (System)

Operating Temperature Range	■ 5°C ~ 35°C (41°F ~ 95°F)
Non-Operating Temperature Range	■ -40°C ~ 60°C (-40°F ~ 140°F)
Operating Relative Humidity Range	■ 8% ~ 90% (non-condensing)
Non-Operating Relative Humidity Range	■ 5% - 95% (non-condensing)

Power Supply

400+400W Triple-redundant AC power supply w/o PFC

AC Voltage	• 115 - 230V, 47-63Hz, 9A/5A
DC Output	• 12V + 5V + 3.3V ≤ 370W
+5V	50.0 Amp
+5V standby	1.0 Amp
-5V	1.5 Amp
+12V	25.0 Amp
-12V	1.5 Amp
+3.3V	30 Amp

Regulatory (Power Supply)

Power Supply Safety / EMC	<ul style="list-style-type: none"> • USA - UL listed, FCC • Canada - CUL listed • Germany - TUV Certified • Europe/CE Mark • EN 60950/IEC 60950-Compliant
---------------------------	--

Components

Standard Parts List

	Part Number	Qty	Description
SC830P4 Chassis	CSE-0058	1	Pedestal Chassis (Beige)
Power Supply	PWS-0029	1	EPR-2405 400+400W Redundant Power Supply
	PWS-0033(M)	2	EPR-405 400W Power Supply Module
Fan(s)	FAN-0036	8	90mm Hot-swappable Fan
	FAN-0037	2	120mm Rear Exhaust Fan
Rear I/O	CSE-PT2	1	I/O Shield for Single LAN and Sound
SCSI Cable	CBL-027-U320	1	31.5" Two-drop Ultra 320 SCSI Cable

Optional Parts List

	Part Number	Qty	Description
SCA	CSE-0031	-	4-Drive Hot-swappable U160 SCSI SCA Mobile Rack
Heatsink / Retention	-	-	Please refer to our Thermal Components Matrix
Peripheral Drives	FPD-SONY-F(B)	1	Sony 3.5" Floppy Drive (Beige, B = Black)

[Terms & Conditions](#) | [Privacy](#) | [Investor Relations](#) | [Jobs](#) | [Site Map](#)

[SuperServer®](#) | [Motherboard](#) | [Chassis](#) | [Rack Cabinet](#) | [SuperBlade®](#) | [Embedded](#) | [Networking](#) | [Storage](#) | [Accessories](#) | [AMD Solution](#) | [Power Supplies](#)

Copyright © 2019 Super Micro Computer, Inc.

Information in this document is subject to change without notice.

Other products and companies referred to herein are trademarks or registered trademarks of their respective companies or mark holders.