


Products ☐ Chassis ☐ 1U ☐ [ SC111LT-360CB ]



### Key Features

- 1. 360W high-efficiency power supply 80 PLUS Silver Level
- 2. 4x Hot-swap 2.5" SAS / SATA HDD trays
- 3. 1x Full-height, full-length expansion slot
- 4. 3x 40x28mm 13K RPM 4-pin PWM fans
- 5. Supports motherboard sizes of 12" x 13", 12" x 10", and 9.6" x 9.6" (E-ATX, ATX, and Micro-ATX)

### Available Colors

Black ☐

### Downloads

Chassis Manual ☐

Product SKUs	CSE-111LT-360CB <ul style="list-style-type: none"><li>SuperChassis 111LT-360CB (Black)</li></ul>
Form Factor	21.95" Depth 1U Rackmount Chassis - support for motherboard size of 12" x 13" (E-ATX), 12" x 10" (ATX), and 9.6" x 9.6" (Micro-ATX)
Processor Support	Supports single and dual (low power) Intel® / AMD processors
Dimensions	<div>Width<ul style="list-style-type: none"><li>16.8" (426mm)</li></ul>Height<ul style="list-style-type: none"><li>1.7" (43mm)</li></ul>Depth<ul style="list-style-type: none"><li>21.95" (558mm)</li></ul>Packaging<ul style="list-style-type: none"><li>24" (W) x 8.3" (H) x 30" (L)</li></ul>Gross Weight<ul style="list-style-type: none"><li>29 lbs (13.2kg)</li></ul>Available Color<ul style="list-style-type: none"><li>Black</li></ul></div>
Expansion Slots	<ul style="list-style-type: none"><li>1x Full-height, Full-length AOC expansion slot</li></ul>
Drive Bays	<div>HDD Bay<ul style="list-style-type: none"><li>4x Hot-swap 2.5" SAS / SATA HDD trays SAS or enterprise SATA HDD only recommended</li></ul></div>
SAS / SATA Backplane	1U 2.5" SAS / SATA HDD backplane
Peripheral Drives	<div>DVD-ROM<ul style="list-style-type: none"><li>Slim DVD-ROM Drive (optional)</li></ul></div>
Front Panel	<div>Buttons<ul style="list-style-type: none"><li>Power On/Off button</li><li>System Reset button</li></ul>LEDs<ul style="list-style-type: none"><li>Power status LED</li><li>HDD activity LED</li><li>2x Network activity LEDs</li></ul></div>
System Cooling	<div>Fans<ul style="list-style-type: none"><li>3x 40x28mm 13K RPM 4-pin PWM fans</li></ul></div>
Operating Environment (System)	<div>Operating Temperature Range<ul style="list-style-type: none"><li>5°C ~ 35°C (41°F ~ 95°F)</li></ul>Non-Operating Temperature Range<ul style="list-style-type: none"><li>-40°C ~ 60°C (-40°F ~ 140°F)</li></ul>Operating Relative Humidity Range<ul style="list-style-type: none"><li>8% ~ 90% (non-condensing)</li></ul>Non-Operating Relative Humidity Range<ul style="list-style-type: none"><li>5% - 95% (non-condensing)</li></ul></div>
Power Supply	<div>360W AC power supply w/ PFCAC Voltage<ul style="list-style-type: none"><li>100-240 V, 50-60 Hz, 4.8-2.7 Amp</li></ul>+5V<ul style="list-style-type: none"><li>20 Amp</li></ul>+5V standby<ul style="list-style-type: none"><li>4 Amp</li></ul>+12V<ul style="list-style-type: none"><li>29 Amp @ 100-140Vac, 32.5 Amp @ 180-240 Vac</li></ul>-12V<ul style="list-style-type: none"><li>0.5 Amp</li></ul>+3.3V<ul style="list-style-type: none"><li>20 Amp</li></ul></div> <div>Certification<div></div>Silver Certified [ <a href="#">Test Report</a> ]</div>
Regulatory (Power Supply)	<div>Power Supply Safety / EMC<ul style="list-style-type: none"><li>USA - UL listed, FCC</li><li>Canada - CUL listed</li><li>CCC Certification</li><li>EN 60950/IEC 60950-Compliant</li><li>Europe/CE Mark</li><li>Germany - TUV Certified</li></ul></div>

Standard Parts List			
	Part Number	Qty	Description
Chassis	CSE-111LT-360CB	1	1U Chassis ( <b>Black</b> )
Backplane	BPN-SAS-809T	1	Sup 4x2.5b hdd; No SES-II; SATA con
Power Supply	PWS-361-1H	1	360W Multiple Outputs Power Supply(Delta)
Power Supply	PWS-361R-1H	1	1U 360W POWER SUPPLY 24PIN
Air Shroud	MCP-310-19006-0N	1	SC111 Intel DP X9 Universal Mylar Air Shroud, 12x13MB
Accessory	MCP-420-11102-0N	1	Accessory "bag" For SC111L Chassis With One Power Cord
Cable 1	CBL-0260L	1	US power cord 18AWG 6ft, PBF (default for low watt)
Cable 2	CBL-0277L	1	HDD POWER CABLE (BIG 4 PIN; 32CM), PBF
Cable 3	CBL-0306L	1	FRONT CTRL CABLE ROUND 16 pin TO 16 pin RIBBON, 65CM 28AWG
Peripheral Drive	MCP-290-11101-0B	1	black DVD dummy cover for SC111
Fan	FAN-0065L4	3	4028mm 13K RPM 4-PIN PWM FAN for SC813MF, SC113M
Floppy Disk & accessory	MCP-290-11104-0B	1	black USB or FDD dummy cover for SC111
Fan Holder	CSE-PT0131	1	Fan tray for three 40x28mm fans
Drive Trays	MCP-220-00047-0B	4	Black gen 3rd hot-swap 2.5inch HDD tray
Part(s)	MCP-260-00024-0N	1	1U I/O shield for X8 server MB (3rd LAN + 4xLAN)
Part(s)	MCP-260-00041-0N	1	1U I/O shield for X9 socket R server MB with Gasket
Mounting Rails	MCP-290-00050-0N	1 set	Rail set, (inner rail: quick-release, outer rail: screw-type)
Rear Window	MCP-240-11102-0N	1	SC111 standard rear window
Optional Parts List			
	Part Number	Qty	Description
Fan(s)	MCP-320-11101-0N	-	Fan holder for 2x 4028 fans
	FAN-0106L4 or FAN-0065L4	-	Extra fan for AOC cooling
Peripheral Drives	DV/MFNSC-824B	-	Black slim IDE DVD (8x DVD, 24x CDR), Panasonic
	MCP-220-11101-0N	-	Slim IDE DVD-ROM accessory Kit
USB/ COM Port	MCP-290-11103-0N	-	USB Kit (FDD Slot) for SC111