

Chip NTC Thermistors (Protection Device)

[Product Top Page](#)
[Search by Part No.](#)
[Search by Characteristics](#)
[Cross Reference](#)
[Catalog](#)
[Tech Notes](#)
[Technical Support Tools](#)
[FAQ](#)

B57350V2104F460

Applications	Commercial Grade
Features	<div>125°C 125°C</div> <div>UL UL Certificate</div>
Type	B57350V2
Status	Production
Brand	EPCOS



Images are for reference only and show exemplary products.

Size	
L x W Size	1.6mm x 0.8mm [EIA 0603]
Thickness Height	0.90mm Max.
Detail Size Information	Please refer to the data sheet

Electrical Characteristics	
Resistance [at 25°C]	100kΩ
Resistance Tolerance	±1%
B value [25/50°C]	4200K
B value [25/85°C]	4260K
B value [25/100°C]	4282K
B value Tolerance	±1%
Max. Electric Power [at 25°C]	180mW
Permissive Operating Current [at 25°C]	170μA
Thermal Dissipation Constant [at 25°C]	3mW/°C 3mW/K
Further Details	Please refer to the data sheet

Other	
Max. Operating Temperature	125°C
UL File No.	E69802
AEC-Q200	No
Soldering Method	Please refer to the document (Mounting Instructions)
Packing	Please refer to the document (Taping and Packing)

PDF file of this page

Buy Now

Contact

Documents
Data Sheet
General Technical Information
Cautions and Warnings
Quality and Environment
Symbols and Terms
Taping and Packing
Mounting Instructions
Climatic Conditions
RoHS Certificate
SVHC/REACH Certificate
Material Data Sheets
Selection Guide
Application Note
Standardized R/T characteristics

Technical Support Tools
NTC R/T Calculation
NTC Thermistor Library for PSpice
Sample Kits

Products

- [» Search by Part No.](#)
[» Search by Characteristics](#)
[» Distributor Inventory Check](#)
- [» Capacitors](#)
[» Inductors \(Coils\)](#)
[» EMC Components](#)
[» RF / SAW Components and Modules](#)
[» Voltage / Current / Temperature Protection Devices](#)
[» Sensors and Sensor Systems](#)
[» Ceramic Switching / Heating, Piezo Components and Buzzers](#)
[» Transformers](#)
[» Ferrites and Accessories](#)
[» Noise Suppressing / Magnetic Sheet](#)

[» Anechoic Chambers and Radio Wave Absorbers](#)
[» Power Supplies](#)
[» Magnets](#)
[» Flash Storages](#)
[» Wireless Charging](#)
[» FA Systems](#)
[» Transparent Conductive Film](#)
[» Micro Modules \(Substrates with Built-in ICs, Products Utilizing with SESUB\)](#)
[» Solar Cells](#)
[» Biosensor](#)

- Application Guides
- Technical Support
- Tech Library
- Environment
- Contact
- News
- Home

- About TDK
- TDK Worldwide

