

Configuration details V901CCV (AC input)

Part number	V901CCV
Product Description	V9FSLF 15C3SN 15C3SN 24C5SN 5/5H1H/1HSN W5FSV4
Total requested output power	920 W
Total output power	900 W
Approvals	C-UL-US, CE.
Cooling	Forward air fan - end mount
Input	Screw
Earth leakage	290 microamps maximum leakage current
Primary option	AC fail with PSU + fan inhibit and 5V/100mA aux supply
Dimensions	Length: 268.4mm, Width: 126.5mm, Height: 62.8mm

- Notes
- 1. Caution: Total connected power (920W) exceeds total available power (900W). You will not be able to use all outputs at maximum rating simultaneously.
 - 2. W5FSV4 wide range modules have a range of 0.25 - 32 Vdc with a current capability of 8.5 A.

Module	W5FSV4	H1H/1H	C5	C3	C3
Output 1	5V/8A	5V/12A	24V/10A	15V/18A	15V/18A
Output 2	-	5V/8A	-	-	-
Option	0-5V programming, current programming, enable, fixed ovp	Inhibit, module good and remote sense	Inhibit, module good, remote sense and current share	Inhibit, module good, remote sense and current share	Inhibit, module good, remote sense and current share
Connection	Screw	Screw	Screw	Screw	Screw

The view shown is of the output end of the supply.

Request a quote