



MODEL 45005

High Temp Glass NTC Thermistor

- Superior Long Term Stability
- Glass Hermetic Seal
- Use up to 250°C
- 3000 ohm Resistance @ 25°C
- Interchangeable $\pm 0.2^{\circ}\text{C}$, 0°C to 70°C
- Pressed Disk Ceramic Sensor
- High sensitivity
- Thermally conductive epoxy coating
- 32 AWG, 3" (7.6 cm) long Gold plated Dumet leads
- RoHS Compliant

FEATURES

- Glass Hermetic Seal
- 3000 Ohm Resistance @ 25°C
- Interchangeability
- Excellent High Temperature Performance
- Superior Long Term Stability
- High Sensitivity
- Thermally Conductive Epoxy Coating
- RoHS Compliance


APPLICATIONS

- High Moisture Applications
- Low to Mid Range Temperature Applications
- Tight Tolerance Instrumentation
- Use up to 250°C
- Applications Requiring Excellent Stability
- Applications Requiring Sensing Small Changes in Temperature
- Non-condensing Moisture Environments
- Allows use in Applications World-wide

PERFORMANCE SPECS

Parameter	Units	Value
Resistance @ 25°C	Ohms	3000
Tolerance 0°C to 70°C	°C	± 0.2
Beta Value 25/85	K	3978
Tolerance on Beta Value	%	0.8
Time response in air	Seconds	< 2.5
Dissipation Constant in air	mW/°C	10
Insulation Resistance (Min. of 100 Mohms for 1 sec.)	Volts	500

MECHANICAL DETAILS



RESISTANCE VS. TEMPERATURE TABLE

Temp °C	K-Ohms	Temp °C	K-Ohms	Temp °C	K-Ohms	Temp °C	K-Ohms	Temp °C	K-Ohms
-55	289.200	-13	19.580	29	2.523	71	0.5078	113	0.1411
-54	268.600	-12	18.520	30	2.417	72	0.4909	114	0.1372
-53	249.700	-11	17.530	31	2.317	73	0.4747	115	0.1336
-52	232.200	-10	16.600	32	2.221	74	0.4590	116	0.1300
-51	216.000	-9	15.720	33	2.130	75	0.4440	117	0.1265
-50	201.100	-8	14.900	34	2.042	76	0.4295	118	0.1232
-49	187.300	-7	14.120	35	1.959	77	0.4156	119	0.1199
-48	174.500	-6	13.390	36	1.880	78	0.4022	120	0.1168
-47	162.700	-5	12.700	37	1.805	79	0.3893	121	0.1138
-46	151.700	-4	12.050	38	1.733	80	0.3769	122	0.1108
-45	141.600	-3	11.440	39	1.664	81	0.3649	123	0.1079
-44	132.200	-2	10.860	40	1.598	82	0.3534	124	0.1052
-43	123.500	-1	10.310	41	1.535	83	0.3422	125	0.1025
-42	115.400	0	9.796	42	1.475	84	0.3315	126	0.0999
-41	107.900	1	9.310	43	1.418	85	0.3212	127	0.0973
-40	101.000	2	8.851	44	1.363	86	0.3113	128	0.0949
-39	94.480	3	8.417	45	1.310	87	0.3017	129	0.0925
-38	88.460	4	8.006	46	1.260	88	0.2924	130	0.0902
-37	82.870	5	7.618	47	1.212	89	0.2835	131	0.0879
-36	77.660	6	7.252	48	1.167	90	0.2749	132	0.0857
-35	72.810	7	6.905	49	1.123	91	0.2666	133	0.0836
-34	68.300	8	6.576	50	1.081	92	0.2586	134	0.0816
-33	64.090	9	6.265	51	1.040	93	0.2509	135	0.0796
-32	60.170	10	5.971	52	1.002	94	0.2434	136	0.0776
-31	56.510	11	5.692	53	0.9650	95	0.2362	137	0.0758
-30	53.100	12	5.427	54	0.9296	96	0.2293	138	0.0739
-29	49.910	13	5.177	55	0.8958	97	0.2226	139	0.0722
-28	46.940	14	4.939	56	0.8633	98	0.2161	140	0.0704
-27	44.160	15	4.714	57	0.8322	99	0.2098	141	0.0688
-26	41.560	16	4.500	58	0.8023	100	0.2038	142	0.0671
-25	39.130	17	4.297	59	0.7737	101	0.1979	143	0.0655
-24	36.860	18	4.105	60	0.7463	102	0.1922	144	0.0640
-23	34.730	19	3.922	61	0.7199	103	0.1868	145	0.0625
-22	32.740	20	3.748	62	0.6947	104	0.1815	146	0.0611
-21	30.870	21	3.583	63	0.6704	105	0.1764	147	0.0596
-20	29.130	22	3.426	64	0.6471	106	0.1714	148	0.0583
-19	27.490	23	3.277	65	0.6247	107	0.1667	149	0.0569
-18	25.950	24	3.135	66	0.6033	108	0.1620	150	0.0556
-17	24.510	25	3.000	67	0.5826	109	0.1576		
-16	23.160	26	2.872	68	0.5628	110	0.1532		
-15	21.890	27	2.750	69	0.5437	111	0.1490		
-14	20.700	28	2.633	70	0.5254	112	0.1450		

MODEL 45005

Hight Temp Glass NTC Thermistor

ORDERING INFORMATION

Model Number	Description	Ω @25°C	MOQ
090049	45005 THERMISTOR	3,000	100
091531	45005-BP (100 PCS) THERM	3,000	100

* For quantities less than Minimum Order Quantity – contact distribution

NORTH AMERICA

Measurement Specialties, Inc.,
a TE Connectivity Company
Tel: 800-522-6752
customercare.ando@te.com

EUROPE

Measurement Specialties (Europe), Ltd.,
a TE Connectivity Company
Tel: 800-440-5100
customercare.tfse@te.com

ASIA

Measurement Specialties (China), Ltd.,
a TE Connectivity Company
Tel: 0400-820-6015
customercare.chdu@te.com

te.com/sensorsolutions

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties (MEAS), American Sensor Technologies (AST), TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2016 TE Connectivity Ltd. family of companies All Rights Reserved.