

MEAS | MEAS 85 Series TE Internal #: 85-100A-8C TE Internal Description: 100 PSIA 1/8-27 NPT RIBBON PRESS SENSOR 13MM MV OUTPUT PRESSURE SENSOR

View on TE.com >



Sensors > Pressure Sensors > Media Isolated Pressure Sensors > 13MM MV OUTPUT PRESSURE SENSOR



Pressure: [100 psi] Pressure Sensor Type: mV Output Pressure Sensors Pressure Type: Absolute Output Signal Type: 100mV Operating Temperature Range: -40 – 125 °C [-40 – 257 °F]

### All 13MM MV OUTPUT PRESSURE SENSOR (18)

## Features

### **Product Type Features**

Pressure Sensor Type

mV Output Pressure Sensors

Pressure Type	Absolute
Sensor Package	Threaded Process Fittings, Weldable
Configuration Features	
Electrical Connection	Cable w/ Connector
Electrical Characteristics	
Supply Current	1.5 mA
Dimensions	
Product Diameter	15.85 mm[.624 in]
Product Height	9.3 mm[.366 in]
Usage Conditions	
Operating Temperature Range	-40 - 125 °C[-40 - 257 °F]
Operation/Application	
Proof Pressure Range	3Х
	100 psi

**C** For support call+1 800 522 6752

08/13/2024 12:05PM | Page 1

85-100A-8C

100 PSIA 1/8-27 NPT RIBBON PRESS SENSOR



Output Signal Type	100mV
Other	
Non-Linearity ±	.1 %
Port Fitting	1/8-27 NPT
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6- trimethylphenyl)- (1% in Component Part) Atile Safe Usage Statements Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Not Yet Reviewed for halogen content

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


# **Compatible Parts**

#### 100 PSIA 1/8-27 NPT RIBBON PRESS SENSOR





# Also in the Series | MEAS 85 Series



# Customers Also Bought



TE Part #8-1437627-4 G12KA=BUTTON GUARD KNURL ALUM

# Documents

CAD Files

3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_85-100A-8C\_G1.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_85-100A-8C\_G1.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_85-100A-8C\_G1.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

**C** For support call+1 800 522 6752

85-100A-8C

100 PSIA 1/8-27 NPT RIBBON PRESS SENSOR



85C

English