

MEAS | MEAS 86 Series TE Internal #: 86-030A-R TE Internal Description: 30 PSIA RIBBON CABLE MV PRESSURE SENSOR View on TE.com >

Sensors > Pressure Sensors > Media Isolated Pressure Sensors





Pressure: [30 psi] Pressure Sensor Type: mV Output Pressure Sensors Pressure Type: Absolute Output Signal Type: 100mV Operating Temperature Range: -40 – 125 °C [-40 – 257 °F] Features

Product Type Features

Pressure Sensor Type

Pressure Type

Sensor Package

mV Output Pressure Sensors

Absolute

O-Ring Mount

Configuration Features

Electrical Connection	Ribbon Cable							
Electrical Characteristics								
Supply Current	1.5 mA							
Dimensions								
Product Diameter	15.82 mm[.622 in]							
Product Height	11.4 mm[.448 in]							
Usage Conditions								
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]							
Operation/Application								
Proof Pressure Range	3X							
	30 psi							
Output Signal Type	100mV							
Other								

S For support call+1 800 522 6752

30 PSIA RIBBON CABLE MV PRESSURE SENSOR



Non-Linearity ±	.1 %
Sensor Options	No Tube
Product Compliance	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Methanone, (diphenylphosphinyl)(2,4,6- trimethylphenyl)- (1% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



30 PSIA RIBBON CABLE MV PRESSURE SENSOR





Also in the Series | MEAS 86 Series



Media Isolated Pressure Sensors(40)

Customers Also Bought



TE Part #M3031-000005-01KPG PRESS XDCR M3031-000005-01KPG	TE Part #85-005G-0RT NISO,GAGE,NO FIT,R.CABLE/TUB		TE Part #85-030V-0R VACGAGE,NO FITTING,RIBCBL	TE Part #85-500G-0R NISO,GAGE,NO FIT,RIBBON CBL
		I		

TE Part #86-300V-R ASSY,NISO,LP,VAC,CABLE ASSY,NISO,LP,VAC,CABLE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_86-030A-R_G1.2d_dxf.zip

English

Customer View Model

C For support call+1 800 522 6752

30 PSIA RIBBON CABLE MV PRESSURE SENSOR



ENG_CVM_CVM_86-030A-R_G1.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_86-030A-R_G1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 86C

English