




Developed specifically to meet the needs of the auto racing industry and proven in industrial applications, our CLP series position transducers offer unrivalled performance in terms of accuracy, repeatability, life expectancy and ease of mounting.

The combination of individually corrected conductive plastic elements and precious metal wipers provide a cost effective measuring system which can operate effectively without being unduly influenced by external environmental conditions.

## CLP

### Linear Potentiometer

**Absolute Linear Position to 10 inches (250 mm)**

**2.5K - 10K ohms • High Cycle Applications**

**Factory Automation or Auto Sport Instrumentation**

**IP65 Protection**

#### General

|                           |                                         |
|---------------------------|-----------------------------------------|
| <b>Full Stroke Ranges</b> | 0-1 to 0-10 in. (0-25 to 0-250 mm)      |
| <b>Output Signal</b>      | voltage divider (potentiometer)         |
| <b>Linearity</b>          | .1% to .2%, see ordering information    |
| <b>Repeatability</b>      | 0.01 mm                                 |
| <b>Resolution</b>         | essentially infinite                    |
| <b>Life Expectancy</b>    | > 25 million cycles                     |
| <b>Operating Speed</b>    | 400 inches (10 M) per second max.       |
| <b>Enclosure Material</b> | Aluminum                                |
| <b>Sensor</b>             | conductive plastic linear potentiometer |
| <b>Weight</b>             | see ordering information                |


#### Electrical

|                                            |                |
|--------------------------------------------|----------------|
| <b>Input Resistance</b>                    | see order code |
| <b>Recommended Maximum Input Voltage</b>   | 42 VDC         |
| <b>Recommended Operating Wiper Current</b> | < 1μA          |

#### Environmental

|                              |                               |
|------------------------------|-------------------------------|
| <b>Enclosure Design</b>      | IP65                          |
| <b>Environmental Sealing</b> | O-ring and felt shaft seal    |
| <b>Operating Temperature</b> | -40° to 212°F                 |
| <b>Vibration</b>             | up to 10 g to 2000 Hz maximum |

## Outline Drawing



## Ordering Information

| Item Number                  | CLP-25  | CLP-50  | CLP-75   | CLP-100  | CLP-150  | CLP-200  | CLP-250  |
|------------------------------|---------|---------|----------|----------|----------|----------|----------|
| measurement range, in. [mm]: | 1[25]   | 2[50]   | 3[75]    | 4[100]   | 6[150]   | 8[200]   | 10[250]  |
| resistance, (±20%):          | 2.5K    | 5.0K    | 5.0K     | 5.0K     | 10K      | 10K      | 10K      |
| linearity, %:                | 0.2%    | 0.2%    | 0.2%     | 0.2%     | 0.1%     | 0.1%     | 0.1%     |
| weight, oz. [grams]:         | 3.0[87] | 3.4[97] | 3.8[108] | 4.1[117] | 4.8[138] | 5.5[157] | 6.2[177] |

## NORTH AMERICA

Measurement Specialties, Inc.,  
a TE Connectivity company  
Tel: 800-522-6752  
Email: [customer@te.com](mailto:customer@te.com)

[TE.com/sensorsolutions](http://TE.com/sensorsolutions)

Measurement Specialties, Inc., a TE Connectivity company.

Measurement Specialties, TE Connectivity, TE Connectivity (logo) and EVERY CONNECTION COUNTS are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2015 TE Connectivity Ltd. family of companies All Rights Reserved.

CLP 12/01/2015