

WP-TS-501Date:13.02.2017Revision:1.1Page:1 von 16

Specification Ni1000SOT NO TIN

Revision 1.1





Customer A	cceptance	
Company:		
Address:		
Date:		
Name:		
Function:		
Signature:		

TE Connectivity Sensors Germany GmbH Hauert 13, D-44227 Dortmund, Germany



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 2 von 16

Content

History	y of changes		3
Applyi	ng Document	ts	4
Legal	disclaimer		4
1	General Info	rmation	5
	1.1	Applications	5
	1.2	Functional Block Diagram	5
	1.3	Part Number	5
	1.4	ESD	5
2	Mechanic		6
	2.1	Views	6
	2.2	Dimensions and Weight	6
	2.3	Mechanical Requirements	7
	2.4	Terminal Connections	7
3	Materials		7
4	Traceability		8
	4.1	Marking on Sensor Package	8
	4.2	Marking on Transportation Package:	8
5	Absolute Ma	ximum Ratings	9
6	Electrical Ch	naracteristics	10
	6.1	Characteristic Data:	10
	6.2	Resistance Table:	11
	6.3	Electrical Tests	11
7	Lifetime- and	d Qualification Tests	12
	7.1	Qualification	12
	7.2	Additional Tests	13
	7.3	Requalification	13
	7.4	Material Tests	13
8	Delivery For	m	14
	8.1	Dimensions of Reel	14
	8.2	Orientation of Sensors inside Tape	14
	8.3	Dimension of Tape	15
9	REACh and	RoHS Conformity	16



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 3 von 16

History of changes

Revision	Date	Descri	Description of changes	
1.0	23.01.2017	•	Finalization to first release	ToS
1.1	7.02.2017	•	Applying documents: update revision of WP-TS-305	ToS
		•	Chapter 2.2: Changing R2_max from 0.3 to 0.5 mm	



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 4 von 16

Applying Documents

#	Document title	Revision	Owner	Description
1	WP-TS-305 Delivery Specification for SOT223, SOT23, E- Line and SOT4W Packaged Products	7.0	TE Connectivity Sensors Germany GmbH	
2				
3				
4				
5				
6				
7				
8				
9				

Legal disclaimer

This product is not designed for use in life support appliances, devices or systems where malfunction of this product can reasonably be expected to result in personal injury. TE Connectivity Sensors Germany GmbH customers using or selling this product for use in such applications do so at their own risk and agree to fully indemnify TE Connectivity Sensors Germany GmbH for any damages resulting from such improper use or sale.

This data sheet contains target specifications for product development which may be subject to changes without notice.



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 5 von 16

1 General Information

Ni1000SOT NO TIN is a nickel thin film resistance temperature detector (RTD) that is suitable for use in contact temperature sensing.

The devices are manufactured by PVD-deposition on a silicon substrate. The thin film structure is covered by a passivation layer for environmental protection and enhanced stability. The nickel elements are mounted on lead frames and encapsulated in SOT23 packages. This technology allows the production of miniature, low cost, high precision temperature sensors.

The characteristics of the temperature sensor comply with the former DIN 43760 standard. It is qualified for the most demanding automotive applications (incl. exposure to hot oil) and is suitable for many more applications in harsh environments.

The lead frame of the used package consist of Alloy 42 with a thin silver surface. The leads are tin free for laser welding assembly process.

1.1 Applications

Temperature sensing, control and compensation in automotive applications

1.2 Functional Block Diagram



Figure 1: Wiring symbol

1.3 Part Number

Device	Part No.	Package
Ni1000SOT NO TIN	G-NICO-024	SOT23, leadframe material: Alloy 42, no tin coating

Customer Specific Part Number: 735.628-02

1.4 ESD

This component can be damaged by ESD. TE Connectivity recommends the handling with appropriate precaution.



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 6 von 16

2 Mechanic

2.1 Views



Figure 2: mechanical outline

2.2 Dimensions and Weight

Dimension	Min	Тур	Max	Unit
А	0.91	1.00	1.10	mm
A1	0.01	0.05	0.10	mm
A2	0.90	0.95	1.00	mm
b	0.35	0.40	0.45	mm
с	0.08	0.10	0.12	mm
D	2.94	3.00	3.06	mm
е	0.90	0.95	1.00	mm
E	2.23	2.42	2.64	mm
E1	1.33	1.38	1.43	mm
e1	1.85	1.90	1.95	mm
L	0.32	0.40	0.48	mm
L1	0.45	0.52	0.62	mm
R1	0.03	0.10	0.30	mm
R2	0.05	0.15	0.50	mm
R11	0.00	0.00	0.05	mm
R12	0.00	0.01	0.05	mm
U	0.34	0.39	0.44	mm
Х	0.00	0.10	0.25	mm
a1	0	7	14	٥
a2	0	7	14	٥
a3	0	7	14	٥
a4	0	7	14	0

Nominal weight: 8mg per sensor



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 7 von 16

2.3 Mechanical Requirements

2.3.1 Die Attach and Wire Bond Scheme:



Figure 3: Die attach and wire bond scheme

2.3.2 Footprint



Figure 4: Footprint

2.4 Terminal Connections

Top view: Pin # 1		Nickel RTD electrical contact	
	Pin # 2	Nickel RTD electrical contact	
	Pin # 3	Electrically isolated thermal contact	

3 Materials

IMDS ID:	608197877
Die:	Silicon wafer with structured thin film layer of Nickel, Titanium, Tungsten and Gold
Leadframe base material:	Alloy 42, thickness 1000µm (nominal)
Leadframe coating:	Ag coating, thickness 0.2 μ m (nominal), over Cu coating, thickness 0.3 μ m (nominal)
Bond wires:	Gold, 22µm diameter, two wires per pad
Mold:	GE1030M, Manufacturer: Nitto (Hitachi)



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 8 von 16

4 Traceability

4.1 Marking on Sensor Package

Three digit marking on package:				
First digit:	Last digit of customer product number:	2		
Second and third digit:	Revision of sensor:	01		
Resulting marking:	201			

4.2 Marking on Transportation Package:

Two different labels have to be applied:

Label 1: at each reel and pizza box as plain text and 1D barcode:

Parameter	Description	Note
Label size	100 x 50 mm ²	
Barcode	Type 39	
Part	NI1000SOT NO TIN	
P/N:	G-NICO-024	
QTY:	Quantity Reel	10000 pcs.
D/C:	Max. 2 Date Codes per Reel	YYWW
Batch:	TE SENSORS Lot number	
Lot No	Max. 2 Lots per Reel	
QTY:	Quantity lot	
Position for the label:	Reel and Pizza-box	



Figure 5 – Label 1



WP-TS-501Date:13.02.2017Revision:1.1Page:9 von 16

Label 2: at pizza box only as plain text and 1D barcode:

Parameter	Description	Note
Label size	100 x 50 mm ²	
Barcode	Туре 39	
Supplier:	TE SENSORS	
TE SENSORS PO No:	Order number TE SENSORS	
QTY:	Quantity Reel	10000 pcs.
Device:	NI1000SOT NO TIN	
P/N:	G-NICO-024	Item number TE SENSORS
Item:	735628-2	Item number end customer
D/C:	Max. 2 Date Codes per Reel	YYWW
Position for the label:	Pizza-box	



Figure 6 – Label 2

5 Absolute Maximum Ratings

Parameter	Symbol	Unit	Min	Тур.	Max	Condition
Storage Temperature	T _{St}	°C	-55		165	
Operating Temperature	Top	°C	-55		165	
Current	I	mA		1.2	5	
ESD Rating (HBM)	Class			1B		MIL 883E3015.7

Note:

Stress above one or more of the limiting values may cause permanent damage to the device. Exposure to limiting values for extended periods may affect device reliability.



WP-TS-501Date:13.02.2017Revision:1.1Page:10 von 16

6 Electrical Characteristics

6.1 Characteristic Data:

Characteristic curve according former DIN 43760	$R(T) = R_0 \cdot (1 + a \cdot T + b \cdot T^2 + c \cdot T^4 + d \cdot T^6)$ with $R_0 = 1000$ Ohm at 0°C T = temperature in °C $a = 5.485^{*}10^{-3}$ $b = 6.650^{*}10^{-6}$ $c = 2.805^{*}10^{-11}$ $d = -2.000^{*}10^{-17}$					
	<i>R</i> ₁₀₀ = 1618 Ohm at 100°C					
	Folerances:					
	$\Delta T = \pm (0.8 + 0.0045 * T)$ in the range of 0 to 160°C $\Delta T = \pm (0.8 + 0.021 * T)$ in the range of -55 to 0°C					
	Self heating of sensor: $\Delta T=P/SH$ with electric power P=R*I ² and selfheating coefficient SH=(1.7 ± 0.3) ^{mW/} _{°C} (Ambient air: 23°C; still air)					
Long term stability:	ΔR = 0.1 % after 1000h at 150°C					
Measurement current (DC):	typ. 1.2 mA; max. 5 mA					
Time constant (t ₆₃)	typ. 0.5 sec (measured in fluor inert liquid, step: 20 … 100°C)					



5



WP-TS-501Date:13.02.2017Revision:1.1Page:11 von 16

6.2 Resistance Table:

Temperature (°C) against Resistance (Ohm).

T(°C)	0	1	2	3	4	5	6	7	8	9
-60	695.2	699.9	704.6	709.3	714.0	718.7	723.4	728.2	733.0	737.8
-50	742.6	747.4	752.2	757.0	761.9	766.8	771.6	776.5	781.4	786.4
-40	791.3	796.3	801.2	806.2	811.2	816.2	821.2	826.3	831.3	836.4
-30	841.5	846.5	851.7	856.8	861.9	867.0	872.2	877.4	882.6	887.8
-20	893.0	898.2	903.4	908.7	913.9	919.2	924.5	929.8	935.1	940.5
-10	945.8	951.2	956.5	961.9	967.3	972.7	978.2	983.6	989.1	994.5
0	1000.0	1005.5	1011.0	1016.5	1022.0	1027.6	1033.1	1038.7	1044.3	1049.9
10	1055.5	1061.1	1066.8	1072.4	1078.1	1083.8	1089.5	1095.2	1100.9	1106.6
20	1112.4	1118.1	1123.9	1129.7	1135.5	1141.3	1147.1	1153.0	1158.8	1164.7
30	1170.6	1176.5	1182.4	1188.3	1194.2	1200.2	1206.1	1212.1	1218.1	1224.1
40	1230.1	1236.1	1242.2	1248.2	1254.3	1260.4	1266.5	1272.6	1278.8	1284.9
50	1291.1	1297.2	1303.4	1309.6	1315.8	1322.0	1328.3	1334.5	1340.8	1347.1
60	1353.4	1359.7	1366.0	1372.4	1378.7	1385.1	1391.5	1397.9	1404.3	1410.8
70	1417.2	1423.7	1430.1	1436.6	1443.1	1449.7	1456.2	1462.8	1469.3	1475.9
80	1482.5	1489.1	1495.7	1502.4	1509.1	1515.7	1522.4	1529.1	1535.9	1542.6
90	1549.3	1556.1	1562.9	1569.7	1576.5	1583.4	1590.2	1597.1	1604.0	1610.9
100	1617.8	1624.7	1631.7	1638.6	1645.6	1652.6	1659.6	1666.7	1673.7	1680.8
110	1687.9	1695.0	1702.1	1709.3	1716.4	1723.6	1730.8	1738.0	1745.2	1752.5
120	1759.7	1767.0	1774.3	1781.6	1788.9	1796.3	1803.7	1811.1	1818.5	1825.9
130	1833.3	1840.8	1848.3	1855.8	1863.3	1870.9	1878.4	1886.0	1893.6	1901.2
140	1908.9	1916.5	1924.2	1931.9	1939.6	1947.4	1955.1	1962.9	1970.7	1978.5
150	1986.3	1994.2	2002.1	2010.0	2017.9	2025.9	2033.8	2041.8	2049.8	2057.8
160	2065.9									

6.3 Electrical Tests

100% test: Each sensor die is checked for correct resistance value related to ambient temperature before dicing and packaging. Every packaged sensor is checked for correct bond wire connection and insulation between Pin1+2 against Pin 3.

Sample test: From each reel a specified quantity of sensors are tested for correct resistance and TCR at 0°C and 100°C. The quantity is defined as follows:

10000 Sensors per reel: 34 Samples



WP-TS-501Date:13.02.2017Revision:1.1Page:12 von 16

7 Lifetime- and Qualification Tests

7.1 Qualification

Before start of production sensors of the pre-series lot will be tested as shown in the table below.

No	Test	Test Conditions	Duration /	Pieces		Allowed	
			Number of cycles	(n)	(c)	Resistance Drift	
1	High temperature life time test	First step: 1638h @ 150°C, Second step: 200h @ 165°C, Medium: Air	1838h	77	0	0.32%	
	IEC 60068-2-2	Operation mode: I _F =1.5mA,					
2 Thermal shock test		-40°C / +150°C, 15min dwell after reaching temperature, Transfer time: < 30sec., Medium: Air	2000	77	0	0.1%	
	Na	Operation mode: not powered, not wired					
3	Damp heat cyclic (with frost)	Operation mode: not powered, not wired	240h	77	0	0.1%	
	IEC 60068-2-38						
4	Low temperature life	-55°C, Medium: Air	1008h	77	0	0.1%	
	time test IEC 60068-2-1	Operation mode: I _F =5mA/0mA, alternating operation, period: 2h					
5	Physical dimensions test	According to AEC-Q200 – see remarks below for		50	0		
		conditions and quantity		+			
				640			
6	ESD Test	According to AEC-Q200 (HBM)		15	0	0.1%	

All electrical and visual changes after test will be documented and provided to the customer.

Remarks to test 5:

To verify dimensions of all molding cavities the following process steps have to be done:

Verifying trim & form process (5x2 Tool): 5 values each of every specified dimension (A, D, E1, L1, L, c, b, E, A1) 50 parts in total.

Cavity measurements: values of specified dimensions D and E1 for all 640 cavities. Due to separation process there will be no correlation between cavity and value, it will be guaranteed that every cavity will be measured.



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 13 von 16

7.2 Additional Tests

The following tests will be performed additionally in collaboration with customer. Results of these tests will be part of the test result report but they are not included into internal qualification process and not part of product specification.

No	Test	Test Conditions	Duration / Number of cycles	Pieces
1	Laser welding and injection molding thermal stability / ability analysis a): RTD laser welded on customer leadframe (50 parts) b): Laser welded RTD injection-molded to customer flange group (25 parts of 50 parts from a))	 Before laser welding (50 parts): A1. Initial function test (measure value of resistance) A2. Delamination check of 10 parts with the aid of a scanning ultrasonic microscope After laser welding (25 parts): B1. Initial function test (measure value of resistance) B2. X-ray investigation of all parts B3. Delamination check of 10 parts (same 10 parts of A2) with the aid of a scanning ultrasonic microscope After laser welding and injection moulding (25 parts): C1. Initial function test (measure value of resistance) C2. X-ray investigation of all parts C3. Random sample size of 5 parts shall be investigated by 3D-RX Tomography C4. Same 5 parts shall be opened by chemical agent (decapsulation) 	1x	50
		C5. Same 5 parts visual evaluation of bonding connections by microscope		
2	Laser welding preconditioning Test: - High temperature storage (7 parts) CECC 50000 - Temperature moisture (7 parts) CECC50000 - RTD laser welded on customer leadframe	Before laser welding (preconditioning): High temperature storage test: 165°C, medium: air, non operating Temperature moisture storage: 85°C / 85% r.h., non operating After laser welding (investigation): EDX topographically analysis and metallographically investigation (micro cross sections) – investigation performed by customer	HTS: 1008h TMS: 1008h	14

7.3 Requalification

A requalification has to be ordered by the customer separately and won't be performed by TE Connectivity periodically. The required amount of parts will be provided by TE Connectivity Sensors Germany GmbH free of charge, any additional service has to be paid by the customer.

7.4 Material Tests

All materials used in the process will be released by checking the corresponding supplier certificates. A regular material analysis from an independent laboratory is not scheduled.



WP-TS-501Date:13.02.2017Revision:1.1Page:14 von 16

8 Delivery Form

The sensor will be delivered in tape and reel package. Reel diameter: 13 inch (330mm): 10000 pieces per reel

8.1 Dimensions of Reel



Figure 8: Reel

Dimension	Min	Тур	Мах	Unit
A			330 (13")	mm
В	1.5			mm
С	12.8	13	13.2	mm
D	20.2			mm
N	60.5	62	63.5	mm
G	6.9	8.4 ± 1.5	9.9	mm
Т			14.4	mm

8.2 Orientation of Sensors inside Tape

Package	Orientation diagrams	Reel size supplied	No. of components	Tape option indicator			
SOT 23		13" (330 mm)	10,000	тс			
Ordering Information: The tape indicator option is added to the requested device type as a suffix i.e. SOT23 FMMT49 TC							



 WP-TS-501

 Date:
 13.02.2017

 Revision:
 1.1

 Page:
 15 von 16

8.3 Dimension of Tape



Figure 9: Tape

Dimension	Min	Тур	Мах	Unit
Tape Size		8		mm
A0		3.2		mm
B0		4		mm
K0			2.4	mm
D0	1.45	1.5	1.55	mm
D1		1.5		mm
E	1.65	1.75	1.85	mm
F	3.495	3.5	3.505	mm
G		0.75		mm
P0	3.9	4	4.1	mm
P1		4		mm
P2	1.95	2	2.05	mm
Т		0.3	0.3	mm
T1		0.1	0.1	mm
T2		2.5	2.5	mm
W	7.7	8	8.3	mm
W3		5.5		mm



WP-TS-501Date:13.02.2017Revision:1.1Page:16 von 16

9 REACh and RoHS Conformity

All used substances comply with EC directive 1907/2006 (Registration, Evaluation and Authorisation of Chemicals, REACh) and with EC directive 2002/95/EC (Restriction of Hazardous Substances Directive, RoHS).