

## MEAS | MEAS HTM2500LF

TE Internal #: HPP809A033

TE Internal Description: HTM2500LFL HIGH TEMP RH/T MOD

Humidity Temperature Transducer

View on TE.com >



Sensors > Humidity Sensors > Humidity Sensor Assemblies > Humidity Temperature Transducer



Humidity Sensor Product Type: RHT Module

Supply Voltage (Peak): 12 VDC

Operating Temperature Range: -40 - 85 °C

Accuracy: ±3 %RH

Nominal Output @55%RH (at 5 VDC): 2.48 V

All Humidity Temperature Transducer (2)

## **Features**

## **Product Type Features**

Humidity Sensor Product Type	RHT Module
Interface Signal Type	Analog

### **Electrical Characteristics**

Supply Voltage (Peak)	12 VDC
Nominal Output @55%RH (at 5 VDC)	2.48 V
Current Consumption	1 mA
Output Impedance	70 Ω

## **Usage Conditions**

Humidity Operating Range	0 – 100 %RH
Operating Temperature Range	-40 – 85 °C
Accuracy	±3 %RH
Sensitivity	26 mV/%RH

### Other

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)  Candidate List Declared Against: JUL 2021 (219)  SVHC > Threshold:  4,4'-isopropylidenediphenol (Bisphenol A) (1% in Component)  Dodecamethylcyclohexasiloxane (D6) (.5% in Component)  Formamide (.2% in Component)  Article Safe Usage Statements:  Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts








Also in the Series | MEAS HTM2500LF





## Customers Also Bought





















## **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_HPP809A033\_D.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_HPP809A033\_D.3d\_igs.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_HPP809A033\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

HTM2500LF-HUMIDITY

English