



Sensors > Ultrasonic Sensors > POWER LOOP O/P ULTRASONIC LIQ LVL SWITCH



Ultrasonic Sensor Type: Point Liquid Level Sensors

Ultrasonic Sensor Style: Gap

All POWER LOOP O/P ULTRASONIC LIQ LVL SWITCH (16)

Features

Product Type Features

Ultrasonic Sensor Type	Point Liquid Level Sensors
Ultrasonic Sensor Style	Gap

Electrical Characteristics

Output Type	Analog 4 - 20 mA Power Loop
Input Voltage	5 – 30 VDC

Dimensions

Cable Length	1.22 m[4 ft]
--------------	--------------

Usage Conditions

Operating Temperature Range	-30 – 80 °C[-22 – 176 °F]
-----------------------------	---------------------------

Operation/Application

Actuation Point/Sensing Range	.25 Inches
	250 psi

Other

Port Fitting	1/4 NPT
--------------	---------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Not Yet Reviewed
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Also in the Series | MEAS LL-01



Customers Also Bought





TE Part #1-6609037-5
20EMC1=F8130



TE Part #LL01-1AA01
RELAY - ULTRASONIC LIQUID LEVEL SWITCH



TE Part #2-320568-2
TERM, RT, PIDG IR, 12, #8



TE Part #2293156-5
ZSFP+ 1X6 CAGE ASSY, PRESS-FIT, HS



TE Part #2294667-5
SFP+ 1X1 CAGE ASSEMBLY, SOLDER TAIL



TE Part #YDBC54H-14-5PNV001
HERM RECP

TE Part #2289858-9
1X1 QSFP CAGE, SOLDER, 0.5 TILT, W/ R HS

TE Part #2294662-3
CAGE ASSY,1X4, QSFP28,SPRING, HS, NO R P

TE Part #2159965-2
CA, 2POS ET TO RING TONGUE

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_LL01-5AA04_G.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_LL01-5AA04_G.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_LL01-5AA04_G.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

LL-01_Series_Power_Loop

English