SM9233-BCE-S-250-002 - ACTIVE

MEAS | SMI 9000

TE Internal #: 9233-BCE-S-250-002 Digital Pressure and Altimeter Sensor Modules, Gauge, 16 bit I2C, ±3% F.S Pressure Accuracy, Supply Voltage Range 5 V, SMI 9000 View on TE.com >



Sensors > Pressure Sensors > Board Mount Pressure Sensors > Ultra-low Pressure Digital Sensor



Pressure Sensor Type: Digital Pressure and Altimeter Sensor Modules

Pressure Type: Gauge

Proof Pressure Range: .07 bar

Output Signal Type: 16 bit I2C

Pressure Accuracy: ±3% F.S

All Ultra-low Pressure Digital Sensor (24)

Features

Product Type Features

Sensor Package

SOIC-16

Pressure Sensor Type

Digital Pressure and Altimeter Sensor

Pressure Sensor Type	Digital Pressure and Altimeter Sensor Modules
Pressure Type	Gauge
Electrical Characteristics	
Supply Voltage Range	5 V
Dimensions	
Product Width	10.31 mm[.405 in]
Product Length	10.26 mm[.403 in]
Product Height	9.32 mm[.366 in]
Usage Conditions	
Operating Temperature Range	-20 – 85 °C[-4 – 185 °F]
Operation/Application	
Output Interface	² C
Proof Pressure Range	.07 bar
Output Signal Type	16 bit I2C

SM9233-BCE-S-250-002

Digital Pressure and Altimeter Sensor Modules, Gauge, 16 bit I2C, ±3% F.S Pressure Accuracy, Supply Voltage Range 5 V, SMI 9000



Pressure Accuracy	±3% F.S
Packaging Features	
Sensor Port Configuration	Dual Vertical
Other	
Sensor Options	Barb Tube, No Option
Product Compliance For compliance documentation, visit the product page on TE.com> EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




SM9233-BCE-S-250-002

Digital Pressure and Altimeter Sensor Modules, Gauge, 16 bit I2C, ±3% F.S Pressure Accuracy, Supply Voltage Range 5 V, SMI 9000



Also in the Series | SMI 9000



Customers Also Bought



TE Part #206708-1 Circular Connector, Environmentally Sealed, CPC Series 6

Documents

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_9233-BCE-S-250-002_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_9233-BCE-S-250-002_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_9233-BCE-S-250-002_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages SM9000

English