Product data sheet Characteristics

9013GMG2S6J99R PRESSURE SWITCH 575VAC 5HP G SPECIAL

		٠	
NЛ	2	ı	r
IVI	а	ı	

dard environment enclosure indoor
and chiving inficint cholosule indoor
ol electrically driven water pumps and air pressors
re D Pumptrol
l

Complementary

1		
Approximate adjustable differential	48 psi (27.5855.16 kPa)	
Depth	3.68 in (93.47 mm)	
Electrical connection	Screw clamp terminal	
Fixing Mode	By brackets	
Fluid connection type	0.25 inch NPSF internal	
Height	5.72 in (145.29 mm)	
Material	Zinc plated steel: flange	
Materials in contact with fluid	Nitrile (Buna-N) diaphragm	
Maximum pressure	100 psig	
Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 3 Hp 115 V AC, 3 phase 3 Hp 230 V AC, 1 phase 5 Hp 230 V AC, 3 phase 5 Hp 460/575 V AC, 1 phase 5 hp 460/575 V AC, 3 phase	
Number of poles	2	
Permissible voltage	575 V AC	
Pressure actuator	Diaphragm	
Net Weight	2.25 lb(US) (1.02 kg)	
Range on decreasing pressure	1035 Psi (68.95241.32 kPa) 5.530.5 psi (37.92210.29 kPa)	
Scale type	Adjustable differential	
Switch function	DPST	
Width	3.44 in (87.38 mm)	

Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	UL listed file E12158 CCN NKPZ[RETURN]CSA file LR25490

Ordering and shipping details

US1CP7G21536	
CP7G	
785901776826	
No	
MX	
	CP7G 785901776826 No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.395 in (31.484 cm)
Package 1 Width	4.880 in (12.395 cm)
Package 1 Length	31.484 in (79.969 cm)
Package 1 Weight	31.999 oz (907.185 g)

Offer Sustainability

0.115 1 111 05	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes