Product data sheet Characteristics

9016GVG1J11 VACUUM SWITCH 480VAC 5HP G +OPTIONS



Main

Device short name	9016GVG
Enclosure type	Standard environment enclosure indoor
Product or Component Type	Electromechanical vacuum switch
Range of Product	Square D
Switch application	Standard

Complementary

1 entry for 1/2" - 14 NPT
Hydraulic oil Non-corrosive liquids Non-corrosive gas Air
525 inHg
020 inHg
Without mounting bracket
0.25 inch 18 NPSF internal
Zinc plated steel: flange
Nitrile (Buna-N) diaphragm
150 psig
2 Hp 110 V AC, 1 phase 3 Hp 220 V AC, 1 phase 5 Hp 440/550 V AC, 1 phase 3 Hp 110 V AC, 3 phase 5 hp 220/550 V AC, 3 phase
NEMA 1
120 cyc/mn
480 V AC
510 inHg
Diaphragm
Electromechanical power pressure switch
1722 inHg
3.5 lb(US) (1.6 kg)
0.4 % adjustable
A III A III III III III II II II II II I
Adjustable differential
Adjustable differential 2 NC - DPST

Environment

Ambient Air Temperature for Operation	-2385 °C (-10185 °F)
Product Certifications	CSA file LR25490[RETURN]UL listed file E12158 CCN NKPZ
Shock resistance	50 gn

Ordering and shipping details

Category	US1CP7G21541
Discount Schedule	CP7G
GTIN	785901523024
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.395 in (31.484 cm)
Package 1 Width	4.880 in (12.395 cm)
Package 1 Length	31.484 in (79.969 cm)
Package 1 Weight	3.481 lb(US) (1.579 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	€Yes

Contractual warranty

Warranty	18 months
vvarianty	16 months