

#### Main

Product or Component Type	Coded magnetic system
Contacts type and composition	1 NO
Material	Plastic
Electrical Connection	Pre-cabled
[Ue] rated operational voltage	120 V AC

#### Complementary

Protection Type	Overload and short-circuit protection
Breaking capacity	380 VA

#### Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

#### Ordering and shipping details

Category	US10DS222487
Discount Schedule	0DS2
GTIN	785901173489
Returnability	No
Country of origin	US

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.575 in (4.000 cm)
Package 1 Width	2.953 in (7.500 cm)
Package 1 Length	5.512 in (14.000 cm)
Package 1 Weight	12.346 oz (350.000 g)

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

#### Contractual warranty

Warranty	18 months
----------	-----------