Product data sheet Characteristics

SM401A0811FP

Hyde Park, microsonic tbeam receiver sm401a 08 11fp

Range of Product Hyde Park Sensor Type Ultrasonic sensor receiver	
Series name Standard format	
Device short name SM401	
Sensor design Miniature	
Material Plastic	
[Us] rated supply 1224 V DC voltage	
Electrical connection Cable	
[Sd] sensing range 0.666 ft (0.203 m)	
IP degree of protection IP66	

Complementary

[Sn] nominal sensing distance	0.666 ft (0.203 m)
Type of sensing window	Fixed
Condition of use	Thru beam
Transmission frequency	500 kHz

Ordering and shipping details

Category	US10DS222490
Discount Schedule	0DS2
GTIN	03389119091398
Returnability	No

Packing Units

- dioming or into		
Unit Type of Package 1	PCE	
		{
Number of Units in Package 1	1	**

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope

Contractual warranty

Contractual warranty	
Warranty	18 months