

Main

| | |
|--------------------------------|----------|
| Product or Component Type | Probe |
| [Ue] rated operational voltage | 130 V DC |

Complementary

| | |
|-----------------|---------------------------------------|
| Protection Type | Overload and short-circuit protection |
|-----------------|---------------------------------------|

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...185 °F (-40...85 °C) |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10DS222487 |
| Discount Schedule | 0DS2 |
| GTIN | 785901173793 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 15.200 oz (430.913 g) |

Offer Sustainability

| | |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|