



# XUN5APXNM12

Photoelectric sensors XU, Photo electric Sensor, Hybrid, Diffuse long, Smax 1 m, PNP, Connector M12

COMMERCIALISED

## Main

|                               |                                        |
|-------------------------------|----------------------------------------|
| Range of product              | Telemecanique Photoelectric sensors XU |
| Series name                   | General purpose single mode            |
| Electronic sensor type        | Photo-electric sensor                  |
| Sensor name                   | XUN                                    |
| Sensor design                 | Compact 32 x 52                        |
| Detection system              | Diffuse                                |
| Material                      | Plastic                                |
| Type of output signal         | Discrete                               |
| Supply circuit type           | DC                                     |
| Wiring technique              | 4 wires                                |
| [Sn] nominal sensing distance | 0.7-0.7 m diffuse                      |
| Discrete output type          | PNP                                    |
| Discrete output function      | 1 NO or 1 NC programmable              |
| Electrical connection         | 1 male connector M12, 4 pins           |
| Emission                      | -                                      |

## Complementary

|                           |          |
|---------------------------|----------|
| Enclosure material        | PC/PBT   |
| Lens material             | PMMA     |
| Output type               | Discrete |
| Status LED                | -        |
| [Us] rated supply voltage | -        |
| Switching capacity in mA  | -        |
| Maximum voltage drop      | -        |

|                     |                              |
|---------------------|------------------------------|
| Current consumption | < 20 mA no load              |
| Delay first up      | 100.0000 MILLISECOND         |
| Delay response      | 0.5000 MILLISECOND           |
| Delay recovery      | -                            |
| Setting-up          | Sensitivity by potentiometer |

## Environment

|                         |                                                                                        |
|-------------------------|----------------------------------------------------------------------------------------|
| Vibration resistance    | 7 gn, amplitude = +/- 1.5 mm (f = 10-55 Hz) for every axis conforming to IEC 60068-2-6 |
| Shock resistance        | 30 gn (duration = 11 ms) for every axis conforming to IEC 60068-2-27                   |
| IP degree of protection | -                                                                                      |

## Packing Units

|                              |                   |
|------------------------------|-------------------|
| Unit type of package 1       | PCE               |
| Number of units in package 1 | 1                 |
| Package 1 height             | 1.8000 CENTIMETER |
| Package 1 width              | 1.6000 CENTIMETER |
| Package 1 length             | 4.4000 CENTIMETER |
| Package 1 weight             | 14.0000 GRAM      |

## Offer Sustainability

For all Reach Rohs enquiries contact us at [sustainability@tesensors.com](mailto:sustainability@tesensors.com)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Updated: 18/12/2024

