



Powering Business Worldwide

Power Distribution Unit (PDU) - Accessory adds additional outlet types to dual voltage UPS System

MODEL NUMBER: **PDU6K**

Description

Tripp Lite's PDU6K AC power distribution unit offers 24 amp, 240/120V capacity in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for wallmount, under-counter or 2U rackmount installation. Detachable flanges allow user configuration in dozens of potential mounting schemes. Includes 8 outlets total (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R), with NEMA L14-30P input plug. 4 ft. AC input cord.

PLUG/OUTLETS: Input: NEMA L14-30P/Output: 1 L5-30, 1 L5-20, 2 L6-30, 2 L6-20, 2 6-20R

ELECTRICAL: 240V AC input, 240/120V AC output

FORMAT: Supports 19 in. rackmount (2U), wallmount and under-counter

Features

- Corded AC power distribution unit with 8 output receptacles
- Versatile all-metal cabinet with detachable mounting flanges allows wallmount, under-counter and 19 inch rackmount mounting in 2U format
- 4 120V and 4 240V output receptacles (1xL5-30R, 1xL5-20R, 2xL6-30R, 2xL6-20R, 1x6-20R)
- 4 ft. AC cord with L14-30 plug-in connection
- Removable plug enables hardwire input connection

Highlights

- 8 outlet PDU system adds 240 and 120V output receptacles to select dual voltage 240/120V UPS systems
- Includes 4 ft. cord with L14-30 plug
- Input plug supports hardwire input connection
- Supports installation in 2U rackmount, wallmount and under-counter applications

Package Includes

- PDU6K rackmount power strip
- Instruction manual

Specifications

OVERVIEW	
UPC Code	037332119346
INPUT	
Input Phase	Single-Phase
Input Connection Type	Nema L14-30 input plug, removable for 4 wire hardwire installation
PDU Plug Type	Hardwire
Voltage Compatibility (VAC)	240
Input Cord Length (ft.)	4
Input Cord Length (m)	1.22
OUTPUT	
Output Receptacles	(1) 6-15/20R; (1) L5-20R; (1) L5-30R; (2) L6-20R; (1) L6-30R
Circuit Breaker (amps)	20
Overload Protection	20A resettable double pole breaker
PHYSICAL	
Material of Construction	Metal



Powering Business Worldwide

Power Cord Color	Black
Form Factors Supported	2U rackmount, wallmount, under-counter
Housing Color	Black
Included Mounting Accessories	Recessed rackmount installation brackets
PDU Form Factor	Horizontal (2U)
Receptacle Color	Black
Shipping Dimensions (hwd / in.)	6.50 x 18.25 x 8.25
Shipping Dimensions (hwd / cm)	16.51 x 46.36 x 20.96
Shipping Weight (lbs.)	8.00
Shipping Weight (kg)	3.63
Unit Dimensions (hwd / in.)	3.500 x 17.250 x 3.750
Unit Dimensions (hwd / cm)	8.9 x 43.8 x 9.5
Unit Weight (lbs.)	6.25
Unit Weight (kg)	2.83

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.