



Power It! 2-Outlet Pop-Up Power and Charging Dock - 2x USB-A, 6 ft. Cord, Antimicrobial Protection, Black

MODEL NUMBER: PS22POPAM











Highlights

- Pushes down out of the way flush with desktop surface when not in use
- 2 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 2 USB-A ports share 4.5A for fast charging of phones and other mobile devices
- 6 ft. input cord allows flexibility in placing devices away from wall outlet
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew

Package Includes

- PS22POPAM 2-Outlet Pop-Up Power and Charging Dock
- Owner's manual

Installs in your desktop's pre-cut grommet to charge and power up to 4 devices at the same time.

Features

Fits into Your Desktop Grommet for Reliable Power and Charging

This Power It!® dock is designed for installation in your desktop's pre-cut three-inch grommet hole. When not being used to power or charge devices, you can push down the PS22POPAM into the grommet and flush against the desktop's surface to save valuable space. To connect devices, simply pop it up out of the hole. This Pop-Up Power and Charging Dock is ideal for home and office workstations with limited desk space.

NEMA 5-15R Outlets and USB Ports Accept a Wide Range of Electronic Devices

Two NEMA 5-15R outlets and two USB-A ports (4.5A combined) are available for powering and charging your laptop, tablet, smartphone or other devices. The six-foot input cord with right-angle plug connects to a nearby AC wall outlet.

Antimicrobial Protection Helps Provide a Safer, Cleaner and Healthier Environment

The PS22POPAM features antimicrobial protection that helps resist the growth of bacteria, viruses, fungi, mold and mildew.

Specifications

OVERVIEW		
OVERVIEW		
UPC Code	037332271914	
Product Type	Power Strip	
Charging Form Factor	Strip	
Device Compatibility	Amazon Kindle; Laptop; Phone; Tablet	
INPUT		





Nominal Input Voltage(s) Supported Recommended Electrical Service Input Cord Length Details Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (It.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 H2 Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Ves CHARGING Number of Charging Ports 2 Charging Method USB Charging Ports / Amps (2) 4.2A Overcharge Protostion No SURGE / Noise SUPPRESSION Automatic Shut-Off No		
Input Cord Length Details Strip Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Ports / Amps (2) 4-2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Nominal Input Voltage(s) Supported	120V AC
Input Cord Gauge (AWG) 14 Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Recommended Electrical Service	120V
Voltage Compatibility (VAC) 120 Input Plug Type NEMA 5-15P Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / App. Overcharge Protection No SURGE / NOISE SUPPRESSION	Input Cord Length Details	Strip
Input Plug Type Input Cord Details Input Cord Length (ft.) Integrated Cord Clip No OUTPUT Frequency Compatibility Integrated Cord Clip Input Receptacles Input Cord Length (ft.) Integrated Cord Clip No OUTPUT Frequency Compatibility Input Cord Length (ft.) Input Cord	Input Cord Gauge (AWG)	14
Input Cord Details SJT Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Voltage Compatibility (VAC)	120
Input Cord Length (ft.) 6 Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Input Plug Type	NEMA 5-15P
Right-Angle Plug No Input Cord Length (m) 1.83 Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Input Cord Details	SJT
Input Cord Length (m) Integrated Cord Clip No OUTPUT Frequency Compatibility	Input Cord Length (ft.)	6
Integrated Cord Clip No OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Right-Angle Plug	No
OUTPUT Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Input Cord Length (m)	1.83
Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Integrated Cord Clip	No
Frequency Compatibility 60 Hz Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION		
Output Receptacles (2) 5-15R Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION		
Transformer Accommodation No Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION		60 Hz
Right-Angle Outlets No USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION		(2) 5-15R
USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Transformer Accommodation	No
CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No	Right-Angle Outlets	No
CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	USER INTERFACE, ALERTS & CONT	TROLS
Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Diagnostic LED(s)	Yes
Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	CHARGING	
Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Number of Charging Ports	2
Charging Ports / Amps (2) 4.2A Overcharge Protection No SURGE / NOISE SUPPRESSION	Charging Method	USB
Overcharge Protection No SURGE / NOISE SUPPRESSION	Charging Port Type	USB A (FEMALE)
SURGE / NOISE SUPPRESSION	Charging Ports / Amps	(2) 4.2A
T	Overcharge Protection	No
Automatic Shut-Off No	SURGE / NOISE SUPPRESSION	
	Automatic Shut-Off	No
DATALINE SURGE SUPPRESSION	DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection No	Cable (Coax) Protection	No
Network (Ethernet) Protection No		No
Telephone/DSL Protection No		No
PHYSICAL	DUD/OLO AL	
Color Black	PHYSICAL	





Material of Construction	Plastic	
Power Cord Color	Black	
Mounting Holes or Slots	No	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	4.20 x 4.10 x 12.00	
Shipping Dimensions (hwd / cm)	10.67 x 10.41 x 30.48	
Shipping Weight (lbs.)	1.90	
Shipping Weight (kg)	0.86	
Unit Dimensions (hwd / in.)	10.140 x 2.950 x 3.000	
Unit Dimensions (hwd / cm)	10.14 x 2.95 x 3	
Unit Weight (lbs.)	1.87	
Unit Weight (kg)	0.85	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	Yes	
Built-In Circuit Breaker	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	CAN/CSA-C22.2 No. 308 (Canada); NOM (Mexico); UL 962A	
Product Compliance	FCC Part 15 Class B (USA); RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.