




12-Outlet Vertical Power Strip, 120V, 15A, 6 ft. (1.83 m) Cord, 5-15P, 36 in.

MODEL NUMBER: PS361206









Highlights

- Ideal for applications needing multiple convenience outlets for powering a variety of electronic equipment
- 36-in. mountable housing with 12 standard NEMA 5-15R outlets and a 6-ft. power cord
- Lighted, covered On/Off switch and 15-amp circuit breaker
- Sturdy construction and heavyduty, all-metal housing

Package Includes

- PS361206
- · Mounting hardware
- Instruction manual

The PS361206 power strip provides horizontal or vertical power distribution for rackmount, raceway and workbench applications in a convenient 36-in. mountable housing.

Features

Multi-Outlet Power Distribution

Vertical or Horizontal Moun

Premium Safety Features

Heavy-Duty Housing

Specifications

OVERVIEW		
UPC Code	037332186621	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	6	
Right-Angle Plug	No	





Input Cord Length (m)	1.83	
Integrated Cord Clip	No No	
integrated out onp		
OUTPUT		
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(12) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	(6) Yes	
Right-Angle Outlets	No	
Outlet Spacing	2.64 in.	
USER INTERFACE, ALERTS & CONTROLS		
Switches	Lighted 2 position switch controls power to all outlets	
Locking Switch Cover	Transparent on/off switch cover prevents accidental turn-off	
PHYSICAL		
Color	Silver	
Material of Construction	Aluminum	
Power Cord Color	Black	
Form Factors Supported	Supports vertical or horizontal mounting in rack enclosures, raceways and a variety of other applications	
Housing Color	Silver	
Mounting Holes or Slots	No No	
Outlets Measurement (Center to Center)	2.65 in.	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	2.40 x 3.50 x 39.90	
Shipping Dimensions (hwd / cm)	6.10 x 8.89 x 101.35	
Shipping Weight (lbs.)	2.90	
Shipping Weight (kg)	1.32	
Unit Dimensions (hwd / in.)	1.250 x 1.500 x 36.000	
Unit Dimensions (hwd / cm)	3.18 x 3.81 x 91.4	
Unit Weight (lbs.)	2.27	
Unit Weight (kg)	1.03	
Outlet Spacing	2.64 in.	
Mounting Details	Includes mounting clips	
FEATURES & SPECIFICATIONS		





Antimicrobial	No	
Built-In Circuit Breaker	Yes	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL 1363; UL Listed	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.