



# Safe-IT UK BS-1363 Medical-Grade Power Strip with 4 UK Outlets, 3 m Cord

MODEL NUMBER: PS410HGUK









Distributes power to plug-connected components inside and outside patient care vicinities, including examining rooms.

#### **Features**

**Power Distribution Anywhere in Any Medical Facility**This 230V, 50/60 Hz medical-grade power strip supplies electricity to plug-connected components in operating rooms, patient-care vicinities, therapy rooms, imaging environments and administrative areas. Compliant with BS-1363 specifications, the PS410HGUK features a three-meter (10-foot) UK power cord with 13A fused Type G plug and four UK outlets.

**Exclusive Antimicrobial Protection Fights Healthcare-Acquired Infections (HAIs)**The power strip is protected by a patented antimicrobial powder coating with EPA-registered and FDA-compliant silver ionic technology. The antimicrobial surface protection is 99.9 percent effective in inhibiting the growth of bacteria and reducing the risk of HAIs in hospitals and other medical environments. The coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

Armed with the Latest Safety Features to Protect Valuable Equipment A built-in replaceable 13A fuse controls all four outlets and protects against overloads by shutting them down if the equipment load draws too much power. The switchless design prevents the unit from being accidentally shut off, which would cut essential power to all connected devices. A green mains indicator lights to signal the power strip is properly connected to an AC power source.

Long Cord Provides Enhanced MobilityThe three-meter UK power cord allows for optimum flexibility when putting together a mobile health care workstation. The PS410HGUK can be mounted in a different area from where it draws AC power, putting you in control of getting reliable power service where you need it most. For best performance, connect the Type G plug to a standard 13A isolated ground receptacle to eliminate unwanted ground noise.

**Equipotential Grounding Helps Your Equipment Perform at Its Best**The included M5 earth ground stud and 250-millimeter-long earth wire help reduce unwanted leakage currents between connected devices

Comes Ready to Install and Use Right Out of the BoxBuilt-in mounting tabs and flanges let you install the PS410HGUK on a wide variety of surfaces, including IV poles, mobile carts, crash carts and mobile medical workstations. The durable all-metal housing is designed to last a long time in demanding work environments.

## **Highlights**

- Meets BS-1363 specifications for use inside and outside patient-care vicinities
- Antimicrobial protection helps prevent the growth of bacteria, viruses, fungi, mold and mildew
- Replaceable 13A fuse shuts down all 4 UK outlets in case of overload
- Mounting tabs/flanges for installation on IV poles, mobile carts and crash carts
- Switchless design protects connected devices from dangerous accidental shutdowns

#### **Applications**

 Medical-grade power distribution for IV poles, mobile carts, crash carts and mobile medical workstations inside and outside operating rooms and other patient-care vicinities

### **Package Includes**

- PS410HGUK UK BS-1363 Medical-Grade Power Strip with 4 UK Outlets, 10-ft. (3.05 m) Cord
- Owner's manual





# **Specifications**

| OVERVIEW                           |   |  |
|------------------------------------|---|--|
| UPC Code                           | 037332203243  |  |
| INPUT                              |   |  |
| Nominal Input Voltage(s) Supported | 230V AC   |  |
| Recommended Electrical Service     | 13A 230V  |  |
| Input Connection Type              | BS1363  |  |
| Input Plug Features                | Hospital Grade Plug   |  |
| Voltage Compatibility (VAC)        | 230   |  |
| Input Plug Type                    | BS1363  |  |
| Input Cord Length (ft.)            | 10  |  |
| Right-Angle Plug                   | No  |  |
| Input Cord Length (m)              | 3.05  |  |
| Integrated Cord Clip               | No  |  |
| OUTPUT                             |   |  |
| Frequency Compatibility            | 50 / 60 Hz  |  |
| Output Receptacles                 | (4) British BS 1363A  |  |
| Circuit Breaker (amps)             | 13  |  |
| Overload Protection                | 13A in plug fuse  |  |
| Outlet Orientation                 | Single row of 4   |  |
| Right-Angle Outlets                | Yes   |  |
| USER INTERFACE, ALERTS & CONTROLS  |   |  |
| Switches                           | No power switch   |  |
| Audible Alarm                      | NO ALARM  |  |
| PHYSICAL                           |   |  |
| Color                              | Beige   |  |
| Material of Construction           | Metal   |  |
| Power Cord Color                   | White   |  |
| Form Factors Supported             | IV poles, mobile carts, crash carts and mobile medical workstations |  |
| Included Mounting Accessories      | Mounting tabs and flanges   |  |
| Mounting Holes or Slots            | Yes   |  |





| Receptacle Color                       | White                   |  |
|--|-------------------------|--|
| Shipping Dimensions (hwd / in.)        | 3.94 x 6.97 x 17.52     |  |
| Shipping Dimensions (hwd / cm)         | 10.01 x 17.70 x 44.50   |  |
| Shipping Weight (lbs.)                 | 3.66                    |  |
| Shipping Weight (kg)                   | 1.66                    |  |
| Unit Dimensions (hwd / in.)            | 1.810 x 2.990 x 13.700  |  |
| Mounting Details                       | Includes flanges        |  |
| FEATURES & SPECIFICATIONS              |                         |  |
| Antimicrobial                          | Yes                     |  |
| Built-In Circuit Breaker               | Yes                     |  |
| Antibacterial                          | No                      |  |
| Built-in Cable Management              | No                      |  |
| STANDARDS & COMPLIANCE                 |                         |  |
| Product Compliance                     | RoHS                    |  |
| WARRANTY & SUPPORT                     |                         |  |
| Product Warranty Period<br>(Worldwide) | 2-year limited warranty |  |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.