



4-Outlet Power Strip with USB-A Charging -BS1363A Outlets, 220-250V, 13A, 1.8 m Cord, BS1363A Plug, White

MODEL NUMBER: PS4B18USBW



4-outlet power strip with USB-A ports distributes electricity to home and office electronics and charges your mobile devices.

Features

35.6 cm Power Strip Delivers Electricity to 4 Devices at the Same TimeCompatible with standard electrical equipment, this Protect It!® power strip features four BS1363A outlets and a durable white plastic housing. It is ideal for powering almost anything with a compatible plug, including computers and mobile devices to appliances and power tools.

Charges 2 Mobile Devices with 2.1A of Shared PowerIn addition to AC outlets, this power strip provides USB charging for up to two mobile devices, including smartphones, tablets and e-readers. The USB-A ports eliminate the need for AC adapters for charging cords, leaving outlets available for AC equipment.

Designed to Give You Flexibility in Placing the Power Strip Where It's Most NeededThe power strip features a space-saving right-angle BS1363A plug that helps you connect to a wall outlet located behind furniture that is placed flush against the wall. The plug is attached to a 1.8-meter power cord, which gives you more choices in placing the power strip away from the connected AC outlet.

Vertical or Horizontal Mounting for Desks and WorkbenchesKeyhole-shaped mounting slots on the back of the power strip allow you to permanently install it on any flat surface, including walls, with user-supplied hardware.

Premium Safety Features Designed for Protecting Your Valuable EquipmentThe PS4B18USBW features an on/off switch with diagnostic LED that provides one-touch control over all connected devices. A built-in 13-amp circuit breaker immediately shuts down the entire power strip in case of an overload to prevent equipment damage.

Specifications

OVERVIEW

UPC Code

037332251602

Highlights

- 4 BS1363A outlets distribute power to appliances, tools, lighting and other electronics
- 1.8 m cord with BS1363A plug offers flexible placement in relation to an AC wall outlet
- 2 USB-A ports share 2.1A of power for charging phones, tablets and other mobile devices
- Rear keyhole slots enable mounting to desk or workbench for easy access to outlets
- 13A circuit breaker shuts down all UK outlets for safety in case of overload

Applications

- Distribute power to computer equipment and other devices in an office, workbench, retail or telecom environment
- Mount a power strip to the edge of a desk or workbench for easy access to outlets
- Charge a smartphone and tablet without taking up available AC outlets

Package Includes

 PS4B18USBW 4-Outlet Power Strip, British BS1363A Outlets, White





Charging Form Factor Strip Device Compatibility Phone; Tablet, Amazon Kindle NPUT 230V AC Recommended Electrical Service 230V (220 250V) Valaga Compatibility (VAC) 220-250V Darized Derivation Spin Input Plug Type British Input Ord Length (II,) S.9 Right-Angle Plug Yes Input Cord Length (III) S.9 Right-Angle Plug Yes Integrated Cord Clip No Output So / 60 Hz Output Receptacles (II) British BS 1383A Ciccui Breaker (amps) 13 Overboad Protection Combo power switch and circuit breaker Outler Orientation Right-angled Right-Angle Outlets Yes Switches To position power switch User MitterFACE, ALERTS & CONCUS Suitches Diagnostic LD0(s) Yes Number of Charging Ports 2 Charging Ports Vee Charging Ports / Amps (2) 2.1A SURCE / NOISE SUPPRESSION	Draduct Tura		
Device Compatibility Prione; Tablet; Amazon Kindle INPUT Salv AC Nominal Input Voltage(s) Supported 230V AC Recommended Electrical Service 230V (220-250V) Voltage Compatibility (VAC) 220-250 Input Plug Type British Input Cord Length (ft) 5.9 Sight-Argie Plug Yes Input Cord Length (ft) 1.80 Integrated Cord Clip No Output Cord Length (ft) 5.9 / 60 Hz Output Receptacles (a) British BS 1863A Circuit Breaker (amps) 13 Output Receptacles (a) British BS 1863A Circuit Dreaker (amps) 13 Overlead Protection Comb power switch and circuit breaker Output Orientation Right-Angie Output Right-Angie Output Yes Switches Two position power switch Origing Ports Yes Switches 2 Charging Ports Yes Switches 2 Charging Port Type USB A (FEMALE) Charging Ports / Amps	Product Type	Power Strip	
NPUT 230V AC Nominal Input Voltage(a) Supported 230V (220-250V) Voltage Compatibility (VAC) 220-350 Input Plug Type British Input Cord Length (ft.) 5.9 Right-Angle Plug Yes Input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility S0 / 60 Hz Output Receptacles Output Receptacles (4) British BS 1363A Cinctul Breaker (amps) 13 Overled Protection Combo power switch and circuit breaker Output Receptacles Yes USER INTERFACE, ALERTS & CONTUCES Diagnostic LED(s) Yes Yes User INTERFACE, ALERTS & CONTUCES Diagnostic DED(s) Yes Yes User INTERFACE, ALERTS & CONTUCES Charging Ports Diagnostic LED(s) Yes Switches Two position power switch Charging Ports / Amps 2 Charging Ports / Amps (2) 2.1 A SURCE / NOISE SUPPRESSION Includes full normal mode (H-N) and common mode			
Nominal Input Voltage(s) Supported 230V AC Recommended Electrical Service 230V (220-250V) Voltage Compatibility (VAC) 220-250 Input Plug Type British Input Plug Type British Input Cord Length (It.) 5.9 Right-Angle Plug Yes Input Cord Length (IT.) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Coulput Recognatibility Output Recognatibility 50 / 60 Hz Output Recognation Combo power switch and circuit breaker Output Recognation Right-angled Site NTERFACE, ALERTS & CONTER Source <t< td=""><td>Device Compatibility</td><td>Phone; Tablet; Amazon Kindle</td></t<>	Device Compatibility	Phone; Tablet; Amazon Kindle	
Recommended Electrical Service 230V (220-250V) Voltage Compatibility (VAC) 220-250 Input Plug Type Brilish Input Cord Length (It.) 5.9 Right-Angle Plug Yes Input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (d) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Outed Portection Combo power switch and circuit breaker Outed Portection Right-Angle Outlets Yes Support State	INPUT		
Voltage Compatibility (VAC) 220-250 Input Plug Type British Input Cord Length (ft.) 5.9 Right-Angle Plug Yes Input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (d) British BS 1363A Circuit Breaker (amps) 13 Combo power switch and circuit breaker Outlet Orientation Right-Angle d Right-Angle Outlets Yes User INTERFACE, ALERTS & CONTOLS Soriches Diagnostic LED(s) Yes Switches Two position power switch Charging Ports Charging Ports 2 Charging Ports 2 Charging Ports / Anps (2) 2.1A SUPER SUPPRESSION Date Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shu-Off No	Nominal Input Voltage(s) Supported	230V AC	
Input Plug Type British input Cord Length (ft.) 5.9 Right-Angle Plug Yes input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Cord Length (m) Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTEX Diagnostic LED(s) Yes Yes Switchas Two position power switch Charging Ports Charging Ports Surface Charging Ports Surface Suppression	Recommended Electrical Service	230V (220-250V)	
Input Cord Length (ft.) 5.9 Right-Angle Plug Yes Right-Angle Plug Yes Input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING CHARGING 2 Charging Ports 2 Clarging Port Type USB A (FEMALE) Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A DATALINE SURGE SUPPRESSION DATALINE SURGE SUPPRESSION	Voltage Compatibility (VAC)	220-250	
Right-Angle Plug Yes Input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Two position power switch Charging Ports 2 Charging Method USB Charging Ports 2 Charging Ports (2) 2.1A SURCE / NOISE SUPPRESSION Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shu-Off No	Input Plug Type	British	
Input Cord Length (m) 1.80 Integrated Cord Clip No OUTPUT Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & COTTOLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Method USB Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Input Cord Length (ft.)	5.9	
Integrated Cord Clip No output Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Combo power switch and circuit breaker Outlet Orientation Right-angled Right-angled Right-Angle Outlets Yes Yes USER INTERFACE, ALERTS & CONTON Diagnostic LED(s) Yes Yes Diagnostic LED(s) Yes Yes CHARGING CHARGING Charging Method USB Charging Ports 2 Charging Ports / Amps 2	Right-Angle Plug	Yes	
OUTPUT 50 / 60 Hz Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING Charging Ports 2 Charging Ports 2 Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURCE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Input Cord Length (m)	1.80	
Frequency Compatibility 50 / 60 Hz Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SuitCes LUPRESSION Protection Modes Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Integrated Cord Clip	No	
Output Receptacles (4) British BS 1363A Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Port Type USB Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	OUTPUT		
Circuit Breaker (amps) 13 Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTOLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Frequency Compatibility	50 / 60 Hz	
Overload Protection Combo power switch and circuit breaker Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Output Receptacles	(4) British BS 1363A	
Outlet Orientation Right-angled Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTRUS Diagnostic LED(s) Yes Switches Two position power switch CHARGING CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Circuit Breaker (amps)	13	
Right-Angle Outlets Yes USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Overload Protection	Combo power switch and circuit breaker	
USER INTERFACE, ALERTS & CONTROLS Diagnostic LED(s) Yes Switches Two position power switch CHARGING CHARGING USB Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Outlet Orientation	Right-angled	
Diagnostic LED(s) Yes Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Right-Angle Outlets	Yes	
Switches Two position power switch CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A surge / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	USER INTERFACE, ALERTS & CONTROLS		
CHARGING Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Diagnostic LED(s)	Yes	
Number of Charging Ports 2 Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Switches	Two position power switch	
Charging Method USB Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	CHARGING		
Charging Port Type USB A (FEMALE) Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Number of Charging Ports	2	
Charging Ports / Amps (2) 2.1A SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No DATALINE SURGE SUPPRESSION	Charging Method	USB	
SURGE / NOISE SUPPRESSION Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No DATALINE SURGE SUPPRESSION	Charging Port Type	USB A (FEMALE)	
Protection Modes Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression Automatic Shut-Off No	Charging Ports / Amps	(2) 2.1A	
Automatic Shut-Off No DATALINE SURGE SUPPRESSION	SURGE / NOISE SUPPRESSION		
DATALINE SURGE SUPPRESSION	Protection Modes	Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression	
	Automatic Shut-Off	No	
Cable (Coax) Protection No	DATALINE SURGE SUPPRESSION		
	Cable (Coax) Protection	No	





Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Color	White	
Material of Construction	Plastic	
Power Cord Color	White	
Housing Color	White	
Mounting Holes or Slots	Yes	
Receptacle Color	White	
Shipping Dimensions (hwd / in.)	14.00 x 3.40 x 2.90	
Shipping Dimensions (hwd / cm)	35.56 x 8.64 x 7.37	
Shipping Weight (lbs.)	0.98	
Shipping Weight (kg)	0.44	
Unit Dimensions (hwd / in.)	14.000 x 3.000 x 2.600	
Unit Dimensions (hwd / cm)	11.6 x 2.9 x 2.9	
Unit Weight (Ibs.)	0.81	
Unit Weight (kg)	0.37	
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
Built-In Circuit Breaker	Yes	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; CE (Europe); REACH; UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.