



Safe-IT 3-Outlet Spherical Surge Protector, 5-15R Outlets, 4 USB Charging Ports, 8 ft. (2.4 m) Cord, Antimicrobial Protection

MODEL NUMBER: TLP38UAM











Safely charges and powers up to 7 devices, including laptops and tablets, during important workplace meetings and conferences.

Features

Sphere-Shaped 3-Outlet Surge Protector Safeguards Your Sensitive Electronics

Ideal for your home or office workstation or travel use, this Safe-IT™ power ball features a surge suppression rating of 540 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP38UAM protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your laptops, projector, printer and other conference-table electronics into three NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. The outlets offer easy 360-degree access to power and are located on different sides to accept bulky transformers without blocking adjacent outlets.

USB Ports Share 4.8 Amps of Charging Power

Four USB-A ports are available for charging your smartphones, tablets and other USB mobile devices. They share 4.8A of charging power, which is plenty for delivering ample power to demanding devices.

Filtering EMI/RFI Line Noise Helps Your Equipment Perform Better

This surge protector filters out disruptive electromagnetic and radio frequency interference that can inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Antimicrobial Protection Helps Provide a Safer, Cleaner and Healthier Work Environment

The Safe-IT TLP38UAM features antimicrobial protection that helps resist the growth of bacteria, viruses, fungi, mold and mildew.

Premium Safety Features Protect Your Valuable Equipment

Automatic shutoff permanently cuts power to outlets if the protection circuit is incapacitated, preventing equipment damage and indicating replacement is required. Safety shutters on unused outlets help prevent electrical shock. A green LED confirms your connected equipment is protected. Mounting slots allow permanent installation on any flat surface.

Highlights

- 3 NEMA 5-15R outlets are spaced apart to accommodate bulky transformers
- 540 joules protect your valuable electronics against dangerous surges and spikes
- 4 USB ports share 4.8A for fast charging of phones, tablets and other mobile devices
- Ball shape takes up little room on your conference table and easily packs away for travel
- Antimicrobial protection helps resist the growth of bacteria, viruses, fungi, mold and mildew

Package Includes

- TLP38UAM 3-Outlet Surge Protector Ball
- · Owner's manual





Compact Spherical Design Gives You Plenty of Options for Installation and Use

Less than four inches in diameter, the spherical TLP38UAM fits easily into your home or office workspace, providing power and USB charging at your fingertips. Its compact design also makes the surge protector ideal for travel, fitting easily into your backpack, laptop bag or suitcase for use in hotels, conference rooms and cruise ships. Mounting slots allow permanent installation on any flat surface.

Specifications

OVERVIEW		
UPC Code	037332265784	
Device Compatibility	Phone; Tablet	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V	
Input Cord Gauge Type	14 gauge; SJT	
Voltage Compatibility (VAC)	120	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	8	
Right-Angle Plug	No	
Input Cord Length (m)	2.44	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	60 Hz	
Output (Watts)	1800	
Output Receptacles	(3) 5-15R	
Circuit Breaker (amps)	15	
Transformer Accommodation	No	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Diagnostic LED Details	1 Green LED - Protection	
CHARGING		
Number of Charging Ports	4	
Total Charging Amps	4.8A	
Total Charging Watts	24	





Charging Method	USB	
Charging Port Type	USB A (FEMALE)	
Charging Ports	(2) 2.4A Quick Charge	
Charging Ports Details	2 x USB-A (2.4A) charging ports for iPhones and iPads2 x USB-A (2.4A) charging ports for Android and other devices	
Charging Ports / Amps	(4) 4.8A	
Overcharge Protection	No	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	540	
AC Suppression Response Time	< 1 ns	
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression	
UL1449 Let Through Rating	500	
EMI / RFI Filtering	Yes	
Immunity	Conforms to IEE 587/ANSI C62.41	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Plastic	
Power Cord Color	Black	
Housing Color	Black; Light Gray	
Mounting Holes or Slots	Yes	
Receptacle Color	Black	
Shipping Dimensions (hwd / in.)	6.30 x 5.20 x 3.50	
Shipping Dimensions (hwd / cm)	16.00 x 13.21 x 8.89	
Shipping Weight (lbs.)	1.75	
Shipping Weight (kg)	0.79	
Unit Dimensions (hwd / in.)	3.590 x 3.560 x 3.320	
Unit Dimensions (hwd / cm)	9.1 x 9.0 x 8.4	
Unit Weight (lbs.)	1.18	
Unit Weight (kg)	0.54	
Input Cord Color	Black	





Mounting Details	Keyhole mounting slots in base	
FEATURES & CRECIFICATIONS		
FEATURES & SPECIFICATIONS		
Rotatable Outlets	No	
Antimicrobial	No	
GaN Technology	No	
STANDARDS & COMPLIANCE		
Product Certifications	UL 1449; UL 1363	
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2025 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.