

## Industrial Power Strip, 4-Outlet, 6 ft. (1.8 m) Cord, Locking Switch Cover

MODEL NUMBER: **UL603CB-6**



### Highlights

- 4 outlets
- 6-ft. (1.83 m) cord
- 7.38" length
- All metal housing
- Lighted on/off switch with locking safety cover

### Package Includes

- UL603CB-6 Power Strip
- Warranty information
- Instruction manual

### Description

The UL603CB-6 Power Strip offers a convenient method of power distribution in workbench, wall-mount or floor-mount applications. Includes four NEMA 5-15R output receptacles with 1.25-inch center-to-center spacing, six-foot (1.8-meter) AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes UL603CB-6 ideal for distributing alternate waveform UPS or generator power. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive blue/gray color scheme.

### Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 4 NEMA 5-15R output receptacles with 1.25 inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs for installation in a wide variety of applications
- UL1363 (USA), cUL (Canada)
- 15 amp power handling capacity with circuit breaker

## Specifications

| OVERVIEW                           |               |
|------------------------------------|---------------|
| UPC Code                           | 037332103734  |
| INPUT                              |               |
| Nominal Input Voltage(s) Supported | 120V AC       |
| Recommended Electrical Service     | 15A 120V      |
| Input Cord Gauge Type              | 14 gauge; SJT |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                                   |                                                                             |
|---------------------------------------------------|-----------------------------------------------------------------------------|
| Voltage Compatibility (VAC)                       | 120                                                                         |
| Input Plug Type                                   | NEMA 5-15P                                                                  |
| Input Cord Length (ft.)                           | 6                                                                           |
| Right-Angle Plug                                  | No                                                                          |
| Input Cord Length (m)                             | 1.83                                                                        |
| Integrated Cord Clip                              | No                                                                          |
| <b>OUTPUT</b>                                     |                                                                             |
| Frequency Compatibility                           | 50 / 60 Hz                                                                  |
| Output (Watts)                                    | 1800                                                                        |
| Output Receptacles                                | (4) 5-15R                                                                   |
| Circuit Breaker (amps)                            | 15                                                                          |
| Transformer Accommodation                         | (2) Yes                                                                     |
| Outlet Orientation                                | Single row of 4                                                             |
| Right-Angle Outlets                               | No                                                                          |
| Outlet Spacing                                    | 1.25 in.                                                                    |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>      |                                                                             |
| Switches                                          | Lighted 2 position switch controls power to all outlets                     |
| Locking Switch Cover                              | Transparent on/off switch cover prevents accidental turn-off                |
| <b>PHYSICAL</b>                                   |                                                                             |
| Color                                             | Gray                                                                        |
| Material of Construction                          | Metal                                                                       |
| Power Cord Color                                  | Black                                                                       |
| Housing Color                                     | Blue; Gray                                                                  |
| Mounting Holes or Slots                           | Yes                                                                         |
| Slot or Hole Mount Measurement (Center to Center) | Distance between keyhole tabs = 127mm; Distance between end tabs = 201.12mm |
| Outlets Measurement (Center to Center)            | 1.18 in.                                                                    |
| Receptacle Color                                  | Black                                                                       |
| Shipping Dimensions (hwd / in.)                   | 2.00 x 9.60 x 6.10                                                          |
| Shipping Dimensions (hwd / cm)                    | 5.08 x 24.38 x 15.49                                                        |
| Shipping Weight (lbs.)                            | 1.60                                                                        |
| Shipping Weight (kg)                              | 0.73                                                                        |
| Unit Dimensions (hwd / in.)                       | 1.500 x 8.540 x 2.500                                                       |
| Unit Dimensions (hwd / cm)                        | 18.75 x 6.4 x 3.8                                                           |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                     |                                |
|-------------------------------------|--------------------------------|
| Outlet Spacing                      | 1.25 in.                       |
| Mounting Details                    | Includes flanges               |
| FEATURES & SPECIFICATIONS           |                                |
| Antimicrobial                       | No                             |
| Built-In Circuit Breaker            | Yes                            |
| STANDARDS & COMPLIANCE              |                                |
| Product Certifications              | cUL Listed; UL 1363; UL Listed |
| Product Compliance                  | RoHS                           |
| WARRANTY & SUPPORT                  |                                |
| Product Warranty Period (Worldwide) | Lifetime limited warranty      |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.