


Reflective Object Sensor

OPB606A, OPB606B, OPB606C
OPB607A, OPB607C

Obsolete (OPB607B)



Features:

- Choice of phototransistor (OPB606) or photodarlington (OPB607) output
- Unfocused for sensing diffuse surface
- Low cost plastic housing
- Filtered (OPB606, OPB607)

Description:

OPB606 consists of an infrared Light Emitting Diode (LED) and an NPN silicon phototransistor which are mounted “side-by-side” on parallel axes in a black opaque plastic housing.

The **OPB607** consists of an infrared Light Emitting Diode (LED) and an NPN silicon photodarlington which are mounted “side-by-side” on parallel axes in a black plastic housing.

The emitting diode and phototransistor of both the **OPB606** and **OPB607** are encapsulated in a filtering epoxy that reduces ambient light noise. On both models, the phototransistors respond to radiation from the emitter only when a reflective object passes within the field of view.


Custom electrical, wire and cabling and connectors are available. Contact your local representative or OPTEK for more information.

Applications:

- Non-contact reflective object sensor
- Assembly line automation
- Machine automation
- Machine safety
- End of travel sensor
- Door sensor

Pin #	LED	Pin #	Transistor
4	Cathode	1	Collector
3	Anode	2	Emitter

Ordering Information								
Part Number	LED Peak Wavelength	Sensor	Typical Reflection Distance Inch (mm)	Lead Length				
OPB606A	935 nm	Transistor	0.050" (1.27 mm)	0.18" (Min)				
OPB606B								
OPB606C								
OPB607A		Darlington						
OPB607B Obsolete								
OPB607C								



RoHS

DIMENSIONS ARE IN:

[MILLIMETERS]
INCHES

CONTAINS POLYSULFONE

To avoid stress cracking, we suggest using ND Industries' **Vibra-Tite** for thread-locking. **Vibra-Tite** evaporates fast without causing structural failure in OPTEK's molded plastics.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

Reflective Object Sensor

OPB606A, OPB606B, OPB606C

OPB607A, OPB607C

Obsolete (OPB607B)



Electrical Specifications

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)


Storage & Operating Temperature Range	-40° C to +85° C
Lead Soldering Temperature [1/16 inch (1.6 mm) from the case for 5 sec. with soldering iron] ⁽¹⁾	260° C
Input Diode	
Forward DC Current	50 mA
Peak Forward Current (1 μs pulse width, 300 pps)	3 A
Reverse DC Voltage	2 V
Power Dissipation ⁽²⁾	75 mW
Output Phototransistor (OPB606) / Output Photodarlington (OPB607)	
Collector-Emitter Voltage OPB606A, OPB606B, OPB606C OPB607A, OPB607C	30 V 15 V
Emitter-Collector Voltage	5 V
Collector DC Current OPB606A, OPB606B, OPB606C OPB607A, OPB607C	25 mA 125 mA
Power Dissipation ⁽²⁾	75 mW

Notes:


(1) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.

(2) Derate linearly 1.25 mW/° C above 25° C.

OPB606 - Output vs Distance



OPB606 - Output vs Distance (Retro)



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTeK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Reflective Object Sensor

OPB606A, OPB606B, OPB606C
OPB607A, OPB607C
Obsolete (OPB607B)




Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Input Diode (See OP165 for additional information)						
V _F	Forward Voltage	-	-	1.7	V	I _F = 20 mA
I _R	Reverse Current	-	-	100	μA	V _R = 2 V
Output Phototransistor (see OP268 for additional information—for reference only)						
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage OPB606 OPB607	30 15	- -	- -	V V	I _C = 100 μA
V _{(BR)ECO}	Emitter-Collector Breakdown Voltage	5	-	-	V	I _E = 100 μA
I _{CEO}	Collector Dark Current OPB606 OPB607	- -	- -	100 250	nA nA	V _{CE} = 5 V, I _F = 0
Combined (see OP508 or OP509 for additional information—for reference only)						
V _{CE(SAT)}	Collector-Emitter Saturation Voltage OPB606 OPB607	- -	- -	0.4 1.1	V	I _F = 20 mA, I _C = 100 μA, d = 0.053" (1.45 mm) ⁽¹⁾⁽²⁾ I _F = 20 mA, I _C = 2 mA, d = 0.053" (1.45 mm) ⁽¹⁾⁽²⁾
I _{C(ON)}	On-State Collector Current OPB606A OPB606B OPB606C OPB607A OPB607C	500 350 200 25 10	- - - - -	- - - - -	μA μA μA mA mA	I _F = 20 mA, V _{CE} = 5 V, d = 0.053" (1.45 mm) ⁽¹⁾⁽²⁾
I _{C(OFF)}	Off-State Collector Current OPB606 OPB607	- -	- -	200 10	nA μA	V _{CE} = 5 V, I _F = 20 mA ⁽³⁾ V _{CE} = 5 V, I _F = 20 mA ⁽³⁾

Notes:

- (1) "d" is the distance from the assembly measurement surface to the reflective surface.
- (2) Measured using Eastman Kodak neutral white test card with 90% diffuse reflectance as a reflecting surface. Reference: Eastman Kodak, Catalog # E 152 7795.
- (3) On OPB606, off-state collector current $I_{C(OFF)}$ is measured with no reflective surface in the optical path. On OPB607, Crosstalk (I_{α}) is the collector current measured with the indicated current in the input diode and with no reflecting surface.
- (4) All parameters tested using pulse techniques.



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.