

UIA(UIB)336 36W Series For Portable Switching AC/DC Adaptor
UI (UIT) 336 36W Series For C.C. & C.V. TYPE

MODEL	INPUT	OUTPUT
UI(T)/UIA(B)336-12	AC100V~240V (50/60Hz)	12V 3.0A
UI(T)/ UIA(B)336-15		15V 2.4A
UI(T)/UIA(B)336-16		16V 2.2A
UI(T)/UIA(B)336-18		18V 2.0A
UI(T)/UIA(B)336-24		24V 1.5A
UI(T)/UIA(B)336-35		35V 1.0A

*** UI/UIA : IEC320 C8 / 2PIN

*** UIT/UIB : IEC320 C6 / 3PIN

FEATURE

- ? UI Series with Constant Current & Constant Voltage
- ? UIA Series with Constant Voltage
- ? Mini Size and Easy Portable
- ? Desktop IEC320/2 or 3 pin Inlet

APPLICATION

- ? LCD Monitor
- ? Note Book PC
- ? Communication Terminals
- ? Wireless Lan Station
- ? Hard Disk
- ? Portable Device or Machine

DIMENSION: L*W*H: 95.9*43.8*28

INPUT/OUTPUT SPECIFICATION

Input Voltage:	AC100V-240V,50/60Hz
Range Voltage:	AC 90V-264V,47/63Hz
Output Power:	36W
Output Voltage:	12V-35V
Over Current Protection:	120% Min
Over Voltage Protection:	120% Min
Short Protection:	Auto Recovery
Load Regulation:	±5%

GENERAL SPECIFICATION

Operating Temperature:	0 ~ 40?
Operating Relative Humidity:	5 ~ 95%RH
Storage Temperature:	-20 ~ 85 ?
Withstanding Voltage:	AC 3000V/Min (between Input & Output),10mA(Max.)
Insulation Resistance:	DC500V 100M?(Min.) (between Input & Output)
Efficiency:	70% Min

SAFETY

- ? UI: PSE,CB,UL / CUL,CE,TUV, BSMI
- ? UIA : PSE ,UL / CUL,CE,CB,CCC, EK(12-24)TUV, BSMI
- ? UIB/UIT: CB,UL / CUL,CE, C-Tick, BSMI



UNIFIVE CO.,LTD.

3-33-14 Nakakasai, Edogawa -ku Tokyo Japan 134 -0083
TEL ? +81-3-5605 -3222 FAX? +81-3-5605 -3220

UNIFIVE TECHNOLOGY CO.,LTD.

4F., No.269, Siangyang Rd., Fongyuan City, Taichung County 420, Taiwan (R.O.C.)
TEL ? +886-4-2523 -0886 FAX? + 886-4-2523 -0913