

UM1700 SERIES

60 Watt DC-DC Converters

- Low Profile 0.91 Inch High
- Efficiency to 84%
- 2:1 Input Range
- PC Mounting
- Pi Input Filter
- OVP on All Outputs

SPECIFICATIONS

All specifications are typical at nominal line, full load and 25°C unless otherwise noted.

INPUT SPECIFICATIONS

Input Voltage Range, 12V	9-18V
24V	18-36V
48V	36-72V
Input Filter	Pi Network
Surge Protection	Transient Clamp
Reverse Voltage Protection	Internal Shunt Diode Use External Fuse

OUTPUT SPECIFICATIONS


Voltage Accuracy, Primary Output	±1.0% max.
-5V, Output	±3.0% max.
Auxiliary Output Balance ¹	±2.0% max.
Voltage Adjustment ²	±1.0%
Line Regulation, HL-LL	±0.5% max.
-5V, Output	±1.0% max.
Load Regulation ³ FL-1/4FL	
Single Output	±1.0% max.
Dual Output	±2.0% max.
-5V, Output	±1.0% max.
Ripple and Noise, 20MHz BW	10mV RMS max. 75mV P-P max.
Temperature Coefficient	±0.02%/°C max.
Voltage Stability, 24 Hours	±0.05% max.
Transient Response ⁴ , ±1% Error Band	
25% Step Load Change	500 µsec. max.
Remote Sense ⁵	Output 1
Short Circuit Protection, All Outputs	Continuous
Overvoltage Protection ⁶	OVP Clamp All Outputs

GENERAL SPECIFICATIONS


Isolation Voltage, Input to Output	500 VDC min.
Input to Case	250 VDC min.
Isolation Resistance	
Input to Output	10 ⁸ Ohms min.
Input to Case	10 ⁶ Ohms min.
Switching Frequency	100KHz
Operating Temperature Range	
Ambient, None Derating	-25°C to +55°C
With Optional Heatsink	-25°C to +71°C
Case	-25°C to +85°C
Derating, above 85°C Case	Linearly to Zero Power at +100°C
Storage Temperature Range	-55°C to +105°C
Cooling	Free-Air Convection or Conduction
Weight, without Heatsink	16 oz. (454 grams)
EMI/RFI	Six-Sided Continuous Shield
Case Material	Black Coated Aluminum with Non-Conductive Base

NOTES

1. Maximum difference between the voltage magnitudes of outputs 2 & 3 for triples: 3 & 4 for quads.
2. All models except triples have provision for output voltage adjustment. See connection table and external output trimming information.
3. No minimum load required for operation
4. Any output.
5. REMOTE SENSE is provided on all singles, and on output #1 of duals and triples. It will compensate for up to 1V drop between converter and load. If remote sense is not being used, the +Sense should be connected to its corresponding +Output, and likewise the -Sense should be connected to its corresponding -Output.
6. 5V output clamped at 6.8V, 12V or 15V outputs clamped at 18V.
7. OUTPUT ISOLATION ON DUALS: The two outputs are isolated, and can be referenced as either positive or negative, No load sharing is possible.

EXTERNAL OUTPUT TRIMMING	
SINGLE & DUAL OUTPUT	QUAD OUTPUT
Output may optionally be externally trimmed (±10%) with a fixed resistor or an external trimpot as shown.	Output may optionally be externally trimmed (±10%) with a fixed resistor
	

REMOTE ON/OFF CONTROL	
Terminal 6 Control	
Logic Compatibility	COMS or Open Collector TTL
Control Voltage, ON	+5.5V or Open Circuit
OFF	+1.2V
Converter Shutdown Idle Current	5mA
Control Common	Input Terminal 2



**UNIVERSAL
MICROELECTRONICS**

UM1700

1 of 2

3,27TH RD., TAICHUNG INDUSTRIAL PARK,
TAICHUNG, TAIWAN, R.O.C.
TEL: 886-4-23590096 FAX: 886-4-23590129

REV.2

