


1220 Alderwood Ave.
Sunnyvale, CA 94089

Tel: (408) 577-1888
Fax: (408) 577-1368



V A S T E C H I N C.

Your number one source for PC Mods & Accesories



Constant Current LED Driver Information 2008

Drawing	Model	Input		Output			Dimension (mm)	Number of LED supported	Waterproof standard	Certificate
		Voltage (Vac)	Frequenc y(Hz)	Voltage (Vdc)	Current (mA)	Max. Power (W)				
	LD-CU3503AF	100-240	50-60	3-12	350	3	65L*35W*23H	1W LED: 1-3	IP66	UL, cUL, CE & RoHS
	LD-CU7006AF	100-240	50-60	3-12	700	6	65L*35W*23H	1W LED:2-6 or 3W LED: 1-2	IP66	UL, cUL, CE & RoHS
	LD-CU3536AF	100-240	50-60	3-36	350	10	65L*35W*23H	1W LED: 3-8.	IP66	UL, cUL, CE & RoHS
	LD-CU7021AF	100-240	50-60	3-21	700	3	65L*35W*23H	1W LED: 2-8. 3W LED: 1-3	IP66	UL, cUL, CE & RoHS
	LD-PI3503AF	100-240	50-60	3-12	350	3	67L*37W*27H	1W LED: 1-3	IP66	UL, cUL, CE & Rohs
	LD-PI7006AF	100-240	50-60	3-12	700	6	67L*37W*27H	1W LED:2-6 or 3W LED: 1-2	IP66	UL, cUL, CE & Rohs
	LD-PI3536AF	100-240	50-60	3-36	350	10	67L*37W*27H	1W LED: 3-8.	IP66	UL, cUL, CE & Rohs
	LD-PI7021AF	100-240	50-60	3-21	700	3	67L*37W*27H	1W LED: 2-8. 3W LED: 1-3	IP66	UL, cUL, CE & Rohs