


## NTC Thermistors, Mini Lug Sensors



### QUICK REFERENCE DATA

| PARAMETER                                                      | VALUE                |
|----------------------------------------------------------------|----------------------|
| Resistance value at 25 °C                                      | 10 kΩ to 47 kΩ       |
| Tolerance on $R_{25}$ - value                                  | ± 2 % to ± 3 %       |
| $B_{25/85}$ value                                              | 3740K to 3984K       |
| Tolerance on $B_{25/85}$ - value                               | ± 0.5 % to ± 1.5 %   |
| Maximum dissipation at 25 °C                                   | 100 mW               |
| Thermal time constant $\tau$                                   | ≈ 5 s                |
| Dissipation factor                                             | 10 mW/K              |
| Operating temperature range at zero power                      | - 40 °C to 125 °C    |
| Min. dielectric withstanding voltage between terminals and lug | 1000 V <sub>AC</sub> |
| R/T values                                                     | See table            |
| Climatic category (IEC 60539)                                  | 40/125/56            |
| Weight (without connector)                                     | 0.5 g                |
| Weight (with connector)                                        | 0.6 g                |

#### Note

- Other  $R_{25}$  values and tolerances available upon request

### FEATURES

- Fast time response for surface applications compared to industry standard NTC lug sensors
- Reduced thermal gradient, due to the use of small dimensions and nickel conductor, allowing for an accurate surface temperature measurement
- The sensor is not suitable for being permanently in contact with water or liquids
- Small size connector and small lug ring tongue terminal, allowing for temperature sensing at locations where only limited space is available
- Connector ZHR-2 (optional)
- Compliant to RoHS directive 2002/95/EC



**RoHS**  
COMPLIANT

### APPLICATIONS

Thermistors used for surface temperature sensing and control in:

- Computer equipment
- MOSFETS, IC's, Power Electronics, heatsink temperature control
- Consumer appliances
- Industrial equipment
- Automotive equipment

### DESCRIPTION

Miniature insulated chip thermistor with a negative temperature coefficient in accordance with IEC 60539. The device has no marking.

### MOUNTING

- The sensor can be mounted by means of a screw. For stud size, metric 2 mm M2/american stud #1 or #2
- The end wire can be soldered, welded or crimped to a connector
- Optional connector for Wire-to-Wire or Wire-to-Board connections

### ELECTRICAL DATA AND ORDERING INFORMATION

| $R_{25}$ - VALUE (kΩ) | $R_{25}$ - TOL. | $B_{25/85}$ - VALUE (K) | $B_{25/85}$ - TOL. | SAP MATERIAL NO.  | DESCRIPTION                         | R/T TABLE |
|-----------------------|-----------------|-------------------------|--------------------|-------------------|-------------------------------------|-----------|
| 10                    | ± 3 %           | 3984                    | ± 0.5 %            | NTCALUGE4103H103  | NTC Mini-Lug 10K 3 %                | Table 1   |
| 10                    | ± 3 %           | 3984                    | ± 0.5 %            | NTCALUGE3103H103C | NTC Mini-Lug 10K 3 % with connector | Table 1   |
| 10                    | ± 2 %           | 3984                    | ± 0.5 %            | NTCALUGE4103G103  | NTC Mini-Lug 10K 2 %                | Table 2   |
| 10                    | ± 2 %           | 3984                    | ± 0.5 %            | NTCALUGE3103G103C | NTC Mini-Lug 10K 2 % with connector | Table 2   |
| 12                    | ± 3 %           | 3740                    | ± 1.5 %            | NTCALUGE4123H103  | NTC Mini-Lug 12K 3 %                | Table 3   |
| 12                    | ± 3 %           | 3740                    | ± 1.5 %            | NTCALUGE3123H103C | NTC Mini-Lug 12K 3 % with connector | Table 3   |
| 47                    | ± 3 %           | 3740                    | ± 1.5 %            | NTCALUGE4473H103  | NTC Mini-Lug 47K 3 %                | Table 4   |
| 47                    | ± 3 %           | 3740                    | ± 1.5 %            | NTCALUGE3473H103C | NTC Mini-Lug 47K 3 % with connector | Table 4   |


Ordering information can be found on: [www.vishay.com/doc?33036](http://www.vishay.com/doc?33036)

# NTC A LUG....103 Series

Vishay BCcomponents NTC Thermistors, Mini Lug Sensors



## DIMENSIONS in millimeters



| L <sub>1</sub> | L <sub>2</sub> | L <sub>3</sub> | L <sub>4</sub> | L <sub>1</sub> + L <sub>3</sub><br>(item without<br>connector) | Ø D <sub>1</sub> | Ø D <sub>2</sub> | Ø D <sub>3</sub> | Ø D <sub>4</sub> | T         | Pitch P   |
|----------------|----------------|----------------|----------------|----------------------------------------------------------------|------------------|------------------|------------------|------------------|-----------|-----------|
| 70 ± 5         | 4 ± 1          | 11.5 ± 0.3     | 8.8 ± 0.3      | 81.5 ± 5                                                       | 2.2 ± 0.3        | 5.5 ± 0.3        | 3.4 ± 0.3        | 0.35 ± 0.1       | 0.8 ± 0.1 | 1.5 ± 0.3 |

### Notes

- (1) Vishay Thermistor chip NTC, with epoxy coating and middle buffer layer
- (2) Metal ring lug, tin plated
- (3) Insulated leads: AWG#32, monostranded, diam 0.20 mm, silver plated Nickel, PEEK insulation, diameter 0.35 mm
- (4) End wire stripped or 2-poles connector crimped (optional)

## MOUNTING

- With screw size metric M2, or American stud 1-2
- For the type without connector ('103'), the electrical connection can be made by soldering or crimping or welding.
- For the type with connector ('103C'), the connector can mate with following counter-connectors <sup>(5)</sup>:
  - A) One of the PCB Board connector - Through Hole:
    - JST B 2B-ZR (top entry)
    - JST S 2B-ZR (side entry)
    - JST B 2B-ZR-3.4 (top entry, for 1.6 mm board)
    - JST S 2B-ZR-3.4 (side entry, for 1.6 mm board)
  - B) One of the PCB Board connector - SMT Surface Mount:
    - JST S 2B-ZR-SM2-TF (SM2 side entry)
    - JST B 2B-ZR-SM3-TF (SM3 top entry)
    - JST S 2B-ZR-SM3A-TF (SM3 side entry)
    - JST B 2B-ZR-SM4-TF (SM4 top entry)
    - JST S 2B-ZR-SM4A-TF (SM4 side entry)
  - C) The Wire-to-wire connector:
    - JST ZMR-02 housing (x 1) + JST SMM-033T-P0.5 terminals (x 2)

### Note

- <sup>(5)</sup> Additional details and dimensions can be found in JST ZH and JST ZM datasheets.

## PACKAGING

Available in plastic bags of 250 pieces. SPQ = 2000 pieces

## DESIGN-IN SUPPORT

- Other resistance curves and tolerances are available on request
- Consult Vishay for other lead length, other connector crimping or other features
- Other applicable screw size are available, for example stud size metric 3 mm/American 3 to 4
- 3D Solid models: [www.vishay.com/doc?29106](http://www.vishay.com/doc?29106)
- NTC curve computation: [www.vishay.com/thermistors/curve-computation-list/](http://www.vishay.com/thermistors/curve-computation-list/)



# NTC A LUG....103 Series

NTC Thermistors, Mini Lug Sensors Vishay BCcomponents

For complete curve computation, visit: [www.vishay.com/thermistors/curve-computation-list/](http://www.vishay.com/thermistors/curve-computation-list/)

TABLE 1

|                   |               |
|-------------------|---------------|
| NTCALUGE4103H103  | 10K 3 % 3984K |
| NTCALUGE3103H103C | 10K 3 % 3984K |

| RESISTANCE TEMPERATURE CHARACTERISTICS |                  |                   |                     |                   |                   |                   |                   |
|----------------------------------------|------------------|-------------------|---------------------|-------------------|-------------------|-------------------|-------------------|
| TEMP.<br>[°C]                          | $R_{(T)}/R_{25}$ | RESISTANCE<br>[Ω] | $\Delta R/R$<br>[%] | $\alpha$<br>[%/K] | $\Delta T$<br>[K] | $R_{min.}$<br>[Ω] | $R_{max.}$<br>[Ω] |
| - 40                                   | 33.427           | 334 274           | 4.92                | - 6.63            | 0.74              | 317 833           | 350 716           |
| - 35                                   | 24.132           | 241 323           | 4.73                | - 6.41            | 0.74              | 229 899           | 252 747           |
| - 30                                   | 17.613           | 176 133           | 4.56                | - 6.19            | 0.74              | 168 107           | 184 158           |
| - 25                                   | 12.990           | 129 900           | 4.39                | - 5.99            | 0.73              | 124 202           | 135 598           |
| - 20                                   | 9.676            | 96 761            | 4.22                | - 5.79            | 0.73              | 92 675            | 100 848           |
| - 15                                   | 7.276            | 72 765            | 4.07                | - 5.61            | 0.73              | 69 806            | 75 723            |
| - 10                                   | 5.522            | 55 218            | 3.92                | - 5.43            | 0.72              | 53 056            | 57 380            |
| - 5                                    | 4.227            | 42 268            | 3.77                | - 5.26            | 0.72              | 40 674            | 43 861            |
| 0                                      | 3.262            | 32 624            | 3.63                | - 5.10            | 0.71              | 31 440            | 33 808            |
| 5                                      | 2.538            | 25 381            | 3.49                | - 4.94            | 0.71              | 24 494            | 26 268            |
| 10                                     | 1.990            | 19 897            | 3.36                | - 4.80            | 0.70              | 19 227            | 20 566            |
| 15                                     | 1.571            | 15 711            | 3.24                | - 4.65            | 0.70              | 15 202            | 16 220            |
| 20                                     | 1.249            | 12 493            | 3.12                | - 4.52            | 0.69              | 12 103            | 12 882            |
| 25                                     | 1.000            | 10 000            | 3.00                | - 4.39            | 0.68              | 9700.0            | 10 300            |
| 30                                     | 0.806            | 8056.0            | 3.11                | - 4.26            | 0.73              | 7805.1            | 8306.8            |
| 35                                     | 0.653            | 6529.7            | 3.22                | - 4.14            | 0.78              | 6319.3            | 6740.2            |
| 40                                     | 0.532            | 5323.9            | 3.33                | - 4.03            | 0.83              | 5146.6            | 5501.1            |
| 45                                     | 0.437            | 4365.3            | 3.43                | - 3.92            | 0.88              | 4215.4            | 4515.1            |
| 50                                     | 0.360            | 3598.7            | 3.53                | - 3.81            | 0.93              | 3471.6            | 3725.8            |
| 55                                     | 0.298            | 2982.3            | 3.63                | - 3.71            | 0.98              | 2874.0            | 3090.5            |
| 60                                     | 0.248            | 2483.8            | 3.72                | - 3.61            | 1.03              | 2391.3            | 2576.3            |
| 65                                     | 0.208            | 2078.7            | 3.81                | - 3.51            | 1.09              | 1999.4            | 2157.9            |
| 70                                     | 0.175            | 1747.7            | 3.90                | - 3.42            | 1.14              | 1679.5            | 1815.9            |
| 75                                     | 0.148            | 1475.9            | 3.99                | - 3.34            | 1.20              | 1417.1            | 1534.8            |
| 80                                     | 0.125            | 1251.8            | 4.07                | - 3.25            | 1.25              | 1200.8            | 1302.8            |
| 85                                     | 0.107            | 1066.1            | 4.15                | - 3.17            | 1.31              | 1021.8            | 1110.4            |
| 90                                     | 0.091            | 911.59            | 4.23                | - 3.09            | 1.37              | 873.01            | 950.16            |
| 95                                     | 0.078            | 782.46            | 4.31                | - 3.02            | 1.43              | 748.75            | 816.17            |
| 100                                    | 0.067            | 674.11            | 4.38                | - 2.94            | 1.49              | 644.56            | 703.66            |
| 105                                    | 0.058            | 582.84            | 4.46                | - 2.87            | 1.55              | 556.87            | 608.82            |
| 110                                    | 0.051            | 505.68            | 4.53                | - 2.81            | 1.61              | 482.79            | 528.57            |
| 115                                    | 0.044            | 440.19            | 4.60                | - 2.74            | 1.68              | 419.96            | 460.42            |
| 120                                    | 0.038            | 384.41            | 4.66                | - 2.68            | 1.74              | 366.49            | 402.34            |
| 125                                    | 0.034            | 336.75            | 4.73                | - 2.62            | 1.81              | 320.83            | 352.67            |



For complete curve computation, visit: [www.vishay.com/thermistors/curve-computation-list/](http://www.vishay.com/thermistors/curve-computation-list/)

TABLE 2

|                   |               |
|-------------------|---------------|
| NTCALUGE4103G103  | 10K 2 % 3984K |
| NTCALUGE3103G103C | 10K 2 % 3984K |

| RESISTANCE TEMPERATURE CHARACTERISTICS |                  |                   |                     |                   |                   |                   |                   |
|----------------------------------------|------------------|-------------------|---------------------|-------------------|-------------------|-------------------|-------------------|
| TEMP.<br>[°C]                          | $R_{(T)/R_{25}}$ | RESISTANCE<br>[Ω] | $\Delta R/R$<br>[%] | $\alpha$<br>[%/K] | $\Delta T$<br>[K] | $R_{min.}$<br>[Ω] | $R_{max.}$<br>[Ω] |
| - 40                                   | 33.427           | 334 274           | 3.90                | - 6.63            | 0.59              | 321 238           | 347 311           |
| - 35                                   | 24.132           | 241 323           | 3.72                | - 6.41            | 0.58              | 232 353           | 250 293           |
| - 30                                   | 17.613           | 176 133           | 3.54                | - 6.19            | 0.57              | 169 895           | 182 370           |
| - 25                                   | 12.990           | 129 900           | 3.37                | - 5.99            | 0.56              | 125 518           | 134 282           |
| - 20                                   | 9.676            | 96 761            | 3.21                | - 5.79            | 0.55              | 93 654            | 99 869            |
| - 15                                   | 7.276            | 72 765            | 3.06                | - 5.61            | 0.54              | 70 541            | 74 988            |
| - 10                                   | 5.522            | 55 218            | 2.91                | - 5.43            | 0.54              | 53 613            | 56 823            |
| - 5                                    | 4.227            | 42 268            | 2.76                | - 5.26            | 0.53              | 41 100            | 43 435            |
| 0                                      | 3.262            | 32 624            | 2.62                | - 5.10            | 0.51              | 31 768            | 33 480            |
| 5                                      | 2.538            | 25 381            | 2.49                | - 4.94            | 0.50              | 24 749            | 26 013            |
| 10                                     | 1.990            | 19 897            | 2.36                | - 4.80            | 0.49              | 19 427            | 20 367            |
| 15                                     | 1.571            | 15 711            | 2.24                | - 4.65            | 0.48              | 15 360            | 16 063            |
| 20                                     | 1.249            | 12 493            | 2.12                | - 4.52            | 0.47              | 12 228            | 12 757            |
| 25                                     | 1.000            | 10 000            | 2.00                | - 4.39            | 0.46              | 9800.0            | 10 200            |
| 30                                     | 0.806            | 8056.0            | 2.11                | - 4.26            | 0.50              | 7885.8            | 8226.1            |
| 35                                     | 0.653            | 6529.7            | 2.22                | - 4.14            | 0.54              | 6384.7            | 6674.8            |
| 40                                     | 0.532            | 5323.9            | 2.33                | - 4.03            | 0.58              | 5200.0            | 5447.7            |
| 45                                     | 0.437            | 4365.3            | 2.43                | - 3.92            | 0.62              | 4259.3            | 4471.3            |
| 50                                     | 0.360            | 3598.7            | 2.53                | - 3.81            | 0.66              | 3507.8            | 3689.7            |
| 55                                     | 0.298            | 2982.3            | 2.62                | - 3.71            | 0.71              | 2904.0            | 3060.5            |
| 60                                     | 0.248            | 2483.8            | 2.72                | - 3.61            | 0.75              | 2416.4            | 2551.3            |
| 65                                     | 0.208            | 2078.7            | 2.81                | - 3.51            | 0.80              | 2020.3            | 2137.0            |
| 70                                     | 0.175            | 1747.7            | 2.89                | - 3.42            | 0.85              | 1697.1            | 1798.2            |
| 75                                     | 0.148            | 1475.9            | 2.98                | - 3.34            | 0.89              | 1432.0            | 1519.9            |
| 80                                     | 0.125            | 1251.8            | 3.06                | - 3.25            | 0.94              | 1213.5            | 1290.1            |
| 85                                     | 0.107            | 1066.1            | 3.14                | - 3.17            | 0.99              | 1032.6            | 1099.6            |
| 90                                     | 0.091            | 911.59            | 3.22                | - 3.09            | 1.04              | 882.23            | 940.94            |
| 95                                     | 0.078            | 782.46            | 3.30                | - 3.02            | 1.09              | 756.67            | 808.25            |
| 100                                    | 0.067            | 674.11            | 3.37                | - 2.94            | 1.14              | 651.40            | 696.83            |
| 105                                    | 0.058            | 582.84            | 3.44                | - 2.87            | 1.20              | 562.79            | 602.90            |
| 110                                    | 0.051            | 505.68            | 3.51                | - 2.81            | 1.25              | 487.92            | 523.43            |
| 115                                    | 0.044            | 440.19            | 3.58                | - 2.74            | 1.31              | 424.43            | 455.95            |
| 120                                    | 0.038            | 384.41            | 3.65                | - 2.68            | 1.36              | 370.39            | 398.43            |
| 125                                    | 0.034            | 336.75            | 3.71                | - 2.62            | 1.42              | 324.25            | 349.25            |



# NTC A LUG....103 Series

NTC Thermistors, Mini Lug Sensors Vishay BCcomponents

For complete curve computation, visit: [www.vishay.com/thermistors/curve-computation-list/](http://www.vishay.com/thermistors/curve-computation-list/)

TABLE 3

|                   |               |
|-------------------|---------------|
| NTCALUGE4123H103  | 12K 3 % 3740K |
| NTCALUGE3123H103C | 12K 3 % 3740K |

| RESISTANCE TEMPERATURE CHARACTERISTICS |                  |                   |                     |                   |                   |                   |                   |
|----------------------------------------|------------------|-------------------|---------------------|-------------------|-------------------|-------------------|-------------------|
| TEMP.<br>[°C]                          | $R_{(T)}/R_{25}$ | RESISTANCE<br>[Ω] | $\Delta R/R$<br>[%] | $\alpha$<br>[%/K] | $\Delta T$<br>[K] | $R_{min.}$<br>[Ω] | $R_{max.}$<br>[Ω] |
| - 40                                   | 25.783           | 309 396           | 8.40                | - 6.07            | 1.38              | 283 397           | 335 395           |
| - 35                                   | 19.125           | 229 504           | 7.88                | - 5.88            | 1.34              | 211 413           | 247 595           |
| - 30                                   | 14.320           | 171 840           | 7.38                | - 5.70            | 1.30              | 159 152           | 184 528           |
| - 25                                   | 10.819           | 129 825           | 6.90                | - 5.52            | 1.25              | 120 861           | 138 789           |
| - 20                                   | 8.244            | 98 933            | 6.45                | - 5.35            | 1.20              | 92 556            | 105 309           |
| - 15                                   | 6.335            | 76 019            | 6.00                | - 5.19            | 1.16              | 71 455            | 80 582            |
| - 10                                   | 4.907            | 58 879            | 5.58                | - 5.03            | 1.11              | 55 595            | 62 163            |
| - 5                                    | 3.829            | 45 953            | 5.17                | - 4.88            | 1.06              | 43 578            | 48 328            |
| 0                                      | 3.011            | 36 129            | 4.77                | - 4.74            | 1.01              | 34 405            | 37 854            |
| 5                                      | 2.384            | 28 607            | 4.39                | - 4.60            | 0.95              | 27 350            | 29 864            |
| 10                                     | 1.900            | 22 804            | 4.03                | - 4.47            | 0.90              | 21 886            | 23 723            |
| 15                                     | 1.525            | 18 298            | 3.67                | - 4.34            | 0.85              | 17 626            | 18 970            |
| 20                                     | 1.231            | 14 773            | 3.33                | - 4.22            | 0.79              | 14 281            | 15 265            |
| 25                                     | 1.000            | 12 000            | 3.00                | - 4.10            | 0.73              | 11 640            | 12 360            |
| 30                                     | 0.817            | 9803.7            | 3.32                | - 3.99            | 0.83              | 9478.2            | 10 129            |
| 35                                     | 0.671            | 8053.9            | 3.63                | - 3.88            | 0.94              | 7761.7            | 8346.2            |
| 40                                     | 0.554            | 6651.9            | 3.93                | - 3.77            | 1.04              | 6390.6            | 6913.2            |
| 45                                     | 0.460            | 5522.3            | 4.22                | - 3.67            | 1.15              | 5289.3            | 5755.2            |
| 50                                     | 0.384            | 4607.2            | 4.50                | - 3.58            | 1.26              | 4399.9            | 4814.5            |
| 55                                     | 0.322            | 3862.1            | 4.77                | - 3.48            | 1.37              | 3677.8            | 4046.4            |
| 60                                     | 0.271            | 3252.4            | 5.04                | - 3.39            | 1.48              | 3088.6            | 3416.2            |
| 65                                     | 0.229            | 2751.1            | 5.29                | - 3.30            | 1.60              | 2605.5            | 2896.7            |
| 70                                     | 0.195            | 2336.9            | 5.54                | - 3.22            | 1.72              | 2207.4            | 2466.4            |
| 75                                     | 0.166            | 1993.3            | 5.78                | - 3.14            | 1.84              | 1878.0            | 2108.6            |
| 80                                     | 0.142            | 1707.0            | 6.02                | - 3.06            | 1.96              | 1604.2            | 1809.7            |
| 85                                     | 0.122            | 1467.3            | 6.25                | - 2.99            | 2.09              | 1375.7            | 1559.0            |
| 90                                     | 0.105            | 1266.0            | 6.47                | - 2.92            | 2.22              | 1184.1            | 1347.9            |
| 95                                     | 0.091            | 1096.2            | 6.69                | - 2.85            | 2.35              | 1022.9            | 1169.4            |
| 100                                    | 0.079            | 952.38            | 6.90                | - 2.78            | 2.48              | 886.71            | 1018.0            |
| 105                                    | 0.069            | 830.20            | 7.10                | - 2.71            | 2.62              | 771.26            | 889.15            |
| 110                                    | 0.061            | 726.02            | 7.30                | - 2.65            | 2.75              | 673.03            | 779.02            |
| 115                                    | 0.053            | 636.88            | 7.49                | - 2.59            | 2.89              | 589.16            | 684.61            |
| 120                                    | 0.047            | 560.36            | 7.68                | - 2.53            | 3.04              | 517.31            | 603.41            |
| 125                                    | 0.041            | 494.46            | 7.87                | - 2.47            | 3.18              | 455.56            | 533.37            |



For complete curve computation, visit: [www.vishay.com/thermistors/curve-computation-list/](http://www.vishay.com/thermistors/curve-computation-list/)

TABLE 4

|                   |               |
|-------------------|---------------|
| NTCALUGE4473H103  | 47K 3 % 3740K |
| NTCALUGE3473H103C | 47K 3 % 3740K |

| RESISTANCE TEMPERATURE CHARACTERISTICS |                  |                   |                     |                   |                   |                   |                   |
|----------------------------------------|------------------|-------------------|---------------------|-------------------|-------------------|-------------------|-------------------|
| TEMP.<br>[°C]                          | $R_{(T)/R_{25}}$ | RESISTANCE<br>[Ω] | $\Delta R/R$<br>[%] | $\alpha$<br>[%/K] | $\Delta T$<br>[K] | $R_{min.}$<br>[Ω] | $R_{max.}$<br>[Ω] |
| - 40                                   | 25.783           | 1 211 802         | 8.40                | - 6.07            | 1.38              | 1 109 973         | 1 313 631         |
| - 35                                   | 19.125           | 898 891           | 7.88                | - 5.88            | 1.34              | 828 034           | 969 749           |
| - 30                                   | 14.320           | 673 040           | 7.38                | - 5.70            | 1.30              | 623 344           | 722 736           |
| - 25                                   | 10.819           | 508 481           | 6.90                | - 5.52            | 1.25              | 473 370           | 543 592           |
| - 20                                   | 8.244            | 387 486           | 6.45                | - 5.35            | 1.20              | 362 512           | 412 460           |
| - 15                                   | 6.335            | 297 740           | 6.00                | - 5.19            | 1.16              | 279 866           | 315 613           |
| - 10                                   | 4.907            | 230 608           | 5.58                | - 5.03            | 1.11              | 217 745           | 243 471           |
| - 5                                    | 3.829            | 179 983           | 5.17                | - 4.88            | 1.06              | 170 681           | 189 285           |
| 0                                      | 3.011            | 141 507           | 4.77                | - 4.74            | 1.01              | 134 752           | 148 262           |
| 5                                      | 2.384            | 112 043           | 4.39                | - 4.60            | 0.95              | 107 121           | 116 966           |
| 10                                     | 1.900            | 89 317            | 4.03                | - 4.47            | 0.90              | 85 721            | 92 914            |
| 15                                     | 1.525            | 71 665            | 3.67                | - 4.34            | 0.85              | 69 033            | 74 297            |
| 20                                     | 1.231            | 57 863            | 3.33                | - 4.22            | 0.79              | 55 936            | 59 790            |
| 25                                     | 1.000            | 47 000            | 3.00                | - 4.10            | 0.73              | 45 590            | 48 410            |
| 30                                     | 0.817            | 38 398            | 3.32                | - 3.99            | 0.83              | 37 123            | 39 672            |
| 35                                     | 0.671            | 31 545            | 3.63                | - 3.88            | 0.94              | 30 400            | 32 689            |
| 40                                     | 0.554            | 26 053            | 3.93                | - 3.77            | 1.04              | 25 030            | 27 077            |
| 45                                     | 0.460            | 21 629            | 4.22                | - 3.67            | 1.15              | 20 717            | 22 541            |
| 50                                     | 0.384            | 18 045            | 4.50                | - 3.58            | 1.26              | 17 233            | 18 857            |
| 55                                     | 0.322            | 15 127            | 4.77                | - 3.48            | 1.37              | 14 405            | 15 848            |
| 60                                     | 0.271            | 12 739            | 5.04                | - 3.39            | 1.48              | 12 097            | 13 380            |
| 65                                     | 0.229            | 10 775            | 5.29                | - 3.30            | 1.60              | 10 205            | 11 345            |
| 70                                     | 0.195            | 9153.0            | 5.54                | - 3.22            | 1.72              | 8645.8            | 9660.2            |
| 75                                     | 0.166            | 7807.1            | 5.78                | - 3.14            | 1.84              | 7355.6            | 8258.7            |
| 80                                     | 0.142            | 6685.6            | 6.02                | - 3.06            | 1.96              | 6283.2            | 7087.9            |
| 85                                     | 0.122            | 5747.0            | 6.25                | - 2.99            | 2.09              | 5388.0            | 6106.0            |
| 90                                     | 0.105            | 4958.4            | 6.47                | - 2.92            | 2.22              | 4637.7            | 5279.2            |
| 95                                     | 0.091            | 4293.3            | 6.69                | - 2.85            | 2.35              | 4006.3            | 4580.3            |
| 100                                    | 0.079            | 3730.1            | 6.90                | - 2.78            | 2.48              | 3472.9            | 3987.3            |
| 105                                    | 0.069            | 3251.6            | 7.10                | - 2.71            | 2.62              | 3020.8            | 3482.5            |
| 110                                    | 0.061            | 2843.6            | 7.30                | - 2.65            | 2.75              | 2636.0            | 3051.2            |
| 115                                    | 0.053            | 2494.5            | 7.49                | - 2.59            | 2.89              | 2307.5            | 2681.4            |
| 120                                    | 0.047            | 2194.7            | 7.68                | - 2.53            | 3.04              | 2026.1            | 2363.4            |
| 125                                    | 0.041            | 1936.6            | 7.87                | - 2.47            | 3.18              | 1784.3            | 2089.0            |



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.