




Ambient Light Sensor



18527-1

DESCRIPTION

TEMD6010FX01 ambient light sensor is a PIN photodiode with high speed and high photo sensitivity in a clear, surface mount plastic package. The detector chip has 0.27 mm² sensitive area. It is sensitive to visible light much like the human eye and has peak sensitivity at 540 nm.

FEATURES

- Package type: surface mount
- Package form: 1206
- Dimensions (L x W x H in mm): 4 x 2 x 1.05
- Radiant sensitive area (in mm²): 0.27
- AEC-Q101 qualified
- High photo sensitivity
- Adapted to human eye responsivity
- Supression filter for near infrared radiation
- Angle of half sensitivity: $\phi = \pm 60^\circ$
- Floor life: 168 h, MSL 3, acc. J-STD-020
- Lead (Pb)-free reflow soldering
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE
GRADERoHS
COMPLIANT
GREEN
(5-2008)

APPLICATIONS

- Automotive sensors
- Ambient light sensors
- Backlight dimming
- Mobil phones
- Notebooks
- Computers

PRODUCT SUMMARY

| COMPONENT | I_{ra} (μA) | ϕ (deg) | $\lambda_{0.5}$ (nm) |
|--------------|---------------|--------------|----------------------|
| TEMD6010FX01 | 0.04 | ± 60 | 430 to 610 |

Note

- Test conditions see table “Basic Characteristics”

ORDERING INFORMATION

| ORDERING CODE | PACKAGING | REMARKS | PACKAGE FORM |
|---------------|---------------|------------------------------|--------------|
| TEMD6010FX01 | Tape and reel | MOQ: 3000 pcs, 3000 pcs/reel | 1206 |

Note

- MOQ: minimum order quantity

ABSOLUTE MAXIMUM RATINGS ($T_{amb} = 25^\circ\text{C}$, unless otherwise specified)

| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
|-------------------------------------|--|------------|---------------|------------------|
| Reverse voltage | | V_R | 16 | V |
| Power dissipation | | P_V | 100 | mW |
| Junction temperature | | T_j | 100 | $^\circ\text{C}$ |
| Operating temperature range | | T_{amb} | - 40 to + 100 | $^\circ\text{C}$ |
| Storage temperature range | | T_{stg} | - 40 to + 100 | $^\circ\text{C}$ |
| Soldering temperature | Acc. reflow solder profile fig. 7 | T_{sd} | 260 | $^\circ\text{C}$ |
| Thermal resistance junction/ambient | Soldered on PCB with pad dimensions: 4 mm x 4 mm | R_{thJA} | 450 | K/W |

**BASIC CHARACTERISTICS** ($T_{\text{amb}} = 25^\circ\text{C}$, unless otherwise specified)

| PARAMETER | TEST CONDITION | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|--|--|-----------------------------|------|------------|------|---------------|
| Breakdown voltage | $I_R = 100\ \mu\text{A}$, $E = 0\ \text{lx}$ | V_{BR} | 16 | | | V |
| Reverse dark current | $V_{\text{CE}} = 10\ \text{V}$, $E = 0\ \text{lx}$ | I_{ro} | | 0.1 | 5 | nA |
| Diode capacitance | $V_R = 0\ \text{V}$, $f = 1\ \text{MHz}$, $E = 0\ \text{lx}$ | C_D | | 60 | | pF |
| | $V_R = 5\ \text{V}$, $f = 1\ \text{MHz}$, $E = 0\ \text{lx}$ | C_D | | 24 | | pF |
| Reverse light current | $E_e = 1\ \text{mW/cm}^2$, $\lambda = 550\ \text{nm}$, $V_R = 5\ \text{V}$ | I_{ra} | | 1 | | μA |
| | $E_v = 100\ \text{lx}$, CIE illuminant A, $V_R = 5\ \text{V}$ | I_{ra} | 0.03 | 0.04 | 0.09 | μA |
| Temperature coefficient of I_{ra} | $E_v = 100\ \text{lx}$, CIE illuminant A, $V_R = 5\ \text{V}$ | $\text{TK}_{I_{\text{ra}}}$ | | 0.2 | | %/K |
| Angle of half sensitivity | | φ | | ± 60 | | deg |
| Wavelength of peak sensitivity | | λ_p | | 540 | | nm |
| Range of spectral bandwidth | | $\lambda_{0.5}$ | | 430 to 610 | | nm |


BASIC CHARACTERISTICS ($T_{\text{amb}} = 25^\circ\text{C}$, unless otherwise specified)

Fig. 1 - Reverse Dark Current vs. Ambient Temperature




Fig. 3 - Diode Capacitance vs. Reverse Voltage




Fig. 2 - Reverse Light Current vs. Illuminance




Fig. 4 - Relative Spectral Sensitivity vs. Wavelength




Fig. 1 - Relative Radiant Sensitivity vs. Angular Displacement



REFLOW SOLDER PROFILE

Fig. 5 - Lead (Pb)-free Reflow Solder Profile acc. J-STD-020D

PACKAGE DIMENSIONS in millimeters

Drawing-No.: 6.541-5080.01-4
Issue: 1; 31.08.09
21884

DRYPACK

Devices are packed in moisture barrier bags (MBB) to prevent the products from moisture absorption during transportation and storage. Each bag contains a desiccant.

FLOOR LIFE

Time between soldering and removing from MBB must not exceed the time indicated in J-STD-020:

Moisture sensitivity: level 3

Floor life: 168 h

Conditions: $T_{amb} < 30\text{ }^{\circ}\text{C}$, $RH < 60\%$



DRYING

In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or label. Devices taped on reel dry using recommended conditions:

192 h at $40\text{ }^{\circ}\text{C}$ (+ 5 $^{\circ}\text{C}$), $RH < 5\%$


or

96 h at $60\text{ }^{\circ}\text{C}$ (+ 5 $^{\circ}\text{C}$), $RH < 5\%$.



Not indicated tolerances ± 0.1

Recommended solder pad
Footprint





Technical drawing of a battery pack showing a cross-section and a top view.


Cross-section (Left):

- Top flange thickness: 0.3 ± 0.05
- Bottom flange thickness: 1.35
- Internal height: 4.26
- Angle: 3°


Top View (Right):

- Overall width: 12 ± 0.3
- Overall height: 5.5
- Distance between top horizontal lines: 4
- Distance between bottom horizontal lines: 4
- Distance between vertical center lines: 2.26
- Radius of semi-circular ends: 1.75
- Cell width: 2
- Cell height: 1.5
- Minimum hole diameter: $\varnothing 1.5 \text{ min.}$
- Labels: Anode, Cathode
- Reel off direction: Indicated by an arrow pointing right.

Not indicated tolerances ± 0.1



Volume: 3000 pcs/reel



Form of the leave open
of the wheel is supplier specific.



Rev. 1.8, 20-Aug-12



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.