


## Ambient Light Sensor in 0805 Package



### DESCRIPTION

TEMT6200FX01 ambient light sensor is a silicon NPN epitaxial planar phototransistor in a miniature transparent 0805 package for surface mounting. It is sensitive to visible light much like the human eye and has peak sensitivity at 550 nm.

### FEATURES

- Package type: surface mount
- Package form: 0805
- Dimensions (L x W x H in mm): 2 x 1.25 x 0.85
- AEC-Q101 qualified
- High photo sensitivity
- Adapted to human eye responsivity
- Supression filter for near infrared radiation
- Angle of half sensitivity:  $\phi = \pm 60^\circ$
- Floor life: 168 h, MSL 3, acc. J-STD-020
- Lead (Pb)-free reflow soldering
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

AUTOMOTIVE  
GRADE

**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### APPLICATIONS

- Automotive sensors
- Ambient light sensor for display backlight dimming in:
  - Mobile phones
  - Notebook computers
  - PDAs
  - Cameras
  - Dashboards

### PRODUCT SUMMARY

| COMPONENT    | $I_{PCE}$ ( $\mu A$ ) | $\phi$ (deg) | $\lambda_{0.5}$ (nm) |
|--------------|-----------------------|--------------|----------------------|
| TEMT6200FX01 | 23                    | $\pm 60$     | 450 to 610           |

#### Note

- Test condition see table "Basic Characteristics"

### ORDERING INFORMATION

| ORDERING CODE | PACKAGING     | REMARKS                                                                                                                                         | PACKAGE FORM |
|---------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| TEMT6200FX01  | Tape and reel | MOQ: 3000 pcs, 3000 pcs/reel. Label with $I_{PCE}$ group on each reel. Specifications of group A/B/C see table "Type Dedicated Characteristics" | 0805         |

#### Note

- MOQ: minimum order quantity

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25^\circ C$ , unless otherwise specified)

| PARAMETER                           | TEST CONDITION                                   | SYMBOL     | VALUE       | UNIT       |
|-------------------------------------|--------------------------------------------------|------------|-------------|------------|
| Collector emitter voltage           |                                                  | $V_{CEO}$  | 6           | V          |
| Emitter collector voltage           |                                                  | $V_{ECO}$  | 1.5         | V          |
| Collector current                   |                                                  | $I_C$      | 20          | mA         |
| Power dissipation                   |                                                  | $P_V$      | 100         | mW         |
| Junction temperature                |                                                  | $T_j$      | 100         | $^\circ C$ |
| Operating temperature range         |                                                  | $T_{amb}$  | -40 to +100 | $^\circ C$ |
| Storage temperature range           |                                                  | $T_{stg}$  | -40 to +100 | $^\circ C$ |
| Soldering temperature               | Acc. reflow profile fig. 9                       | $T_{sd}$   | 260         | $^\circ C$ |
| Thermal resistance junction/ambient | Soldered on PCB with pad dimensions: 4 mm x 4 mm | $R_{thJA}$ | 450         | K/W        |




Fig. 1 - Power Dissipation Limit vs. Ambient Temperature

| <b>BASIC CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                 |                 |      |            |      |               |
|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|-----------------|------|------------|------|---------------|
| PARAMETER                                                                                           | TEST CONDITION                                                  | SYMBOL          | MIN. | TYP.       | MAX. | UNIT          |
| Collector emitter breakdown voltage                                                                 | $I_C = 0.1\text{ mA}$                                           | $V_{CEO}$       | 6    |            |      | V             |
| Collector dark current                                                                              | $V_{CE} = 5\text{ V}$ , $E = 0\text{ lx}$                       | $I_{CEO}$       |      | 3          | 50   | nA            |
| Collector emitter capacitance                                                                       | $V_{CE} = 0\text{ V}$ , $f = 1\text{ MHz}$ , $E = 0\text{ lx}$  | $C_{CEO}$       |      | 16         |      | pF            |
| Photo current                                                                                       | $E_V = 20\text{ lx}$ , CIE illuminant A, $V_{CE} = 5\text{ V}$  | $I_{PCE}$       |      | 4.6        |      | $\mu\text{A}$ |
|                                                                                                     | $E_V = 100\text{ lx}$ , CIE illuminant A, $V_{CE} = 5\text{ V}$ | $I_{PCE}$       | 7.5  | 23         | 39   | $\mu\text{A}$ |
| Temperature coefficient of $I_{PCE}$                                                                | CIE illuminant A                                                | $TK_{IPCE}$     |      | 1.18       |      | %/K           |
|                                                                                                     | LED, white                                                      | $TK_{IPCE}$     |      | 0.9        |      | %/K           |
| Angle of half sensitivity                                                                           |                                                                 | $\phi$          |      | $\pm 60$   |      | deg           |
| Wavelength of peak sensitivity                                                                      |                                                                 | $\lambda_p$     |      | 550        |      | nm            |
| Range of spectral bandwidth                                                                         |                                                                 | $\lambda_{0.5}$ |      | 450 to 610 |      | nm            |
| Collector emitter saturation voltage                                                                | $E_V = 20\text{ lx}$ , $0.45\text{ }\mu\text{A}$                | $V_{CEsat}$     |      | 0.1        |      | V             |

| <b>TYPE DEDICATED CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                       |              |           |      |      |               |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|--------------|-----------|------|------|---------------|
| PARAMETER                                                                                                    | TEST CONDITION                                                        | BINNED GROUP | SYMBOL    | MIN. | MAX. | UNIT          |
| Photo current                                                                                                | $E_V = 100\text{ lx}$ ,<br>CIE illuminant A,<br>$V_{CE} = 5\text{ V}$ | A            | $I_{PCE}$ | 7.5  | 15   | $\mu\text{A}$ |
|                                                                                                              |                                                                       | B            | $I_{PCE}$ | 12   | 24   | $\mu\text{A}$ |
|                                                                                                              |                                                                       | C            | $I_{PCE}$ | 19.5 | 39   | $\mu\text{A}$ |

**Note**

- Each 3000 piece packing unit will contain a single group. The label on the bag will indicate which binned group is in the bag. A specific group cannot be ordered. Production shipments containing multiple bags will likely include multiple groups. Please design accordingly.


**BASIC CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 2 - Collector Dark Current vs. Ambient Temperature




Fig. 5 - Photo Current vs. Collector Emitter Voltage




Fig. 3 - Relative Photo Current vs. Ambient Temperature




Fig. 6 - Collector Emitter Capacitance vs. Collector Emitter Voltage




Fig. 4 - Photo Current vs. Illuminance




Fig. 7 - Relative Spectral Sensitivity vs. Wavelength




Fig. 8 - Relative Radiant Sensitivity vs. Angular Displacement

## REFLOW SOLDER PROFILE




Fig. 9 - Lead (Pb)-free Reflow Solder Profile acc. J-STD-020

## DRYPACK

Devices are packed in moisture barrier bags (MBB) to prevent the products from moisture absorption during transportation and storage. Each bag contains a desiccant.

## FLOOR LIFE

Time between soldering and removing from MBB must not exceed the time indicated in J-STD-020:




Moisture sensitivity: level 3

Floor life: 168 h


Conditions:  $T_{amb} < 30\text{ }^{\circ}\text{C}$ ,  $RH < 60\%$

## DRYING


In case of moisture absorption devices should be baked before soldering. Conditions see J-STD-020 or label. Devices taped on reel dry using recommended conditions 192 h at  $40\text{ }^{\circ}\text{C}$  (+  $5\text{ }^{\circ}\text{C}$ ),  $RH < 5\%$ .

**PACKAGE DIMENSIONS** in millimeters


Not indicated tolerances  $\pm 0.1$




Recommended solder pad  
Footprint



Drawing-No.: 6.541-5063.01-4

Issue: 3; 23.02.07

19757

**BLISTER TAPE DIMENSIONS** in millimeters


Drawing-No.: 9.700-5310.01-4

Issue: 2; 14.08.07

20690

Not indicated tolerances  $\pm 0.1$



Quantity per reel: 3000 pcs



technical drawings  
according to DIN  
specifications



**REEL DIMENSIONS** in millimeters



Drawing-No.: 9.800-5096.01-4  
Issue: 2; 26.04.10  
20875



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.