



## IR Receiver Modules for Remote Control Systems



### DESCRIPTION

This IR receiver series is optimized for short burst remote control systems in different environments. The customer can choose between different IC settings (AGC variants), to find the optimum solution for his application. The higher the AGC, the better noise is suppressed, but the lower the code compatibility.

The devices contain a PIN diode and a preamplifier assembled on a lead frame. The epoxy package contains an IR filter. The demodulated output signal can be directly connected to a microprocessor for decoding. These components have not been qualified to automotive specifications.

### FEATURES

- Individual IC settings to reach maximum performance
- Immunity against noise (lamps, LCD TV, Wi-Fi)
- Low supply current
- Photo detector and preamplifier in one package
- Supply voltage: 2.0 V to 5.5 V
- Material categorization:  
for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)


### LINKS TO ADDITIONAL RESOURCES



### DESIGN SUPPORT TOOLS

- [3D models](#)
- [Window size calculator](#)

### BLOCK DIAGRAM



20445-1




# TSOP753..W, TSOP755..W

Vishay Semiconductors

## MECHANICAL DATA

### Pinning:

1, 4 = GND, 2 =  $V_S$ , 3 = OUT



## ORDERING CODE


### Taping:

TSOP75...WTT - top view taped, 2200 pcs/reel

TSOP75...WTR - side view taped, 2300 pcs/reel

## APPLICATION CIRCUIT

17170-14



$R_1$  and  $C_1$  recommended in case there are strong ripple or spikes on the supply line.

## PARTS TABLE

| AGC               |        | NOISY ENVIRONMENTS<br>AND SHORT BURSTS (AGC3)                                                                                                                                                                                                                                                                                                                    | VERY NOISY ENVIRONMENTS<br>AND SHORT BURSTS (AGC5) |
|-------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| Carrier frequency | 30 kHz | TSOP75330W                                                                                                                                                                                                                                                                                                                                                       | TSOP75530W                                         |
|                   | 33 kHz | TSOP75333W                                                                                                                                                                                                                                                                                                                                                       | TSOP75533W                                         |
|                   | 36 kHz | TSOP75336W <sup>(1)</sup>                                                                                                                                                                                                                                                                                                                                        | TSOP75536W                                         |
|                   | 38 kHz | TSOP75338W <sup>(2)(3)(4)</sup>                                                                                                                                                                                                                                                                                                                                  | TSOP75538W                                         |
|                   | 40 kHz | TSOP75340W                                                                                                                                                                                                                                                                                                                                                       | TSOP75540W                                         |
|                   | 56 kHz | TSOP75356W                                                                                                                                                                                                                                                                                                                                                       | TSOP75556W                                         |
| Package           |        | Heimdall no lens                                                                                                                                                                                                                                                                                                                                                 |                                                    |
| Pinning           |        | 1, 4 = GND, 2 = $V_S$ , 3 = OUT                                                                                                                                                                                                                                                                                                                                  |                                                    |
| Dimensions (mm)   |        | 6.8 W x 3.0 H x 2.35 D                                                                                                                                                                                                                                                                                                                                           |                                                    |
| Mounting          |        | SMD                                                                                                                                                                                                                                                                                                                                                              |                                                    |
| Application       |        | Remote control                                                                                                                                                                                                                                                                                                                                                   |                                                    |
| Best choice for   |        | <sup>(1)</sup> MCIR <sup>(2)</sup> RECS-80 Code <sup>(3)</sup> r-map <sup>(4)</sup> XMP                                                                                                                                                                                                                                                                          |                                                    |
| Special options   |        | <ul style="list-style-type: none"> <li>Extended temperature range: <a href="http://www.vishay.com/doc?82738">www.vishay.com/doc?82738</a></li> <li>Narrow optical filter: <a href="http://www.vishay.com/doc?81590">www.vishay.com/doc?81590</a></li> <li>Wide optical filter: <a href="http://www.vishay.com/doc?82726">www.vishay.com/doc?82726</a></li> </ul> |                                                    |

## ABSOLUTE MAXIMUM RATINGS

| PARAMETER                   | TEST CONDITION       | SYMBOL    | VALUE                   | UNIT |
|-----------------------------|----------------------|-----------|-------------------------|------|
| Supply voltage              |                      | $V_S$     | -0.3 to +6              | V    |
| Supply current              |                      | $I_S$     | 3                       | mA   |
| Output voltage              |                      | $V_O$     | -0.3 to ( $V_S + 0.3$ ) | V    |
| Output current              |                      | $I_O$     | 5                       | mA   |
| Junction temperature        |                      | $T_j$     | 100                     | °C   |
| Storage temperature range   |                      | $T_{stg}$ | -25 to +85              | °C   |
| Operating temperature range |                      | $T_{amb}$ | -25 to +85              | °C   |
| Power consumption           | $T_{amb} \leq 85$ °C | $P_{tot}$ | 10                      | mW   |

### Note

- Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect the device reliability.



| ELECTRICAL AND OPTICAL CHARACTERISTICS ( $T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified) |                                                                                |                   |      |          |      |                 |
|-------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|-------------------|------|----------|------|-----------------|
| PARAMETER                                                                                             | TEST CONDITION                                                                 | SYMBOL            | MIN. | TYP.     | MAX. | UNIT            |
| Supply voltage                                                                                        |                                                                                | $V_S$             | 2.0  | -        | 5.5  | V               |
| Supply current                                                                                        | $E_v = 0$ , $V_S = 3.3\text{ V}$                                               | $I_{SD}$          | 0.25 | 0.35     | 0.45 | mA              |
|                                                                                                       | $E_v = 40\text{ klx}$ , sunlight                                               | $I_{SH}$          | -    | 0.45     | -    | mA              |
| Transmission distance                                                                                 | $E_v = 0$ , test signal see Fig. 1, IR diode TSAL6200, $I_F = 50\text{ mA}$    | $d$               | -    | 16       | -    | m               |
| Output voltage low                                                                                    | $I_{OSL} = 0.5\text{ mA}$ , $E_e = 0.7\text{ mW/m}^2$ , test signal see Fig. 1 | $V_{OSL}$         | -    | -        | 100  | mV              |
| Minimum irradiance                                                                                    | Test signal: RC5 code                                                          | $E_e\text{ min.}$ | -    | 0.23     | 0.5  | $\text{mW/m}^2$ |
|                                                                                                       | Test signal: XMP code                                                          | $E_e\text{ min.}$ | -    | 0.3      | 0.6  | $\text{mW/m}^2$ |
| Maximum irradiance                                                                                    | $t_{pi} - 3/f_0 < t_{po} < t_{pi} + 3.5/f_0$ , test signal see Fig. 1          | $E_e\text{ max.}$ | 30   | -        | -    | $\text{W/m}^2$  |
| Directivity                                                                                           | Angle of half transmission distance                                            | $\Phi_{1/2}$      | -    | $\pm 75$ | -    | $^{\circ}$      |

### TYPICAL CHARACTERISTICS ( $T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified)




Fig. 1 - Output Active Low




Fig. 3 - Output Function




Fig. 2 - Pulse Length and Sensitivity in Dark Ambient




Fig. 4 - Output Pulse Diagram



Fig. 5 - Frequency Dependence of Responsivity




Fig. 8 - Max. Envelope Duty Cycle vs. Burst Length




Fig. 6 - Sensitivity in Bright Ambient




Fig. 9 - Sensitivity vs. Ambient Temperature




Fig. 7 - Sensitivity vs. Supply Voltage Disturbances




Fig. 10 - Relative Spectral Sensitivity vs. Wavelength




Fig. 11 - Horizontal Directivity




Fig. 12 - Vertical Directivity




Fig. 13 - Sensitivity vs. Supply Voltage

**SUITABLE DATA FORMAT**

The TSOP753..W, TSOP755..W series are designed to suppress spurious output pulses due to noise or disturbance signals. Data and disturbance signals can be distinguished by the devices according to carrier frequency, burst length and envelope duty cycle. The data signal should be close to the band-pass center frequency (e.g. 38 kHz) and fulfill the conditions in the table below.

When a data signal is applied to the TSOP753..W, TSOP755..W in the presence of a disturbance signal, the sensitivity of the receiver is reduced to insure that no spurious pulses are present at the output. Some examples of disturbance signals which are suppressed are:

- DC light (e.g. from tungsten bulb or sunlight)
- Continuous signals at any frequency
- Strongly or weakly modulated pattern from fluorescent lamps with electronic ballasts (see Fig. 14 or Fig. 15)



Fig. 14 - IR Disturbance from Fluorescent Lamp With Low Modulation



Fig. 15 - IR Disturbance from Fluorescent Lamp With High Modulation


|                                                                                  | <b>TSOP753..W</b>               | <b>TSOP755..W</b>                |
|----------------------------------------------------------------------------------|---------------------------------|----------------------------------|
| Minimum burst length                                                             | 6 cycles/burst                  | 6 cycles/burst                   |
| After each burst of length<br>a minimum gap time is required of                  | 6 to 35 cycles<br>≥ 10 cycles   | 6 to 20 cycles<br>≥ 10 cycles    |
| For bursts greater than<br>a minimum gap time in the data stream is<br>needed of | 35 cycles<br>> 9 x burst length | 20 cycles<br>> 25 x burst length |
| Maximum number of continuous short<br>bursts/second                              | 2000                            | 2000                             |
| MCIR code                                                                        | Preferred                       | No                               |
| XMP code                                                                         | Preferred                       | Yes                              |
| RECS-80 code                                                                     | Preferred                       | Yes                              |
| r-map code                                                                       | Preferred                       | Yes                              |
| Suppression of interference from fluorescent<br>lamps                            | Fig. 14 and Fig. 15             | Fig. 14 and Fig. 15              |

**Note**

- For data formats with long bursts please see the datasheet for TSOP752..W, TSOP754..W



**PACKAGE DIMENSIONS** in millimeters



**ASSEMBLY INSTRUCTIONS**

**Reflow Soldering**



- Reflow soldering must be done within 72 h while stored under a max. temperature of 30 °C, 60 % RH after opening the dry pack envelope
- Set the furnace temperatures for pre-heating and heating in accordance with the reflow temperature profile as shown in the diagram. Exercise extreme care to keep the maximum temperature below 260 °C. The temperature shown in the profile means the temperature at the device surface. Since there is a temperature difference between the component and the circuit board, it should be verified that the temperature of the device is accurately being measured
- Handling after reflow should be done only after the work surface has been cooled off

**Manual Soldering**

- Use a soldering iron of 25 W or less. Adjust the temperature of the soldering iron below 300 °C
- Finish soldering within 3 s
- Handle products only after the temperature has cooled off

Figure 1 is a graph showing the temperature profile of a sample during a DSC measurement. The y-axis represents Temperature (°C) from 0 to 300, and the x-axis represents Time (s) from 0 to 300. The profile shows a ramp up at 3 °C/s to 255 °C at 50 s, a dwell at 255 °C for 120 s, a ramp down at 6 °C/s to 217 °C at 150 s, a dwell at 217 °C for 100 s, a second ramp down at 6 °C/s to 245 °C at 200 s, a dwell at 245 °C for 20 s, and a final ramp down at 6 °C/s to 100 °C at 280 s. The maximum temperature is 260 °C.


A cross-sectional diagram of a composite beam. It shows a top flange and a bottom flange connected by a central web. There is a horizontal gap between the top and bottom flanges on the left side, labeled with a dimension of 0.3. The total vertical height of the beam is labeled with a dimension of 3.6. The beam is shown in a perspective view, with dashed lines indicating the internal structure.




THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT [www.vishay.com/doc?91000](http://www.vishay.com/doc?91000)



**TAPING VERSION TSOP..TT DIMENSIONS** in millimeters




Drawing-No.: 9.700-5341.01-4  
Issue: 3; 06.10.15






**REEL DIMENSIONS** in millimeters



Form of the leave open of the wheel is supplier specific.

Dimension acc. to IEC EN 60 286-3

Tape width 16




Drawing-No.: 9.800-5052.V2-4

Issue: 1; 07.05.02

16734

**LEADER AND TRAILER DIMENSIONS** in millimeters



**COVER TAPE PEEL STRENGTH**

According to DIN EN 60286-3


0.1 N to 1.3 N

300 ± 10 mm/min.

165° to 180° peel angle

**OUTER PACKAGING**

The sealed reel is packed into a pizza box.

**CARTON BOX DIMENSIONS** in millimeters

|                                                   | THICKNESS | WIDTH | LENGTH |
|---------------------------------------------------|-----------|-------|--------|
| Pizza box (SMD and heimdall)<br>(taping in reels) | 50        | 340   | 340    |

**LABEL****Standard bar code labels for finished goods**

The standard bar code labels are product labels and used for identification of goods. The finished goods are packed in final packing area. The standard packing units are labeled with standard bar code labels before transported as finished goods to warehouses. The labels are on each packing unit and contain Vishay Semiconductor GmbH specific data.


**VISHAY SEMICONDUCTOR GmbH STANDARD BAR CODE PRODUCT LABEL** (finished goods)

| PLAIN WRITING         | ABBREVIATION | LENGTH       |
|-----------------------|--------------|--------------|
| Item-description      | -            | 18           |
| Item-number           | INO          | 8            |
| Selection-code        | SEL          | 3            |
| LOT-/serial-number    | BATCH        | 10           |
| Data-code             | COD          | 3 (YWW)      |
| Plant-code            | PTC          | 2            |
| Quantity              | QTY          | 8            |
| Accepted by           | ACC          | -            |
| Packed by             | PCK          | -            |
| Mixed code indicator  | MIXED CODE   | -            |
| Origin                | xxxxxxx+     | Company logo |
| LONG BAR CODE TOP     | TYPE         | LENGTH       |
| Item-number           | N            | 8            |
| Plant-code            | N            | 2            |
| Sequence-number       | X            | 3            |
| Quantity              | N            | 8            |
| Total length          | -            | 21           |
| SHORT BAR CODE BOTTOM | TYPE         | LENGTH       |
| Selection-code        | X            | 3            |
| Data-code             | N            | 3            |
| Batch-number          | X            | 10           |
| Filter                | -            | 1            |
| Total length          | -            | 17           |



## DRY PACKING

The reel is packed in an anti-humidity bag to protect the devices from absorbing moisture during transportation and storage.



## FINAL PACKING

The sealed reel is packed into a cardboard box.

## RECOMMENDED METHOD OF STORAGE

Dry box storage is recommended as soon as the aluminum bag has been opened to prevent moisture absorption. The following conditions should be observed, if dry boxes are not available:

- Storage temperature 10 °C to 30 °C
- Storage humidity ≤ 60 % RH max.

After more than 72 h under these conditions moisture content will be too high for reflow soldering.

In case of moisture absorption, the devices will recover to the former condition by drying under the following condition:

192 h at 40 °C + 5 °C / - 0 °C and < 5 % RH (dry air / nitrogen) or  
 96 h at 60 °C + 5 °C and < 5 % RH for all device containers or  
 24 h at 125 °C + 5 °C not suitable for reel or tubes.

An EIA JEDEC® standard J-STD-020 level 4 label is included on all dry bags.


## ESD PRECAUTION

Proper storage and handling procedures should be followed to prevent ESD damage to the devices especially when they are removed from the antistatic shielding bag. Electrostatic sensitive devices warning labels are on the packaging.


## VISHAY SEMICONDUCTORS STANDARD BAR CODE LABELS

The Vishay Semiconductors standard bar code labels are printed at final packing areas. The labels are on each packing unit and contain Vishay Semiconductors specific data.

## BAR CODE PRODUCT LABEL (example)



22178



22522

EIA JEDEC standard J-STD-020 level 4 is included on all dry bags



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.