



Data

Electrical data

Note on contact resistance

approx. 1m Ω contact resistance approx. 0.25m Ω contact transition
plug/socket

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Ratings per IEC/EN

Legend (ratings)

(III / 3) \triangleq Overvoltage category III / Pollution degree 3

Physical data

Width 190 mm / 7.48 inch

Height 30 mm / 1.181 inch

Mechanical data

Mounting type Wall screw adapter
Secured to mounting plate

Plug-in connection

Mismating protection Yes

Locking of plug-in connection locking lever

Material data

Insulation material Polyamide 66 (PA 66)

Contact material Copper or copper alloy, surface-treated

Environmental requirements

Continuous operating temperature up to 85 °C

Processing temperature -5 ... +40 °C

Continuous operating temperature -35 ... +85 °C

Note on continuous operating temperature Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group 20 (WINSTA)

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.