



Data

Electrical data

Note on contact resistance

approx. 1mΩ contact resistance approx. 0.25mΩ contact transition
plug/socket

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

**Ratings per IEC/EN**

Legend (ratings)

(III / 3) \triangleq Overvoltage category III / Pollution degree 3**Physical data**

Width 190 mm / 7.48 inch

Height 30 mm / 1.181 inch

Mechanical dataMounting type Wall screw adapter
Secured to mounting plate**Plug-in connection**

Mismating protection Yes

Locking of plug-in connection locking lever

Material data

Insulation material Polyamide 66 (PA 66)

Contact material Copper or copper alloy, surface-treated

Environmental requirements

Processing temperature -5 ... +40 °C

Continuous operating temperature -35 ... +85 °C

Note on continuous operating temperature Insulating parts for temperatures ≤ 105 °C**Commercial data**

Product Group 20 (WINSTA)

Installation Notes

Subject to changes. Please also observe the further product documentation!