

Data sheet:

Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug



Article no.: 11026

EUR 38.00

*Net price for commercial users

Versatile plug-in power supply

24V power supply with 85% efficiency and with low standby losses < 0.1W (per DoE Level VI)

Properties

General Data

- 24V AC adapter
- High efficiency: min. 85%
- Low standby losses < 0.1W (per DoE Level VI)
- Limited Power Source (LPS)
- Flexible in application:
 - Primary-side interchangeable adapter system
 - Generous 100...240V input range
 - CE Marking as well as UL / cUL and CCC approval
- Compact form factor: 74 x 43.5 x 34 mm

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - Noise emission and noise immunity for residential and commercial areas
- **5 year guarantee**



Wish for something!

[Your suggestions for improvement and additions](#)

Technical data

Input voltage: 100...240VAC
Frequency: 50...60Hz
Input current: max. 0.6A

Output voltage: 24V DC
Tolerance: $\pm 5\%$
Ripple: max. 150mV
Output power: max. 18W
Rated current: 0.75A, short-circuit protected
Minimum load: none

Efficiency: min. 85%

No-load losses: <0.1W per DoE Level VI
LPS: Yes

Dielectric strength: In-Out: 3KV AC
Leakage current: < 0.25mA

Mains connection: Euro, US and UK adapters
(multi-adapter system)

Secondary connection: 2-pole special connector for screw terminal
Cable type: Twin leads with ferrite core
Cable length: 1.8 meters

Operating temperature: 0..40°C
Storage temperature: -10..70°C
Relative humidity: 20...80% rH (non-condensing)
MTBF: >200,000 hours (per MIL-HDBK-217F at 25° C)

Dimensions: 74 x 43.5 x 34 mm (L x W x H)
Weight: 140 g

Approvals: CE, GS, UL, c-UL, CCC
Safety standard: EN 62368-1
EMC - Emission: EN 55032 B
EN 61000-3-2, EN 61000-3-3
EMV - Noise immunity: EN 55024
EN 61000-4-2, EN 61000-4-3
EN 61000-4-4, EN 61000-4-5
EN 61000-4-6, EN 61000-4-8
EN 61000-4-11

Manufacturer: GlobTec Inc.
GlobTek Deutschland GmbH
Hafenweg 26a
48155 Münster

Power supply type: GT-46180-1824

Article list

		*Net unit price for commercial users	
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00€	
Plug-in Power Supply, 24V / 750mA DC with Euro plug	11025	33.00€	
Plug-in Power Supply, 24V / 750mA DC with US plug	11027	33.00€	

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

Wiesemann & Theis GmbH
Porschestra. 12
42279 Wuppertal
Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)
Fax: +49 202/2680-265
info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.

[Data Privacy](#)

