

Pt Temperature Sensor with Ceramic Housing according to DIN EN 60751

Temperature range -40 °C to +260 °C

- Electrically insulating alumina ceramic housing
- Possible subassembly for stainless steel housing sensor
- Rugged PTFE-insulated connection wires

The electrically insulating housing facilitates quick assembly in a stainless steel sensor probe housing. Possible applications include temperature measurement in commercial cooking equipment, analytical instruments, or any application requiring an electrically isolated sensor body.

Nominal Resistance R_0 [Ω]	Tolerance Class	Order Number
Pt100	F 0.3 (B)	5117588
Pt1000	F 0.3 (B)	5117589

Temperature Range of Tolerance Class

Tolerance Class F 0.3 (B) -40 °C to +260 °C

Temperature Coefficient

TCR = 3850 ppm/K

Connection Wire

PTFE insulated
26 AWG (0.14 mm²), 20in (0.51 m) long, color coded
Pt100: 3 wire connection
Pt1000: 2 wire connection

Internal Conductor Resistance

0.04 Ω /ft (0.134 Ω /m) for each conductor

Housing

Aluminium oxide ceramic

Applications

- Temperature probe assembly
- HVAC
- Laboratory instrumentation
- Laboratory ovens
- Applications requiring an electrically insulating or non-metallic sensor body



Image for illustration purposes only

Pt Temperature Sensor with Ceramic Housing according to DIN EN 60751

Temperature range -40 °C to +260 °C

Features

- Alumina ceramic housing provides excellent electrical isolation
- Small diameter (0.135", 3.43 mm) allows insertion into metal housings with OD of 0.156" (3.96 mm) & larger
- Widely used for a variety of temperature sensing applications
- Available in Pt100 or Pt1000 resistance values
- +260 °C maximum operating temperature

Options

- Wire length
- Resistance Value
- Connectors

Resistance vs Temperature Table

Reference table @ www.herae.us/technical-information




Image for illustration purposes only



The information provided in this data sheet describes certain technical characteristics of the product, but shall not be qualified or construed as quality guarantees whatsoever. Furthermore, the information provided in this data sheet does not constitute a warranty, implied or express, whatsoever, including but not limited to warranties of merchantability, fitness for a particular purpose, or use. The information provided in this data sheet regarding measurement values (including, but not limited to, response time, long-term stability, vibration and shock resistance, insulation resistance and self-heating) are average values that have been obtained under laboratory conditions in tests of large numbers of the product. Product results or measurements achieved by customer or any other person in any production, test, or other environment may vary depending on the specific conditions of use.

The customer is solely responsible to determine whether the product is suited for customer's intended use; in this respect Heraeus cannot assume any liability. The sale of any products of Heraeus is exclusively subject to the Terms and Conditions of Sale of Heraeus in their current version at the time of purchase, which is available under www.heraeus.com/gtc or may be furnished upon request. This data sheet is subject to changes without prior notice.

Heraeus Nexensos USA, a division of Heraeus Epurio LLC, 770 Township Line Road, Suite 300, Yardley, Pennsylvania, USA 19067