

# Products

## 【PS2】HG2-6350P



## DOWNLOAD

- › [DRAWING](#)
- › [CB](#)
- › [FCC](#)
- › [TUV](#)
- › [Manual-English](#)
- › [Manual-Chinese](#)
- › [CCC](#)
- › [BSMI](#)
- › [MTBF\(RoHS\)](#)
- › [MTBF\(ROHS\)\(NO FAN\)](#)
- › [MTBF\(ROHS\)\(50°C\)](#)
- › [MTBF\(ROHS\)\(50°C\)\(NO FAN\)](#)
- › [CE](#)
- › [TUV\(62368-1\)](#)
- › [CB-62368](#)

## OUTPUT WATTAGE

350W

## BEST SOLUTION FOR

Server ,Workstation ,Storage System ,IPC ,PCs

## DIMENSION

140x150x86(mm)

5.51x5.91x3.39(inch)

## INPUT SPEC

VOLTAGE: 90 ~ 264 VAC FULL RANGE

## DC OUTPUT SPEC

120mV

| Output Voltage | Output Current Min. | Output Current Max. | Regulation Load | Regulation Line | Output Ripple & Noise Max.[P-P] |
|----------------|---------------------|---------------------|-----------------|-----------------|---------------------------------|
| 5V             | 3                   | 35                  | ± 5%            | ± 1%            | 50mV                            |
| 12V            | 2                   | 26                  | +7% ~ -5%       | ± 1%            |                                 |
| -5V            | 0                   | 0.5                 | ±5%             | ± 1%            | 150mV                           |
| -12V           | 0                   | 0.8                 | ±5%             | ± 1%            | 150mV                           |
| 3.3V           | 1                   | 28                  | ± 5%            | ± 1%            | 50mV                            |
| +5VSB          | 0.1                 | 2                   | ± 5%            | ± 1%            | 50mV                            |

REMARKS: THE OUTPUT CURRENT OF 5V & 3.3V NOT EXCEED 45A

## FEATURES

\*12V MAX. CURRENT: 26A

\*NOISE & THERMAL CONTROL(SILENCE & RELIABLE)

\*TEMPERATURE RANGE: OPERATING -10°C ~ 50°C

\*EFFICIENCY: 70% AT 115V, FULL LOAD

\* HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%

\* REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS

\*COOLING: ONE 80mm DC FAN

\*ACTIVE POWER FACTOR CORRECTION MEET IEC-1000-3-2 CLASS D

\*EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B

\*SAFETY: UL, CSA 22.2 NO/ 60950, TUV, CCC

\*Serial ATA optional

\*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH

keywords:zippy,1U Redundant,1U Single,2U Redundant,2U Single,3U Single,Cloud Power,Easy Swap,Medical,Micro Redundant,Mini 1U Single,Mini Redundant,N+1 Redundant,Open Frame,PS2,PS2\*2 Redundant,PS2+,Redundant module

About us

Company Overview  
Power Division  
Switch Division  
Leadership  
Corporate Milestones  
Organizational Chart  
Corporate Culture  
Management Philosophy  
ZIPPY Advantages  
Future Prospects  
Zippy Worldwide

Products

Power Products  
Power Online Support  
Switches

News

News  
Events

Investor Relation

Financial  
Annual Reports  
Control  
Shareholder

Human Resource

HR Brief  
Compensation and Welfare  
Training and Development  
How to Apply  
Recruiting Flow  
Where is Zippy

Language

繁體中文  
English