



Products

Search :

【 PS2】HG2-6400P



Output Wattage...

400W

Best Solution for...

Server ,Workstation ,Storage
System ,IPC ,PCs

Dimension...

140x150x86(mm)
5.51x5.91x3.39(inch)

Input Spec...

VOLTAGE: 90 ~ 264 VAC FULL RANGE

DC Output Spec...

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
5V	3	35	± 5%	± 1%	50mV
12V	2	30	+7% ~ -5%	± 1%	120mV
-5V	0	0.5	±5%	± 1%	150mV
-12V	0	0.8	±5%	± 1%	150mV
+3.3V	1	28	± 5%	± 1%	50mV
+5VSB	0.1	2	± 5%	± 1%	50mV

REMARKS: THE OUTPUT CURRENT OF 5V & 3.3V NOT EXCEED 45A

Features...

- *12V MAX. CURRENT: 30A
- *NOISE & THERMAL CONTROL(SILENCE & RELIABLE)
- *TEMPERATURE RANGE: OPERATING -10°C ~ 45°C
- *EFFICIENCY: 70% AT 115V, FULL LOAD
- * HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%
- * REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS
- *COOLING: ONE 80mm DC FAN
- *ACTIVE POWER FACTOR CORRECTION MEET IEC-1000-3-2 CLASS D
- *EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B
- *SAFETY: UL, CSA 22.2 NO/ 60950, TUV, CCC
- *Serial ATA optional

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.

Keywords Search:

[New Product](#)
[1U Redundant](#)
[1U Single](#)
[2U Redundant](#)
[2U Single](#)
[3U Single](#)
[Cloud Power](#)
[Easy Swap](#)
[Medical](#)
[Micro Redundant](#)
[Mini 1U Single](#)
[Mini Redundant](#)
[N+1 Redundant](#)
[Open Frame](#)
[PS2](#)
[PS2*2 Redundant](#)
[PS2+](#)
[Redundant module](#)

[DRAWING](#)
[CB](#)
[TUV](#)
[MTBF](#)
[Manual-English](#)
[Manual-Chinese](#)
[MTBF](#)
[MTBF](#)
[CCC](#)
[FCC](#)
[BSMI](#)
[MTBF\(ROHS\)](#)
[MTBF\(ROHS\)\(50°C\)](#)
[MTBF\(ROHS\)\(50°C\)\(NO](#)
[FAN\)\(ROHS\)\(NO FAN\)](#)
[CE](#)