



Products

Search :

【 PS2】 HP2-6500P



Output Wattage...

500W

Best Solution for...

Server ,Workstation ,Storage
System ,IPC

Inquiry

Dimension...

140x150x86(mm)
5.51x5.91x3.39(inch)

Input Spec...

VOLTAGE: 90 ~ 264 VAC FULL RANGE

DC Output Spec...

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
5V	2.5	40	± 5%	± 1%	60mV
12V	1	32	± 5%	± 1%	100mV
-5V	0	0.8	± 5%	± 1%	100mV
-12V	0	1	± 5%	± 1%	100mV
3.3V	1	30	+5, -5%	± 1%	60mV
+5VSB	0.1	2	± 5%	± 1%	60mV

REMARKS: *TOTAL OUTPUT NOT EXCEED 500W ** WHEN IT PERFORMS CROSS REGULATION TEST, IT IS REQUESTED TO SET THE HIGHER OUTPUT CHANNEL AT 90% MAX. OF ITS SPEC., AND THE LOWER OUTPUT CHANNELS AT 20% MIN. OF THEIRS

Features...

- *ACTIVE PFC (FULL RANGE)
- *12V MAX. CURRENT: 32A
- *TEMPERATURE RANGE : OPERATING 0°C ~ 40°C, STORAGE -20°C ~ 70°C
- * HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%
- * REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS
- *EMI : MEET FCC CLASS B, CISPR22 CLASS B
- *SAFETY: UL, CUL, TUV
- *COOLING: ONE 80 mm DC FAN
- *FAN SPEED CONTROL(OPTIONAL)
- *BUILT-IN ACTIVE POWER FACTOR CORRECTOR
- *SERIAL ATA OPTIONAL

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.

Keywords Search:

GO!

New Product

1U Redundant

1U Single

2U Redundant

2U Single

3U Single

Cloud Power

Easy Swap

Medical

Micro Redundant

Mini 1U Single

Mini Redundant

N+1 Redundant

Open Frame

PS2

PS2*2 Redundant

PS2+

Redundant module

Download

DRAWING

CB

CCC

FCC

TUV

MTBF

Manual-English

Manual-Chinese

MTBF

BSMI

CE

MTBF(RoHS)

FCC

CE(Radiation)

