

Products

【Mini 1U Single】P1S-2507V48

DOWNLOAD

MTBF(RoHS)



OUTPUT WATTAGE

500W

BEST SOLUTION FOR

Server ,Workstation ,Storage System ,IPC ,Blade server

DIMENSION

170x81.5x40.3(mm)

6.69x3.21x1.59(inch)

INPUT SPEC

VOLTAGE : 180~264VAC

FREQUENCY : 47~63HZ

INPUT CURRENT : 6.5A (RMS) FOR 115 VAC / 3.5A (RMS)
FOR 230 VAC

INRUSH CURRENT : 60/80 AMPS @115/230 VAC

(AT 25 DEGREES AMBIENT COLD START FOR EACH POWER UNIT)

DC OUTPUT SPEC

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
+48V	1	10.4	±5%	±1%	480mV
+5VSB	0.1	2.5	±5%	±1%	50mV

* TOTAL OUTPUT MAX: 500W

FEATURES

- * TEMPERATURE RANGE: OPERATING 0°C~40°C, STORAGE -20°C~80°C
- * HOLD UP TIME: WHEN POWER SHUTDOWN DC OUTPUT 5V MUST BE MAINTAIN 16MSEC IN REGULATION LIMIT AT NORMAL INPUT VOLTAGE
- * EFFICIENCY: 87.8% AT 230VAC, FULL LOAD
- * LEAKAGE CURRENT: 3.5MA. MAX. AT NOMINAL VOLTAGE 240VAC
- * POWER GOOD SIGNAL: ON DELAY 100mS TO 500mS, OFF DELAY 1Ms
- * OVER POWER PROTECTION: 110~160% MAX
- * OVER VOLTAGE PROTECTION: +48V→52.8 ~ 62.4V
- * SHORT CIRCUIT PROTECTION: +48V, +5VSB
- * SAFETY: MEET UL, CUL, TUV, CCC
- * REMOTE ON/OFF CONTROL
- * WARNING METHOD: AUDIO ALARM(BUZZER SOUND, RESETABLE), FALUT LED, TTL

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.

keywords:zippy,1U Redundant,1U Single,2U Redundant,2U Single,3U Single,Cloud Power,Easy Swap,Medical,Mini Redundant,Mini 1U Single,Mini Redundant,N+1 Redundant,Open Frame,PS2,PS2*2 Redundant,PS2+,Redundant module

關於新巨

新巨簡介
經營團隊
企業沿革
企業組織
企業文化
經營策略
ZIPPY優勢
未來展望
全球服務據點

產品

電源產品
電源產品線上支援
開關

新聞中心

News
Events

語言

繁體中文
English

股東服務

財務資訊
公司年報
公司治理
股東專欄

人才招募

人事概況
薪資及福利
訓練與發展
應徵方式
招募流程
如何到新巨

CSR暨 利害關係人專區

企業社會責任
綠色永續
利害關係人專區
員工照顧
客戶與供應商